

tesafilm® doble cara - 57912

La cinta autoadhesiva tesafilm® es una cinta de doble cara para usos múltiples. Diseñada especialmente para pegar papel, cartón e impresiones fotográficas.

Aplicación principal

Como su nombre indica, la cinta de doble cara autoadhesiva de tesafilm® coincide con una amplia gama de aplicaciones que requieren un pegado y una fijación discretos del papel o del cartón. La cinta transparente no tiene ni PVC ni disolventes. Se compone de una hoja de polipropileno altamente resistente al paso del tiempo con una cobertura adhesiva sin disolventes en ambos lados. La cinta de tesafilm® para la oficina de doble cara invisible es realmente fina. Se presenta en un dispensador especial para una aplicación cómoda y fácil.

- Adhesivo de doble cara
- Buena adhesión
- Desenrollado práctico

Datos técnicos y Propiedades

Dimensiones	7,5 m : 12 mm
Color	Transparente
Adhesivo	Acrílico
Soporte	Película de polipropileno (PP)
Espesor	75 m
Resistencia a la tensión	58 N / cm
Almacenamiento	Alta resistencia al paso del tiempo

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Información adicional e imágenes



57912

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.