

tesa® Cinta Antideslizante - 55587

La cinta antideslizante tesa® ofrece seguridad extra en suelos que tienden a ser resbaladizos. Es ideal para escalones, rampas, escaleras, cubiertas de barcos y otras superficies resbaladizas.

Aplicación principal

La cinta antideslizante Anti-Slip Tape de tesa® es un medio inteligente y eficaz para prevenir las caídas en peldaños de escaleras, rampas, suelos resbaladizos o cascos de barcos. Ayuda a prevenir accidentes y es sinónimo de adhesión fuerte y duradera. También protege de los rayos UV y es muy resistente al agua, las temperaturas extremas y a los productos de limpieza. Un paquete contiene 5 o incluso 15 m de cinta la cual es o bien 25 o 50 mm de ancho y está disponible en tres colores. Puede cortar la cinta o rasgarla con la mano para que coincida con una situación específica.

- Tiras extremadamente fuertes y duraderas
- Adhesión muy fuerte
- Se pueden cortar a mano
- Resistentes al agua, la intemperie, los rayos ultravioleta y los productos de limpieza

Datos técnicos y Propiedades

Dimensiones	5m x 25mm
Color	Negro, transparente y amarillo fluorescente
Adhesivo	Adhesivo Acrílico
Soporte	PVC

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Información adicional e imágenes



55587

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.