

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Ink for use in felt pens

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 2; H411

Flam. Liq. 2; H225

Skin Irrit. 2; H315

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07



GHS09

Signal word

Danger

Hazardous component(s) to be indicated on label:

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

 Hydrocarbons, C7-C9, Isoalkanes
 ETHYLCYCLOHEXANE

Hazard statement(s)

 H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

Hazard statements (EU)

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statement(s)

 P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.
 P391 Collect spillage.
 P405 Store locked up.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients
3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures
Chemical characterization

Mixture (preparation)

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	Hydrocarbons, C7-C9, Isoalkanes		
	- 921-728-3 - 01-2119471305-42-0010	Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336	>= 25.00 - < 50.00 wt%
2	ETHYLCYCLOHEXANE		
	1678-91-7 216-835-0 - 01-2120769125-52-0000	Flam. Liq. 2; H225 Aquatic Chronic 2; H411 STOT SE 3; H336 Aquatic Acute 1; H400 Asp. Tox. 1; H304	>= 10.00 - < 25.00 wt%
3	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]		
	13463-67-7 236-675-5 022-006-00-2 -	Carc. 2; H351i	>= 10.00 - < 25.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
----	------	-------------------------------	------------------	--------------------

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

3	V, W, 10	-	-	-
---	----------	---	---	---

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

No	Route, target organ, concrete effect
3	H351i inhalational; -; -

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Rinse the mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO); Nitrogen oxides (NO_x); Toxic gases/vapours

5.3 Advice for firefighters

Use self-contained breathing apparatus. Cool endangered containers with water spray jet. Wear protective clothing. Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: Bases; Acids; oxidizing agents

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
List of approved workplace exposure limits (WELs) / EH40			
Titanium dioxide			
total inhalable dust			
WEL long-term (8-hr TWA reference period)		10	mg/m ³
List of approved workplace exposure limits (WELs) / EH40			
Titanium dioxide			
respirable dust			
WEL long-term (8-hr TWA reference period)		4	mg/m ³

DNEL, DMEL and PNEC values

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

PNEC values

PNEC values			
No	Substance name		CAS / EC no
	ecological compartment	Type	Value
1	ETHYLCYCLOHEXANE		1678-91-7 216-835-0
	water	fresh water	0.63 µg/L
	water	marine water	63 ng/L
	water	Aqua intermittent	6.3 µg/L
	water	fresh water sediment	0.573 mg/kg dry weight
	water	marine water sediment	57.3 µg/kg dry weight
	soil	-	0.114 mg/kg dry weight
	sewage treatment plant	-	32 mg/L

8.2 Exposure controls
Appropriate engineering controls

No data available.

Personal protective equipment
Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties
9.1 Information on basic physical and chemical properties

State of aggregation
liquid
Form/Colour
liquid
red
Odour
characteristic
pH value
No data available
Boiling point / boiling range
No data available
Melting point/freezing point
No data available

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

Decomposition temperature		
No data available		
Flash point		
Value	7	°C
Ignition temperature		
No data available		
Flammability		
No data available		
Lower explosion limit		
No data available		
Upper explosion limit		
No data available		
Vapour pressure		
No data available		
Relative vapour density		
No data available		
Relative density		
No data available		
Density		
Value	0.96	g/cm³
Reference temperature	20	°C
Solubility in water		
Comments	insoluble	
Solubility		
No data available		
Partition coefficient n-octanol/water (log value)		
No data available		
Viscosity		
Value	21.5	mm²/s
Reference temperature	40	°C
Type	kinematic	
Particle characteristics		
No data available		

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

Bases; Acids; Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C7-C9, Isoalkanes	-	921-728-3
LD50	>	2000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C7-C9, Isoalkanes	-	921-728-3
LD50	>	2000	mg/kg bodyweight
Species	rabbit		
Source	ECHA		

Acute inhalational toxicity	
No data available	

Skin corrosion/irritation	
No data available	

Serious eye damage/irritation	
No data available	

Respiratory or skin sensitisation	
No data available	

Germ cell mutagenicity	
No data available	

Reproduction toxicity	
No data available	

Carcinogenicity	
No data available	

STOT - single exposure	
No data available	

STOT - repeated exposure	
No data available	

Aspiration hazard	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure	
Inhalation of vapours may lead to headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.	

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C7-C9, Isoalkanes	-	921-728-3
LL50		18.4	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
2	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
LC50		0.75	mg/l
Duration of exposure		96	h
Species	Oryzias latipes		
Method	OECD 203		
Source	CSR		

Toxicity to fish (chronic)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C7-C9, Isoalkanes	-	921-728-3
NOELR		0.778	mg/l
Duration of exposure		28	day(s)
Species	Oncorhynchus mykiss		
Method	(Q)SAR		
Source	ECHA		

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C7-C9, Isoalkanes	-	921-728-3
EL50		appr. 2.4	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		
2	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
EC50		0.667	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	CSR		

Toxicity to Daphnia (chronic)			
No data available			

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
EC50		0.633	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	CSR		

Toxicity to algae (chronic)			
No	Substance name	CAS no.	EC no.
1	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
NOEC		0.22	mg/l
Duration of exposure		72	h
Species	Algae		

Bacteria toxicity			
No data available			

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
Value		0	%
Duration		28	day(s)
Method		OECD 301 C	
Source		CSR	
Evaluation		not readily biodegradable	

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	ETHYLCYCLOHEXANE	1678-91-7	216-835-0
BCF		474	- 839
Method		QSAR	
Source		CSR	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3
Environmentally hazardous substance mark	Symbol "fish and tree"

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT
EmS	F-E, S-E
Label	3
Marine pollutant mark	Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	E2, P5b
If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.	

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Trade name: edding Paint Marker-Ink (red) contained in: edding 750, edding 751, edding 780

Current version : 5.0.0, issued: 22.09.2021

Replaced version: 4.1.0, issued: 03.06.2019

Region: GB

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.
The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H304	May be fatal if swallowed and enters airways.
H351i	Suspected of causing cancer by inhalation.
H400	Very toxic to aquatic life.

Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

V	If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.
W	It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.
1	The concentration stated or, in the absence of such concentrations, the generic concentrations of this Regulation (Table 3.1) or the generic concentrations of Directive 1999/45/EC (Table 3.2), are the percentages by weight of the metallic element calculated with reference to the total weight of the mixture.

Creation of the safety data sheet

UMCO GmbH
Georg-Wilhelm-Str. 187, D-21107 Hamburg
Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.
The safety data sheet describes products with a view to safety requirements.
It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.
Prod-ID 25592