

## tesafilm® transparent – 04140

- Gelbliche, transparente Qualität und farblos nach Anbringung
- Starke Klebkraft
- Reißfest
- Stark alterungsbeständig
- Leises Abrollen
- Lösungsmittelfreier Kleber
- PP-Folie
- Passend für alle erhältlichen tesafilm® Abroller (10m & 33m)

## Hauptanwendung

- Einpacken von Geschenken
- Verschließen von Umschlägen
- Befestigung von Notizen, Plänen, Organisationsplänen, Postkarten, Kinderzeichnungen, etc.
- Verschließen angebrochener Lebensmittelverpackungen
- Aufhängen von Girlanden oder Dekoration an Fenstern
- Reparieren von Buchseiten und Kinderzeichnungen

## Technische Daten & Eigenschaften

<b>Dimensionen</b>	10m, 33m, 66m / 12mm, 15mm, 19mm, 25mm
<b>Produktstruktur</b>	Einseitig
<b>Farbe</b>	Gelblich transparent
<b>Klebstofftyp</b>	Acryl
<b>Adhäsion/Stahl</b>	3,2 N/cm
<b>Trägertyp</b>	Polypropylen (PP)
<b>Gesamtdicke</b>	48 µm
<b>Abrollkraft (0,3m/min)</b>	2,5 N/cm
<b>Reißfestigkeit</b>	25 N/cm
<b>Lagerzeit</b>	12 Monate nach Öffnung
<b>Feuchtigkeitsresistenz</b>	Stabil
<b>UV Resistenz</b>	Stabil

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

## Zusätzliche Informationen & Bilder



10m:12mm



10m:15mm



10m:19mm



33m:12mm



33m:15mm



33m:10mm



66m:15mm



66m:19mm



66m:25mm

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

## IBNR's

IBNR	Artikelbeschreibung
57344	2X TESAFILM TRANSPARENT 10:15, BLISTER
57401	12X TESAFILM TRANSPARENT 10:12, OFFICE BOX
57370	10X TESAFILM TRANSPARENT 10:15, OFFICE BOX
57404	8X TESAFILM TRANSPARENT 10:19, OFFICE BOX
57402	12X TESAFILM TRANSPARENT 33:12, OFFICE BOX
57371	10X TESAFILM TRANSPARENT 33:15, OFFICE BOX
57405	8X TESAFILM TRANSPARENT 33:19, OFFICE BOX
57403	12X TESAFILM TRANSPARENT 66:12, OFFICE BOX
57372	10X TESAFILM TRANSPARENT 66:15, OFFICE BOX
57406	8X TESAFILM TRANSPARENT 66:19, OFFICE BOX
57379	6X TESAFILM TRANSPARENT 66:25, OFFICE BOX
57340	1X TESAFILM TRANSPARENT 10:15, FALTSCHACHTEL
57341	1X TESAFILM TRANSPARENT 33:15, FALTSCHACHTEL
57342	1X TESAFILM TRANSPARENT 66:15, FALTSCHACHTEL

IBNR	Artikelbeschreibung
57599	2X TESAFILM TRANSPARENT 10:19 + MINI ABROLLER, ROT-BLAU, BLISTER
53908	4X TESAFILM TRANSPARENT 33:19 + SMART ABROLLER, CYAN, SHRINK
53909	4X TESAFILM TRANSPARENT 33:19 + SMART ABROLLER, PINK, SHRINK
53916	1X TESAFILM TRANSPARENT 33:19 + ORCA ABROLLER, SHRINK
53917	1X TESAFILM TRANSPARENT 10:19 + CURVE ABROLLER, FALTSCHACHTEL
53918	8X TESAFILM TRANSPARENT 33:19 + CURVE ABROLLER, SHRINK

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.