Skipper



The cord strap clips utilise a robust bungee cord to tourniquet to structures such as pillars, trees and scaffolding. The clip is available in two variants; a non-marking magnetic version which is designed to attach to angular surfaces, and a curved version to fit securely to poles and cylindrical surfaces. The cord strap clips are highly practical for indoor and warehouse environments, where they easily connect to shelving and pillars to both hold the Skipper XS unit and receive its tape end clip.

• Holds the Skipper XS unit via its connector points or receives any Skipper tape end clip

• Designed to attach to curved pillars or posts

to surfaces

• Includes a surface protector to prevent damage to the back of the pillar

• Soft pads to prevent scratching

Product Specifications

end clip

Width: 131mm Height: 105mm 5.2" 4.1"

Depth: 40mm Weight: 85g 1.6"

The curved cord strap holder/ receiver can hold the Skipper XS unit, or receive any Skipper tape

selling points

Q. What is the tourniquet cord made from?

A. The tourniquet cord is made from 8mm diameter bungee cord, which is 600mm long. It has a stopper on one end to prevent the cord from slipping though one hole.

Q. How exactly does the cord strap holder/receiver work?

A. Simply hold the clip in position on the pillar, then thread the cord through the left hole, round the pillar, then back through the right hole. Then pull the cord down to tighten. Full instructions are provided.