#### **TECHNICAL SHEET**

# CHATBOX by SILEN

### PROPERTIES

GENERAL	3 models of acoustic cabins that can accommodate 1 - 6 persons.  - CB1: 1 person standing  - CB2: up to 4 persons  - CB4: up to 6 persons  They are sold empty or equipped with a table (for versions CB2 and CB4) to be ordered with the cabin.			
EXTERIOR	<ul> <li><u>Glazed walls</u>: Sécurit acoustic transparent glass</li> <li><u>Doors</u>: Left or right opening (can be changed after installation), magnetic closure</li> <li><u>Side panels</u>: black or white metal (other colours possible, consult us)</li> </ul>			
INTERIOR	> <u>Wall</u> and ceiling Echofree recycled acoustic panels > <u>Floor</u> : Antistatic, stain-resistant fitted carpet for public spaces (standard EN 1307) > Cabin CB1 is equipped as standard with a white laminated anti-bacterial worktop H1050xL700xP300 mm, 132mm thick			
	> <u>Adjustable stabiliser feet</u> : For levelling - Adjustable from the inside			
BASE	Number of adjustable stabiliser feet			
	CB1	CB2	CB4	
	7	10	20	
ACOUSTIC	34 Db (measured on site acco	ording to standard ISO 16283-1	.)	
	> Low consumption LED with presence detector			
LIGHTING	CB1	CB2	CB4	
2.5	6.7w, 4000k, 900lm	28w, 4000k, 2240lm	56w, 4000k, 4480lm	
	> Low consumption air circulation system > Very good air circulation			
	Max consumption			
VENTILATION	CB1	CB2	CB4	
	3.4w	5.1w	10.2w	
		Air circulation		
	CB1	CB2	CB4	
	more than 22l/s (79m3/h)	more than 55l/s (198m3/h)	more than 85I/s (306m3/h)	
POWER AND CABLE MANAGEMENT	> Cabins equipped as standard with Eur, UK or CH sockets: - CB1: 1 socket + 1 USB-A (on the worktop) - CB2: 2 sockets + 2 USB-A (centred on the back wall) - CB4: 1 socket + 2 USB-A (on the side wall) > Supply cable of 3 metres with Eur, UK or CH socket			



#### **OPTIONS**

Table	To be ordered at the same time as the cabin	
	<ul> <li>&gt; Laminated board 21 mm thick - white anti-bacterial</li> <li>&gt; Black metal feet</li> <li>&gt; Central on fixed feet, for CB2 or CB4 cabins         Dimensions: H.730 x W500/1400 x D716 mm     </li> <li>&gt; Side on electrically-adjustable feet for CB2 cabin         Dimensions: H.700/1100 x W900 x D550     </li> </ul>	
Screen support arm without articulation	To be ordered at the same time as the cabin	
235/0.2 200/7.9 100/3.9 100/3.9 VESA mounting troles	For cabins CB1, CB2 or CB4 (to be ordered at the same time as the cabin)  > To support screens from 19 to 43 inches  > Vesa 75, 100 and 200  > distance between the wall and the screen: 2.3 cm  > Maximum weight supported 20 kg  > Finish: matt black	
Screen support arm with articulation		
MIN 75/3.0 - MAX 200/7.9 MAX 388/15.3 MAX 15° mm/inch VESA mounting holes	To be ordered at the same time as the cabin  For cabins CB2 or CB4 (to be ordered at the same time as the cabin)  > To support screens from 19 to 40 inches  > 180° rotation  > Vesa 75, 100 and 200  > Maximum weight supported 15 kg  > Finish: matt black	
Benches	Dimensions: Backrest height: 770 mm - Seat height: 460 mm - Depth: 620 mm - Width: 00 mm Black metal feet. Seat and backrest of fire-resistant Nevotex fabric (dark grey colour, other colours with upplement, please ask)	
Other	The cabin can be integrated with other products from the EOL range > Eloise Tables > Zelie Writing Table > Task Chairs > Bip Easy Chairs > Tom, Spoon Stool etc.	



## DIMENSIONS

CABINS (in mm)				
	CB1	CB2	CB4	
HxWxD Exteriors	2220x1000x1000	2220x2130x1030	2220x2130x1940	
M2 to the floor	1,00	2,19	4,13	
HxWxD Interiors	2040x870x980	2040x2000x930	2040x2000x1860	
Back wall	Glazed	Full	Glazed	
Number of persons	1	up to 4	up to 6	
Weight (kg)	370	550	980	
Power and cable management	1 socket + 1 USB-A	2 socket + 2USB-A	1 socket + 2USB-A	

EQUIPMENT (in mm)				
Tables				
. 65.65	For CB2 (central)	For CB4 (central)	For CB2 (side)	
Height	730		700 / 1100	
Width	500	1400	900	
Depth	716		550	
Benches				
Height	770			
Width	900			
Depth	620,00			
Seat height	460			
Seat depth	450			
Weight supported (kg)	200			

