


Product Datasheet model ultravision with faceguard 9301 555

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

**Product
characteristics**

- combination of goggle 9301105 and faceguard 9301318
- Anatomical shape and soft material allow close, yet comfortable fit
- Fits comfortably over most prescription spectacles
- Frosted top to reduce glare
- High-quality, easily adjustable headband
- Optically correct lens (EN 166 class 1) does not distort view or cause headaches
- Simple lens replacement reduces cost

| | |
|---|--|
| Technical details | |
| Frame | |
| Material | Front piece PVC |
| Features | ventilation system |
| Colour | transparent grey |
| | Headband |
| Material | synthetic headband |
| Features | adjustable |
| Colour | anthracite/lime |
| | Marking |
| Manufacturer's ID code | W |
| Applicable EN norm | 166 |
| Field of use | 3 (drops and splashes of liquid) 4 (large dust particles) |
| Impact resistance | B (120 m/s) |
| Resistance to high speed particles at extremes of temp. | T |
| Conformity symbol | CE |
| Lens | |
| Material | PC |
| Thickness | 2,2 mm at PD |
| Coating | uvex supravision excellence |
| Colour | clear |
| UV protection | UV400 |
| Replacement lens | 9301255 |

| | |
|---|---|
| Filter | Marking 2C-1,2 (DIN EN 170) |
| Manufacturer's ID code | W |
| Optical class | 1 |
| Low-energy impact | B (120 m/s) |
| Resistance to high speed particles at extremes of temp. | T |
| Surface resistance to fine particles | K |
| Antifog | N |
| Conformity symbol | CE |
| Factory symbol |  |
| Faceguard | |
| Material | PC |
| Colour | Clear |
| Article number | 9301318 |
| Marking | |
| Conformity symbol | CE |
| Miscellaneous | |
| Weight | 212 g |
| Packing | 18 pieces in one carton |
| Standards | DIN EN 166 + DIN EN 170 |
| PPE Category | Category II |