







Learn more

TEGERA® INFINITY 8810R

SUPER SOFT WINTER GLOVE, PALM DIPPED

Winter lined glove with super soft nitrile foam palm dipping for the cold season or in cool work areas. Designed for versatile work in dry to semi-dry environments. It is warm and comfortable but still soft and flexible with the high dexterity and fingertip sensitivity that is unique for an Infinity glove. Breathable materials for all day comfort. Skin friendly with Derma-test and Oeko-Tex certificate. Retail packed with descriptive hangtag to help customers with their in-store choice.

CHARACTERISTICS

- Durable
- Extra comfortable
- · Good fingertip sensitivity
- Flexible
- Warm
- Good grip

FUNCTIONS

- Withstands contact heat up to 100°C
- · Approved for handling foodstuffs

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with cold

PRIMARY ENVIRONMENTS OF USE

Dry environments, cold environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Machine operating, building and construction, carpentry, installation work, construction, transport work, machine driving, warehouse work, airport work, repair work

PRIMARY INDUSTRIES OF USE

Machinery and equipment, mro, transportation, utilities, building and construction, logistics

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cold insulation gloves, Heat protection gloves

CATEGORY Cat. II

COLLECTION Infinity

LINING Winter-lined

LINING MATERIAL Fleece, Nylon, Acrylic, Spandex, 10 gg, 15 gg

LENGTH 235-275 mm

DEXTERITY 5

GRIP DESIGN Foam grip pattern

COLOUR Black, Yellow

PAIRS PER: BUNDLE/CARTON 6/72

DISPLAY TYPE Hangtag with euro slot

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam, Waterbased PU

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

CUT RESISTANCE (EN ISO 13997) Cut resistance level A

CUT RESISTANCE (EN ISO 13997) TDM: 8N

INNER MATERIAL SPECIFICATION Acrylic

OUTER MATERIAL SPECIFICATION Nitrile, Nylon

COMPLIANCE



UK

Cat. II



TP TC 019:2011



77

EN 407:2020 (No flame protection)

EN 388:2016+A1:2018 4221A EN ISO 21420:2020









Contact heat rating valid for palm area only

FEATURES



SIZE		ARTICLE NUMBER	EAN
7	S	8810R-7	7340118370378
8	М	8810R-8	7340118370408
9	L	8810R-9	7340118370439
10	XL	8810R-10	7340118370460
11	XXL	8810R-11	7340118370491



Limavägen 28, SE-793 32 Leksand, Sweden Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com