

# 58-530W

Unique combination of grip and chemical resistance

# Abrasion-resistant chemical gloves with heightened grip, perfect for indoor application

- Enhanced grip: AlphaTec<sup>®</sup> 58-530W chemical gloves' ANSELL GRIP™ coating means less force is required when handling wet or oily components
- Elevated comfort: Their white nylon inner liner enhances comfort and offers excellent durability
- Advanced defenses: A bonded construction, whereby their coating polymer doesn't penetrate the liner in manufacture, guarantees EN 374 Type A chemical protection
- Improved durability: These AlphaTec<sup>®</sup> gloves also achieve EN level 3 and ANSI level 5 abrasion resistance levels
- Specialized protection: In addition, they offer EN 407 heat resistance, for improved workplace safety
- Augmented dexterity: AlphaTec<sup>®</sup> 58-530W industrial gloves' light 13-gauge design makes them more dexterous, for maneuverable hand protection

### **Industries**

- Automotive
- Automotive Aftermarket
- Machinery and Equipment
- Metal fabrication
- Chemical
- Oil and gas
- Food Processing

### **Applications**

- Metalworking & assembly operations
- Body painting including surface inspection
- Applying sealers, touching up
- Changing tools and dies
- Handling application & cleaning tools
- Warehousing of raw materials
- Loading and unloading trucks and vehicles
- Filling, blending and charging of raw materials
- Transferring liquids and solids
- Loading and unloading of proces equipment
- Transferring liquids and solids between vessels and tanks and process equipment
- Supervision of running operation
- Handling outgoing goods: cans, vessels, bulkpack and cartons
- Opening furnaces draining pumps valves or lines and crackers BTX process
- Food Processing







# 58-530W

Unique combination of grip and chemical resistance

### **Key Features**

- ANSELL GRIP™ Technology: Less force needed to grip wet or oily
- White nylon liner: Safety gloves with enhanced comfort and durability
- Bonded construction: Zero liner penetration, heightened dexterity

### **Vulcanization Chemical Accelerators**

• Zinc Diethyldithiocarbamate

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

## **Technologies**





### **Performance Standards**

ANSI/ISEA 105-2024















### **Specifications**

BRAND   STYLE	DESCRIPTION	SIZE	LENGT H	COLOR	PACKAGE
AlphaTec® 58- 530W	Liner Material: Nylon Coating Material: Nitrile Featured Technology: ANSELL GRIP™	7, 8, 9, 10, 11	290 / 11.4	Grey	<ul><li>6 pairs/polybag; 12 polybags/carton</li><li>Vend pack variant ,1 pair per bag,72 bags per carton</li></ul>

### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV Ansell Healthcare Europ Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Canada Ansell Canada Inc. Ansell Canada Inc. 105, rue Lauder Cowansville (Québec) J2K 2K8, Canada T: 1800 363-8340 F: 1888 267-3551 North America Region

Ansell Healthcare Products LLC 111 Wood Avenue South, Suite 210 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. Blvd. Bernardo Quintana No. 7001-C Blvd. Bernardo Quintana No. 70 Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

