



Superior nitrile grip in oily environments.
Waterproof and with chemical approval type C.

TEGERA® OIL GRIP 8853



Learn more

FULLY DIPPED AND WATERPROOF

This glove offers superior nitrile grip in oily environments. Waterproof and with chemical approval type C. Fully and triple-dipped with nitrile foam and a long cuff. The liner is knitted in 18 gg and made of over 90% recycled polyester. Additionally, the gloves feature touchscreen functionality, allowing you to handle control devices without needing to remove the gloves. Oeko-Tex approved. Withstands contact heat up to 100°C/212°F. Wide size range.

CHARACTERISTICS

- Good fingertip sensitivity
- Flexible
- Durable
- Excellent grip in oily environments
- Comfortable

FUNCTIONS

- Withstands contact heat up to 100°C
- For touchscreen
- Extra long
- Oil and grease resistant
- Windproof
- Waterproof
- Thin



PREVENTS RISK OF

Abrasion injuries, Blisters, Grazes, Scratches, lacerations, Chapping,
Contact with moisture, Contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Wet environments, Oily and greasy environments, Dirty
environments

PRIMARY AREAS OF USE

Building and construction, Installation work, Machine operating,
Mining, Repair work, Service work, Shop work, Transport work

PRIMARY INDUSTRIES OF USE

Agriculture, Mining, Oil, gas, petrochemical, Machinery and
equipment, MRO, Automotive, Transportation, Utilities, Building and
construction

TYPE OF WORK

Light weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Heat protection gloves, Precision work gloves

CATEGORY Cat. III

COLLECTION Oil Grip

KNITTING GAUGE (GG) 18

LINING MATERIAL Recycled polyester

LENGTH 250-285 mm

DEXTERITY 5

GRIP DESIGN Foam grip pattern

COLOUR Black

PAIRS PER: BUNDLE/CARTON 6/72

DISPLAY TYPE Bulk pack

DIPPING Fully dipped

DIPPING MATERIAL Nitrile, Nitrile foam

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

INNER MATERIAL SPECIFICATION Recycled polyester

OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE



TP TC 019:2011

CE2777

EN ISO 21420:2020

EAC

EN
388:2016+A1:2018
4111X



EN 407:2020 (No
flame protection)
X1XXXX

EN 511 cl. 4.3 Water
penetration
(ISO 15383): Pass



EN ISO 374-
1:2016/A1:2018 Type
C



Contact heat rating valid for palm area only

Note: This product needs a few minutes of oil contact to activate
the oil grip.

FEATURES



For touchscreen



Waterproof



Windproof

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	J
Permeation level	4
Degradation %	11.1

SIZE		ARTICLE NUMBER	EAN
10	XL	8853-10	7340118472263
11	XXL	8853-11	7340118472416
12	3XL	8853-12	7340118472560
6	XS	8853-6	7340118471662
7	S	8853-7	7340118471815
8	M	8853-8	7340118471969
9	L	8853-9	7340118472119

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com