



TEGERA® INFINITY 8805R



Learn more

SUPER SOFT, PALM DIPPED, CUT B GLOVE

Dexterous cut resistant glove, level B, with touchscreen function. Ultra-light thanks to 18 gg knitted with CRF® cut resistant technology. Palm dipped with super soft nitrile foam that provides excellent grip on dry surfaces. Reinforced thumb crotch for improved longevity. Suitable for precision work. Breathable materials for all day comfort. Protection against contact heat up to 100°C/212°F. Wide range of sizes means a perfectly fitting glove for everyone. Skin friendly with Derma-test and Oeko-Tex certificate. Retail packed with descriptive hangtag to help customers with their in-store choice.

CHARACTERISTICS

- Good fingertip sensitivity
- Flexible
- Durable
- Good grip
- Extra comfortable

FUNCTIONS

- Withstands contact heat up to 100°C
- Approved for handling foodstuffs
- For touchscreen
- Reinforcement between index finger and thumb
- Thin



PREVENTS RISK OF

Cut injuries, Abrasion injuries, Blisters, Grazes, Scratches, lacerations, Contact with dirt, Drying out, Chapping

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, Dry environments, Moist environments, Dirty environments

PRIMARY AREAS OF USE

Fine assembly, Assembly, Machine operating, Building and construction, Carpentry, Painting, Installation work, HVAC installation, Sheet-metal work, Engineering, Transport work, Machine driving, Warehouse work, Airport work, Metalwork, Glass industry work, Repair work, Paper industry work, Service work, Shop work

PRIMARY INDUSTRIES OF USE

Agriculture, forestry and fishing, Basic metals manufacturing, Building and construction, Electricity and gas supply, Facility management services, Glass, ceramics and construction materials, Public safety, security and defence, Pulp and paper, Retail and wholesale, Transportation and logistics, Warehousing

TYPE OF WORK

Light weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

COLLECTION Infinity

KNITTING GAUGE (GG) 18

LINING MATERIAL Carbon, CRF® Technology, HPPE, Nylon, Stainless steel fibre yarn

LENGTH 220-270 mm

DEXTERITY 5

GRIP DESIGN Foam grip pattern

COLOUR Grey

PAIRS PER: BUNDLE/CARTON 6/72

DISPLAY TYPE Hangtag with euro slot

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam, Waterbased PU

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) TDM: 9N

INNER MATERIAL SPECIFICATION Nylon, HPPE (High performance polyethylene), Stainless steel fibre yarn, Carbon thread

OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE



Cat. II

TP TC 019:2011



Cat. II

EN ISO 21420:2020



EN 388:2016+A1:2018 4X42B



EN 407:2020 (No flame protection) X1XXXX



Contact heat rating valid for palm area only

FEATURES



Cut protection



For touchscreen

SIZE		ARTICLE NUMBER	EAN
6	XS	8805R-6	7340118369204
7	S	8805R-7	7340118369297
8	M	8805R-8	7340118369389
9	L	8805R-9	7340118369471
10	XL	8805R-10	7340118369563
11	XXL	8805R-11	7340118369655

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com