

Ergonomically designed to reduce hand fatigue

- Designed with ERGOFORM Technology to reduce hand fatigue, enabling workers to exert less muscle effort and increase productivity
- ERGOFORM Design Technology delivers ergonomic fit and superior comfort
- Unparalleled sensitivity versus most other examination gloves
- Up to 60% stronger than leading nitrile brands and up to 90% stronger than leading latex brands
- Offers confident protection from pinholes and other quality issues with extremely low 0.65% acceptable quality limits (AQL)



Industries

- Automotive
- Dental
- Healthcare
- Industrial Safety
- Laboratory
- Manufacturing
- Tattoo Artists

Applications

- Analytical testing
- Biotechnologies
- Dairy & food processing
- Intricate parts handling
- Laboratory analysis and testing
- Light assembly tasks
- Light duty maintenance
- Paint and spray shops
- Patient examinations
- Pharmaceutical manufacturing
- Preparing pharmaceutical products
- Protection from blood and other bodily fluids

TECHNICAL DATA SHEET

PRODUCT INFORMATION

	XCEED®
Material	Nitrile
Color	Blue
Glove Design	Ambidextrous, Powder-Free, Chlorinated, Textured Fingers
Cuff	Beaded Cuff
Manufacturing/ QMS Audit Standards	ISO 13485
Regulatory/Standards Compliance	MDD 93/42/EEC, PPED 89/686/EEC CATEGORY III, COMPLEX DESIGN, EN 455 1,2 AND 3, EN374-3, EN374-2 LEVEL 3 AQL .65, ASTM D6319, EN420 (SIZING FOR SPECIAL PURPOSES), REACH COMPLIANT, TGA, US QSR/FDA 510(K)
* Packaging	250 gloves per dispenser, 10 dispensers per shipper carton, 2500 gloves per shipper carton.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia
User needs Segment	High Touch Glove - Ultra-thin gloves that provide the highest level of tactile sensitivity, especially at the fingertip.

*XL contains 230 gloves/box

PHYSICAL PROPERTIES

	TYPICAL VALUES					TESTING METHOD
	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	
Length (mm/in.)	240/9.5	240/9.5	240/9.5	240/9.5	240/9.5	ASTM D3767/EN 420
Average Palm Width (mm/in.)	80/3.14	86/3.38	96/3.77	107/4.21	115/4.52	
Freedom from Holes (Inspection level I)	0.65 AQL					ASTM D5151/EN 374-2
Palm Thickness Single Wall	mm : 0.07 / mil : 2.8					ASTM D3767/EN 420
	BEFORE AGING		AFTER AGING			
Ultimate Tensile Strength	33 MPa		31 MPa			ASTM D 412-06a
Elongation at Break (%)	> 500		> 400			ASTM D 412-06a
Force at break (N)	7		7			EN 455-2

ORDERING INFORMATION

	SIZE	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL
XCEED®	REORDER NO.	XC-310-XS	XC-310-S	XC-310-M	XC-310-L	XC-310-XL

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa

Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
+32 2 528 74 00
+32 2 528 74 01

Asia Pacific

Ansell Global Trading Center
(Malaysia) Sdn Bhd
Prima 6, Prima Avenue
Block 3512, Jalan Teknokrat 6
63000 Cyberjaya
Selangor, Malaysia
T: +60 3 83106688
F: +60 3 8318 6699

North America

Ansell Healthcare Products LLC
111 Wood Avenue South
Suite 210
Iselin, NJ 08830, USA
+1 800 800 0444
+1 800 800 0445

Latin America & Caribbean

Ansell Brazil Ltda.
Rua das Figueiras 474 - 4º Andar
Bairro Jardim
SP 09080-300 Santo André
Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100

Australia

Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
+61 1800 337 041
+61 1800 803 578


Russia

Анселл РУС
123610 Россия, Москва
Краснопресненская
Наб. 12, п.3, оф. 1304А
Тел. +7 495 258 13 16

Technology



Regulatory Compliance



Performance Standards

