

**Trade name:** edding permanent ink (red) contained in: edding 300, edding 330

**Current version :** 3.2.0, issued: 19.03.2018

**Replaced version:** 3.1.0, issued: 06.06.2016

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding permanent ink (red) contained in: edding 300, edding 330**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Refill ink

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Flam. Liq. 2; H225

STOT SE 3; H336

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



GHS02



GHS07

**Signal word**

Danger

**Hazardous component(s) to be indicated on label:**

1-methoxy-2-propanol

**Hazard statement(s)**

H225

Highly flammable liquid and vapour.

H336

May cause drowsiness or dizziness.

**Trade name:** edding permanent ink (red) contained in: edding 300, edding 330

**Current version :** 3.2.0, issued: 19.03.2018

**Replaced version:** 3.1.0, issued: 06.06.2016

**Region:** GB

#### Precautionary statement(s)

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P370+P378	In case of fire: Use water spray, extinguishing powder, foam or CO <sub>2</sub> to extinguish.
P405	Store locked up.
P501	Dispose of contents/container to a facility in accordance with local and national regulations.

#### 2.3 Other hazards

No data available.

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable. The product is not a substance.

#### 3.2 Mixtures

##### Chemical characterization

Mixture (preparation)

##### Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	<b>ethanol</b>		
	64-17-5 200-578-6 603-002-00-5 -	Flam. Liq. 2; H225	> 50.00 - < 70.00 %-b.w.
2	<b>1-methoxy-2-propanol</b>		
	107-98-2 203-539-1 603-064-00-3 -	Flam. Liq. 3; H226 STOT SE 3; H336	> 25.00 - < 30.00 %-b.w.

Full Text for all H-phrases and EUH-phrases: pls. see section 16

#### 3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

##### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

##### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners.

##### After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

##### After ingestion

Rinse mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

**Trade name:** edding permanent ink (red) contained in: edding 300, edding 330

**Current version :** 3.2.0, issued: 19.03.2018

**Replaced version:** 3.1.0, issued: 06.06.2016

**Region:** GB

#### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

##### Unsuitable extinguishing media

High power water jet

#### 5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

#### 5.3 Advice for firefighters

Use self-contained breathing apparatus. Cool endangered containers with water spray jet. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

##### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

#### 6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

#### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

#### 6.4 Reference to other sections

No data available.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

##### Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far as possible by the state of the art.

##### General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

##### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

**Trade name:** edding permanent ink (red) contained in: edding 300, edding 330

**Current version :** 3.2.0, issued: 19.03.2018

**Replaced version:** 3.1.0, issued: 06.06.2016

**Region:** GB

### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

### Advice on storage assembly

Do not store together with: Acids; Alkalis; Oxidizing agents

### 7.3 Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
Ethanol			
	TWA	1920	mg/m <sup>3</sup> 1000 ml/m <sup>3</sup>
2	1-methoxy-2-propanol	107-98-2	203-539-1
<b>List of approved workplace exposure limits (WELs) / EH40</b>			
1-Methoxypropan-2-ol			
	STEL	560	mg/m <sup>3</sup> 150 ml/m <sup>3</sup>
	TWA	375	mg/m <sup>3</sup> 100 ml/m <sup>3</sup>
	Skin resorption / sensibilisation	Sk	
<b>2000/39/EC</b>			
1-Methoxypropanol-2			
	STEL	568	mg/m <sup>3</sup> 150 ppm
	TWA	375	mg/m <sup>3</sup> 100 ppm
	Skin resorption / sensibilisation	Skin	

### 8.2 Exposure controls

#### Appropriate engineering controls

No data available.

#### Personal protective equipment

##### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

##### Eye / face protection

Safety glasses with side protection shield (EN 166)

##### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness		0.5	mm
Breakthrough time	>	240	min

##### Other

Normal chemical work clothing.

#### Environmental exposure controls

No data available.

Trade name: edding permanent ink (red) contained in: edding 300, edding 330

Current version : 3.2.0, issued: 19.03.2018

Replaced version: 3.1.0, issued: 06.06.2016

Region: GB

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>Form/Colour</b>			
liquid			
red			
<b>Odour</b>			
characteristic			
<b>Odour threshold</b>			
No data available			
<b>pH value</b>			
No data available			
<b>Boiling point / boiling range</b>			
Value	>	70	°C
Reference pressure		1013	hPa
<b>Melting point / melting range</b>			
No data available			
<b>Decomposition point / decomposition range</b>			
No data available			
<b>Flash point</b>			
Value		18 - 21	°C
<b>Auto-ignition temperature</b>			
No data available			
<b>Oxidising properties</b>			
No data available			
<b>Explosive properties</b>			
No data available			
<b>Flammability (solid, gas)</b>			
No data available			
<b>Lower flammability or explosive limits</b>			
No data available			
<b>Upper flammability or explosive limits</b>			
No data available			
<b>Vapour pressure</b>			
Value	<	110	kPa
Reference temperature		50	°C
<b>Vapour density</b>			
No data available			
<b>Evaporation rate</b>			
No data available			
<b>Relative density</b>			
No data available			
<b>Density</b>			
Value		0.80 - 1.20	g/cm <sup>3</sup>
Reference temperature		20	°C

**Trade name:** edding permanent ink (red) contained in: edding 300, edding 330

**Current version :** 3.2.0, issued: 19.03.2018

**Replaced version:** 3.1.0, issued: 06.06.2016

**Region:** GB

<b>Solubility in water</b>	
No data available	
<b>Solubility(ies)</b>	
No data available	
<b>Partition coefficient: n-octanol/water</b>	
No data available	
<b>Viscosity</b>	
Value	12 - 80 sec
Reference temperature	20 °C
Type	Efflux time
Method	DIN cup 4 mm
<b>Solvent separation test</b>	
Value	< 3 %

## 9.2 Other information

<b>Other information</b>
The physical data is that of the main component/s.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

### 10.3 Possibility of hazardous reactions

No data available.

### 10.4 Conditions to avoid

No data available.

### 10.5 Incompatible materials

Acids; Alkalis; Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

<b>Acute oral toxicity</b>			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LD50		6200	mg/kg bodyweight
Species	rat		
Source	Manufacturer		
2	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		5660	mg/kg bodyweight
Species	rat		
Source	Manufacturer		
<b>Acute dermal toxicity</b>			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		9999.99	mg/kg bodyweight
Species	rabbit		
Source	Manufacturer		

**Trade name:** edding permanent ink (red) contained in: edding 300, edding 330

**Current version :** 3.2.0, issued: 19.03.2018

**Replaced version:** 3.1.0, issued: 06.06.2016

**Region:** GB

<b>Acute inhalational toxicity</b>
No data available
<b>Skin corrosion/irritation</b>
No data available
<b>Serious eye damage/irritation</b>
No data available
<b>Respiratory or skin sensitisation</b>
No data available
<b>Germ cell mutagenicity</b>
No data available
<b>Reproduction toxicity</b>
No data available
<b>Carcinogenicity</b>
No data available
<b>STOT - single exposure</b>
No data available
<b>STOT - repeated exposure</b>
No data available
<b>Aspiration hazard</b>
No data available
<b>Delayed and immediate effects as well as chronic effects from short and long-term exposure</b>
Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.

## SECTION 12: Ecological information

### 12.1 Toxicity

<b>Toxicity to fish (acute)</b>			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LC50		8150	mg/l
Duration of exposure		96	h
Species	Leuciscus idus		
Source	Manufacturer		
<b>Toxicity to fish (chronic)</b>			
No data available			
<b>Toxicity to Daphnia (acute)</b>			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
EC50		9268 - 14221	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	Manufacturer		

**Trade name:** edding permanent ink (red) contained in: edding 300, edding 330

**Current version :** 3.2.0, issued: 19.03.2018

**Replaced version:** 3.1.0, issued: 06.06.2016

**Region:** GB

<b>Toxicity to Daphnia (chronic)</b>
No data available
<b>Toxicity to algae (acute)</b>
No data available
<b>Toxicity to algae (chronic)</b>
No data available
<b>Bacteria toxicity</b>
No data available

## 12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Value			%
Source		Manufacturer	
Evaluation		readily biodegradable	

## 12.3 Bioaccumulative potential

No data available.

## 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

No data available.

## 12.6 Other adverse effects

No data available.

## 12.7 Other information

<b>Other information</b>
Do not discharge product unmonitored into the environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

#### Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

## SECTION 14: Transport information

### 14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT RELATED MATERIAL
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3



**Trade name:** edding permanent ink (red) contained in: edding 300, edding 330

**Current version :** 3.2.0, issued: 19.03.2018

**Replaced version:** 3.1.0, issued: 06.06.2016

**Region:** GB

#### 14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT RELATED MATERIAL
EmS	F-E, S-E
Label	3

#### 14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint related material
Label	3

#### 14.4 Other information

No data available.

#### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

#### 14.6 Special precautions for user

No data available.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulations

##### **Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

##### **REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

##### **Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, PREPARATIONS AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annexe XVII.	No 3, 40
---	----------

##### **Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category:	P5b
--	-----

#### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

### SECTION 16: Other information

#### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

---

**Trade name:** edding permanent ink (red) contained in: edding 300, edding 330

**Current version :** 3.2.0, issued: 19.03.2018

**Replaced version:** 3.1.0, issued: 06.06.2016

**Region:** GB

---

**Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

H226 Flammable liquid and vapour.

**Department issuing safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: [umco@umco.de](mailto:umco@umco.de)

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 19261