

Temp-Dex 720

DESCRIPTION AND GENERAL PROPERTIES

- Material Nitrile
- Length (cm) 23 - 28
- Wrist Knitted wrist
- Colour/Color Orange
- Interior finish Knitted thermal protection
- Exterior finish Dots
- Size / EAN 7 9 11
- Packaging 1 pair/bag - 12 /bag - 72 pairs/carton
- Complementary information Guaranteed without silicone.
Guaranteed without DMF



PERFORMANCE RESULTS

Certification category 2



X2XXXX



4343
ISO 13997 :
10,2 N (970 g)

ISO 13997 defines the weight on the blade required to cut in a single movement.

Data was obtained according to ISO 13997, from the average of several measurements. As individual specimens will obviously have greater or lesser cut resistance than the average, so this result can provide only a general indication of the cut resistance of any protective material.

Legends



MECHANICAL HAZARDS EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
Puncture resistance
Tear resistance
Blade cut resistance
Abrasion resistance



LOW CHEMICAL PROTECTION EN 374



MICRO-ORGANISMS EN 374



RADIOACTIVE CONTAMINATION EN 421



HEAT AND FIRE EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
Resistance to large quantities of molten metal
Resistance to small drops of molten metal
Radiant heat resistant
Convective heat resistance
Contact heat resistance
Burning behaviour



SPECIFIC CHEMICAL PROTECTION EN 374

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1
Water permeability
Contact cold resistance
Convective cold resistance

For more details: www.mapa-pro.com

DESCRIPTION AND GENERAL PROPERTIES

- Special nitrile Grip coating facilitates work in moderately oily environments
- Knitted aramide fibres ensures protection from cuts
- Comfort and insulation of the interior terry-cloth
- Excellent abrasion resistance: superior durability

MAIN FIELDS OF USE

Rubber industry

- Vulcanization, demoulding, forming, etc.

Other industries

- Handling of moulds in the ceramic industry
- Handling of hot steel after welding
- Handling of hot piping

Mechanical industry

- Working with hot, sharp and oily parts

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- It is not recommended for persons sensitized to dithiocarbamates and to natural latex (wrist with elastic natural rubber)
- Do not use in direct contact with a flame, these gloves should not be used near moving machinery, risk of being caught
- Put the gloves on dry, clean hands.
- Ensure the inside of the gloves is dry before putting them on again.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

Store the glove in their original packaging protected from heat, light and humidity.

Laundering conditions

Caution: improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

Food contact US

FDA 21CFR 177.2600

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0075/014/162/07/12/0580

- Issued by the notified body nr

0075

C.T.C. – rue H. FRENKEL - F-69367 LYON CEDEX 07