HyFlex® 11-618

TECHNICAL DATASHEET

Multi-purpose

Print date 28-01-2019

Glove material

- Polyurethane (Coating material)
- Nylon (Liner material)

Possible Harmful ingredients

Sensitizers

Natural rubber proteins

Only a very small number of users may be sensitised to this ingredient in the glove and hence may develop irritant and/or allergic contact reactions.

Reach Regulation 1907/2006

For more information, please consult the REACH statement on the Ansell website

Properties

- Superior comfort; no seams on the inside of the gloves
- Superior flexibility and finger dexterity

EN Test Data

	а	b	С	d	е	f
EN388:2003	3	1	2	1		
EN388:2016	3	1	2	1	Х	

European conformity

Gloves conform to the requirements of the European Directive 89/686/EEC and to the European standards EN 420:2003 + A1:2009 and EN 388:2003.

They are categorised in "Intermediate Design" (= Protection against intermediate risks).

EC-Type Examination Certificate for the final product by Centexbel

Technologiepark 7

B-9052 Zwijnaarde

Application - Limitations of use

Do not use against chemicals; the glove is not liquidproof Do not use against flames or temperatures < - 25°C or > 100°C Do not use for heavy duty mechanical applications Hand protection - light duty applications.

Storage

Keep away from sources of ozone or ignition.
Keep out of direct sunlight; store in a cool and dry place.

Construction	Liner material	Gauge	Coating material	Finishing	Cuff style	Colour	EN Sizes	Length (mm)	Packaging
Knitted	Nylon	18	Polyurethane	Palm coated	Knitwrist	Black and	6,7,8,9,10,11	195 - 245	12 pairs in a bag; 12
						dark blue			bags in a carton

The length of the gloves is below the EN requirements for total minimum glove length. Hence, the glove is called 'Fit for special purpose'

