

# uvex

SAFETY  
EYEWEAR

03.08.2015  
SBU-E-PGM-PM

## Product Datasheet model ultrasonic 9302 285



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

|                                |  |
|--------------------------------|--|
| <b>Product characteristics</b> | <ul style="list-style-type: none"><li>* Panoramic lens shape allows 180° uninterrupted lateral vision</li><li>* Medium-energy impact 'B' (120 m/s)</li><li>* Integrated, indirect ventilation allows air movement directly across the lens</li><li>* Fits comfortably over most prescription spectacles</li><li>* Simple lens replacement</li><li>* High-quality, easily adjustable headband</li></ul> |
| <b>Technical details</b>       |  |
| <b>Frame</b>                   |  |
| Material                       | <b>Front piece</b><br>PP/TPE   |
| Colour                         | black/grey   |
| Material                       | <b>Headband</b><br>synthetic headband  |
| Features                       | individually adjustable  |
| Colour                         | grey/black   |

|                                      |  |
|--------------------------------------|--|
| Manufacturer's ID code               | <b>Marking</b><br>W  |
| Applicable EN norm                   | 166  |
| Field of use                         | 3 (drops and splashes of liquid)<br>4 (large dust particles)<br>9 (molten material and hot solids) |
| Low-energy impact                    | B (120 m/s)  |
| Tested acc. to DIN                   | DIN  |
| No. of certificat. body              | 0196   |
| Conformity symbol                    | CE   |
| <b>Lens</b>                          |  |
| Material                             | PC   |
| Thickness                            | 2,2 mm   |
| Coating                              | supravision HC-AF  |
| Colour                               | clear  |
| <b>Marking</b>                       |  |
| Filter                               | 2-1,2 (DIN EN 170)   |
| Manufacturer's ID code               | W  |
| Optical class                        | 1  |
| Low-energy impact                    | B (120 m/s)  |
| Field of use                         | 9 (molten material and hot solids)   |
| Surface resistance to fine particles | K  |
| Antifog                              | N  |
| Tested acc. to DIN                   | DIN  |
| Conformity symbol                    | CE   |
| <b>Miscellaneous</b>                 |  |
| Weight                               | 80 g   |
| Packing                              | 4 goggles per box<br>72 pieces in one carton   |
| Standards                            | DIN EN 166 + DIN EN 170  |