Lyreco Solvent Based Correction Fluid

Version No: 2.1.1.1

Safety Data Sheet (Conforms to Regulations (EC) No 2015/830)

Issue Date: 05/10/2016 Print Date: 06/10/2021 Initial Date: Not Available S.REACH.GBR.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1.Product Identifier

1.1.Froduct identifier	
Product name	Lyreco Solvent Based Correction Fluid
Synonyms	Not Available
Proper shipping name	PAINT or PAINT RELATED MATERIAL
Other means of identification	Not Available
1.2.Relevant identified	uses of the substance or mixture and uses advised against
Relevant identified uses	Correction fluid for paper or fax copies.
Uses advised against	Not Applicable
1.3.Details of the supp	lier of the safety data sheet
Registered company name	LYRECO SWITZERLAND
Address	Kehrstrasse 10, 5606 Dintikon, Switzerland
Telephone	+41 566 16 5054
Fax	Not Available
Website	Not Available
Email	msds@lyreco.com
Association / Organisation	Not Available
Emergency telephone numbers	Tox Info Suisse – 24hr – Tel: 145
Other emergency telephone numbers	Not Available
SECTION 2 HAZARDS	IDENTIFICATION

2.1.Classification of the substance or mixture

Considered a dangerous mixture according to Directive 1999/45/EC, Reg. (EC) No 1272/2008 (if applicable) and their amendments. Classified as Dangerous Goods for transport purposes.

DSD classification	In case of mixtures, classification has been prepared by following DPD (Directive 1999/45/EC) and CLP Regulation (EC) No 1272/2008 regulations		
DPD classification [1]	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
	R65	HARMFUL-May cause lung damage if swallowed.	
	R22	Harmful if swallowed.	
	R11	Highly flammable.	

¹.4.Emergency telephone number

Lyreco Solvent Based Correction Fluid Page 2 of 15

Issue Date: 05/10/2016 Print Date: 06/10/2021

Legend:	1.Classification drawn from EC Directive 67/548/EEC - Annex I ; 2. Classification drawn from EC Directive 1272/2008 - Annex VI
Classification according to regulation (EC) No	Flammable Liquid Category 2, Acute Toxicity (Oral) Category 4, Aspiration Hazard Category 1, Chronic Aquatic Hazard Category 2
1272/2008 [CLP] ^[1]	
Legend:	1.Classification drawn from EC Directive 67/548/EEC - Annex I ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
2.2. Label elements	
CLP label elements	
SIGNAL WORD	DANGER
Hazard statement(s)	

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H315	May cause skin irritation
H411	Toxic to aquatic life with long lasting effects

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

P241	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P273	Avoid release into the environment.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider
P302+P352	If on the skin wash with plenty of soap and water.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
Precautionary statement(s) Storage	

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

2.3. Other hazards

REACh - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1.Substances

See 'Composition on ingredients' in Section 3.2

Lyreco Solvent Based Correction Fluid Page 3 of 15

3.2.Mixtures

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to directive 67/548/EEC [DSD]	Classification according to regulation (EC) No 1272/2008 [CLP]
1.64741-84-0 2.265-086-6 3.649-278-00-0 4.01-2119485160-44- XXXX, 01-2119488738-16-XXXX, 01-211948860-35-XXXX	<45	naphtha petroleum, light solvent-refined	R45, R46, R65 ^[2]	Carc. 1B, Muta. 1B, Asp. Tox. 1; H350, H340 ^[3]
1.13463-67-7 2.215-280-1, 215-282-2, 236-675-5 3.Not Available 4.01-2119954396-27- XXXX, 01-2119489379-17-XXXX	<15	titanium dioxide	R49 ^[1]	Carcinogen Category 1A; H350i ^[1]
1.471-34-1 2.215-279-6, 207-439-9 3.Not Available 4.01-2119486795-18-XXXX	<35	calcium carbonate	R37/38, R41 ^[1]	Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, STOT - SE (Resp. Irr.) Category 3; H315, H318, H335 ^[1]
Legend:		on drawn from EC Directiv on drawn from C&L	/e 67/548/EEC - Annex I ; 2. Cla	ssification drawn from EC Directive 1272/2008 - Anne x VI 4

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures

	► If swallowed do NOT induce vomiting.
	If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
	► Observe the patient carefully.
	▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
	• Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
	▶ Seek medical advice.
	► Avoid giving milk or oils.
	▶ Avoid giving alcohol.
General	▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.
	 Other measures are usually unnecessary. If this product comes in contact with the eyes:
	► Wash out immediately with fresh running water.
	• Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
	Seek medical attention without delay; if pain persists or recurs seek medical attention.
	Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If skin or hair contact occurs:
	▶ Flush skin and hair with running water (and soap if available).
	Seek medical attention in event of irritation.
	If this product comes in contact with the eyes:
	► Wash out immediately with fresh running water.
Eye Contact	Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
	▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.
	▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Lyreco Solvent Based Correction Fluid Page 4 of 15

	Print Date. 001020
	If skin or hair contact occurs:
Skin Contact	▶ Flush skin and hair with running water (and soap if available).
	► Seek medical attention in event of irritation.
Inhalation	▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.
	► Other measures are usually unnecessary.
	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent
	aspiration. ▶ Observe the patient carefully.
Ingestion	▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
	▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
	▶ Seek medical advice.
	▶ Avoid giving milk or oils.
	▶ Avoid giving alcohol.
4.2 Most important syr	nptoms and effects, both acute and delayed
	See Section 11

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours. Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

5.1. Extinguishing media Foam. Dry chemical powder. • BCF (where regulations permit). Carbon dioxide. Water spray or fog - Large fires only. 5.2. Special hazards arising from the substrate or mixture Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result **Fire Incompatibility** 5.3. Advice for firefighters Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. **Fire Fighting** • Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water course. • Consider evacuation (or protect in place). Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat, flame and/or oxidisers. **Fire/Explosion Hazard** ▶ Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). **SECTION 6 ACCIDENTAL RELEASE MEASURES**

6.1. Personal precautions, protective equipment and emergency procedures

Lyreco Solvent Based Correction Fluid Page 5 of 15

6.2. Environmental precautions

	See section 12	
6.3. Methods and material for containment and cleaning up		
Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb small quantities with vermiculite or other absorbent material. 	
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. 	
6.4. Reference to other	r sections	
	Personal Protective Equipment advice is contained in Section 8 of the SDS.	

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling	 Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs.
	▶ Use in a well-ventilated area.
Fire and explosion protection	See section 5
Other information	 Store in original containers in approved flame-proof area. No smoking, naked lights, heat or ignition sources. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. Keep containers securely sealed. Store away from incompatible materials in a cool, dry well ventilated area.
7.2. Conditions for saf	e storage, including any incompatibilities
Suitable container	 Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid. Check that containers are clearly labelled and free from leaks.
Storage incompatibility	► Avoid reaction with oxidising agents

7.3. Specific end use(s)

See section 1.2

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL)

Not Available

PREDICTED NO EFFECT LEVEL (PNEC)

Not Available

- OCCUPATIONAL EXPOSURE LIMITS (OEL)
- INGREDIENT DATA

Lyreco Solvent Based Correction Fluid Page 6 of 15

Issue Date: 05/10/2016

		Page 6 of 15						Issue D	Date: 05/10/201
								Print	Date: 06/10/2
Source	Ingredient Material name			TWA		STEL	Peak	k	Notes
UK Workplace Exposure Limits (WELs)	titanium dioxide	Ŭ		0	Not Available	Not Avail	lable	Not Available	
UK Workplace Exposure Limits (WELs)	Calcium carbonate inhalable / Calcium carbonate calcium carbonate / Limestone total inhalable / Limestone carbonate respirable / Marble total inhalable / Marble respirable			10 m / 4 m	g/m3 ig/m3	Not Available	Not Avail	lable	Not Available
MERGENCY LIMITS	1	·							
Ingredient	Material name		TEEL	TEEL-1 TEEL-2		TEEL-2	TEEL-3		
titanium dioxide	Titanium oxide;	(Titanium dioxide)	10 mg	10 mg/m3		10 mg/m3 10 mg/m3		n3	
calcium carbonate	Limestone; (Cal	cium carbonate; Dolomite)	27 mg	/m3		27 mg/m3	27 mg/m3 1300 mg/m3		g/m3
calcium carbonate	Carbonic acid, c	alcium salt	45 mg	/m3		210 mg/m3 1300 mg/m3		g/m3	
Ingredient	Original IDLH				Revise	d IDLH			
naphtha petroleum, light solvent-refined	Not Available				Not Ava	ailable			
titanium dioxide	N.E. mg/m3 / N.	E. ppm			5,000 n	ng/m3			
calcium carbonate	Not Available				Not Ava	ailable			
2. Exposure controls	5								
8.2.1. Appropriate engineering controls	Broose control	of engineering controls are: s which involve changing the way a job activity or p	rocess is o	done to	reduce	the risk.			
	Enclosure and/c	r isolation of emission source which keeps a selec ds" and "removes" air in the work environment. Ve		"physi	ically" av	way from the wo			
8.2.2. Personal protection	Enclosure and/c			"physi	ically" av	way from the wo			
8.2.2. Personal	 Enclosure and/c strategically "ad Safety glass goggles. Contact lens describing th lens absorp Medical and 	ds" and "removes" air in the work environment. Ver the work environment of the work environment. Ver es with side shields, Chemical es may pose a special hazard; soft contact lenses of he wearing of lenses or restrictions on use, should ion and adsorption for the class of chemicals in use first-aid personnel should be trained in their remov	nay absor pe created and an a	b and o for ea ccount	ically" av ove or di concentri ich work t of injurg	way from the wo ilute an air conta rate irritants. A v place or task. T y experience.	aminant written p 'his shou	t if design	ed properly.
8.2.2. Personal protection Eye and face protection	 Enclosure and/c strategically "ad Safety glass goggles. Contact lens describing the lens absorption 	ds" and "removes" air in the work environment. Ver the work environment of the work environment. Ver es with side shields, Chemical es may pose a special hazard; soft contact lenses of he wearing of lenses or restrictions on use, should ion and adsorption for the class of chemicals in use first-aid personnel should be trained in their remov	nay absor pe created and an a	b and o for ea ccount	ically" av ove or di concentri ich work t of injurg	way from the wo ilute an air conta rate irritants. A v place or task. T y experience.	aminant written p 'his shou	t if design	ed properly.
8.2.2. Personal protection Eye and face protection	 Enclosure and/c strategically "ad Strategically "ad Safety glass goggles. Contact lens describing th lens absorp Medical and See Hand prote Wear chemic Wear chemic Wear safety The selection of to manufacturer advance and has The exact break when making a 	ds" and "removes" air in the work environment. Ver ds" and "removes" air in the work environment. Ver es with side shields • Chemical es may pose a special hazard; soft contact lenses the ne wearing of lenses or restrictions on use, should ion and adsorption for the class of chemicals in use first-aid personnel should be trained in their remover ction below train protective gloves, e.g. PVC. footwear or safety gumboots, e.g. Rubber suitable gloves does not only depend on the mater . Where the chemical is a preparation of several su s therefore to be checked prior to the application. . through time for substances has to be obtained from final choice.	nay absor pe created a and an a al and suit ial, but als bstances,	b and d for ea ccount table e	concenti concenti ch work t of injury quipmer	way from the wo ilute an air conta rate irritants. A v place or task. T y experience. nt should be rea arks of quality v of the glove ma	written p 'his shou adily ava which va aterial ca	bolicy doo uld incluc ailable.	cument, le a review of nanufacturer
8.2.2. Personal protection Eye and face protection Skin protection Hands/feet protection	 Enclosure and/c strategically "ad Strategically "ad Safety glass goggles. Contact lens describing the lens absorp Medical and See Hand prote Wear chemic Wear safety The selection of to manufacturer advance and has The exact break when making a Suitability and d 	ds" and "removes" air in the work environment. Ver ds" and "removes" air in the work environment. Ver es with side shields • Chemical es may pose a special hazard; soft contact lenses in the wearing of lenses or restrictions on use, should ion and adsorption for the class of chemicals in use first-aid personnel should be trained in their removing ction below al protective gloves, e.g. PVC. footwear or safety gumboots, e.g. Rubber suitable gloves does not only depend on the mater . Where the chemical is a preparation of several su is therefore to be checked prior to the application. . through time for substances has to be obtained fro final choice. urability of glove type is dependent on usage.	nay absor pe created a and an a al and suit ial, but als bstances,	b and d for ea ccount table e	concenti concenti ch work t of injury quipmer	way from the wo ilute an air conta rate irritants. A v place or task. T y experience. nt should be rea arks of quality v of the glove ma	written p 'his shou adily ava which va aterial ca	bolicy doo uld incluc ailable.	nanufacturer
8.2.2. Personal protection Eye and face protection Skin protection	 Enclosure and/c strategically "ad Safety glass goggles. Contact lens describing til lens absorpt Medical and See Hand prote Wear chemic Wear chemic Wear safety The selection of to manufacturer advance and ha The selection of to manufacturer advance and ha The selection of to manufacturer Wear safety The selection of to manufacturer Wear chemic <li< td=""><td>ds" and "removes" air in the work environment. Ver the work environment is a preparation of several suitable gloves does not only depend on the mater . Where the chemical is a preparation of several suitable glove type is dependent on usage. . Through time for substances has to be obtained from through time for substances has to be obtained fro</td><td>nay absor pe created a and an a al and suit ial, but als bstances,</td><td>b and d for ea ccount table e</td><td>concenti concenti ch work t of injury quipmer</td><td>way from the wo ilute an air conta rate irritants. A v place or task. T y experience. nt should be rea arks of quality v of the glove ma</td><td>written p 'his shou adily ava which va aterial ca</td><td>bolicy doo uld incluc ailable.</td><td>nanufacturer</td></li<>	ds" and "removes" air in the work environment. Ver the work environment is a preparation of several suitable gloves does not only depend on the mater . Where the chemical is a preparation of several suitable glove type is dependent on usage. . Through time for substances has to be obtained from through time for substances has to be obtained fro	nay absor pe created a and an a al and suit ial, but als bstances,	b and d for ea ccount table e	concenti concenti ch work t of injury quipmer	way from the wo ilute an air conta rate irritants. A v place or task. T y experience. nt should be rea arks of quality v of the glove ma	written p 'his shou adily ava which va aterial ca	bolicy doo uld incluc ailable.	nanufacturer
8.2.2. Personal protection Eye and face protection Skin protection Hands/feet protection Body protection	 Enclosure and/c strategically "ad Safety glass goggles. Contact lens describing til lens absorpt Medical and See Hand prote Wear chemic Wear chemic Wear safety The selection of to manufacturer advance and ha The selection of to manufacturer advance and ha The selection of to manufacturer Wear safety The selection of to manufacturer Wear chemic <li< td=""><td>ds" and "removes" air in the work environment. Ver ds" and "removes" air in the work environment. Ver discontinuent of the second of the sec</td><td>nay absor pe created a and an a al and suit ial, but als bstances,</td><td>b and d for ea ccount table e</td><td>concenti concenti ch work t of injury quipmer</td><td>way from the wo ilute an air conta rate irritants. A v place or task. T y experience. nt should be rea arks of quality v of the glove ma</td><td>written p 'his shou adily ava which va aterial ca</td><td>bolicy doo uld incluc ailable.</td><td>nanufacturer</td></li<>	ds" and "removes" air in the work environment. Ver ds" and "removes" air in the work environment. Ver discontinuent of the second of the sec	nay absor pe created a and an a al and suit ial, but als bstances,	b and d for ea ccount table e	concenti concenti ch work t of injury quipmer	way from the wo ilute an air conta rate irritants. A v place or task. T y experience. nt should be rea arks of quality v of the glove ma	written p 'his shou adily ava which va aterial ca	bolicy doo uld incluc ailable.	nanufacturer

Lyreco Solvent Based Correction Fluid Page 7 of 15

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

8.2.3. Environmental exposure controls

See section 12

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	White liquid with a mild odour; does not mix with water.			
Physical state	Liquid	Relative density (Water = 1)	~1.15	
Odour	Not Available	Partition coefficient n- octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available	
pH (as supplied)	Not Available	Decomposition temperature	Not Available	
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available	
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable	
Flash point (°C)	Not Available	Taste	Not Available	
Evaporation rate	Not Available	Explosive properties	Not Available	
Flammability	Not Available	Oxidising properties	Not Available	
Upper Explosive Limit (%)	7.0	Surface Tension (dyn/cm or mN/m)	Not Available	
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available	
Vapour pressure (kPa)	Not Available	Gas group	Not Available	
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available	
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available	

9.2. Other information

Not Available

SECTION 10 STABILITY AND REACTIVITY

10.1.Reactivity	See section 7.2
10.2.Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2

Lyreco Solvent Based Correction Fluid Page 8 of 15

materials 10.6. Hazardous See section 7.2

decomposition products

10.5. Incompatible

See section 5.3

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

	by EC Directives using animal models). Nevertheless, a	ealth effects or irritation of the respiratory tract following inhalation (as classifi dverse systemic effects have been produced following			
Inhaled	exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and				
	that suitable control measures be used in an occupation	0			
	Not normally a hazard due to non-volatile nature of proc				
		mal experiments indicate that ingestion of less than 150 gram may be fatal or			
Ingestion	may produce serious damage to the health of the individ Swallowing of the liquid may cause aspiration into the	ungs with the risk of chemical pneumonitis; serious consequences may resu			
	(ICSC13733)				
Skin Contact	The liquid may be miscible with fats or oils and may deg	rease the skin, producing a skin reaction described as non-allergic contact			
	dermatitis. The material is unlikely to produce an irritant				
	Open cuts, abraded or irritated skin should not be expose Although the liquid is not thought to be an irritant (as cla	sed to this material sified by EC Directives), direct contact with the eye may produce transient			
Eye	is a second of the second of t				
Chronic	Long-term exposure to the product is not thought to product animal models); nevertheless exposure by all routes sho	duce chronic effects adverse to the health (as classified by EC Directives usin buld be minimised as a matter of course.			
yreco Solvent Based Correction Fluid	ΤΟΧΙΟΙΤΥ	IRRITATION			
	Not Available	Not Available			
naphtha petroleum,	TOXICITY	IRRITATION			
light solvent-refined	Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Not Available			
	Oral (rat) LD50: >2000 mg/kg ^[1]				
	ΤΟΧΙΟΙΤΥ	IRRITATION			
	Inhalation (rat) LC5 0: >2.28 mg/l4 h ^[1]	Skin (human): 0.3 mg /3D (int)-mild *			
	Inhalation (rat) LC50: >3.56 mg/l4 h ^[1]				
titanium dioxide	Inhalation (rat) LC50: >6.82 mg/l4 h ^[1]				
	Inhalation (rat) LC50: 3.43 mg/l4 h ^[1]				
	Inhalation (rat) LC50: 5.09 mg/l4 h ^[1]				
	Oral (rat) LD50: >2000 mg/kg ^[1]				
	ΤΟΧΙΟΙΤΥ	IRRITATION			
calcium carbonate	141				
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 0.75 mg/24h - SEVERE			
	Oral (rat) LD50: >2000 mg/kg ^[1]	Skin (rabbit): 500 mg/24h-moderate			
	Oral (rat) LD50: 6450 mg/kge ^[2]				
Legend:	1. Value obtained from Europe ECHA Registered Subst	ances - Acute toxicity 2.* Value obtained from manufacturer's SDS. - Register of Toxic Effect of chemical Substances			

Lyreco Solvent Based Correction Fluid Page 9 of 15

NAPHTHA PETROLEUM, LIGHT SOLVENT-REFINED	No significant acute toxicological data identified in literature search. for petroleum: This product contains benzene which is known to cause acute myeloid leukaemia and n-hexane which has been shown to metabolize to compounds which are neuropathic. This product contains toluene. There are indications from animal studies that prolonged exposure to high concentrations of toluene may lead to hearing loss. This product contains ethyl benzene and naphthalene from which there is evidence of tumours in rodents Carcinogenicity: Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans. for full-range naphthas			
TITANIUM DIOXIDE	The material may produce moderate eye irritation leading to inflammation. Repeat conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and m production of vesicles, scaling and thickening of the skin. Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When in causing dysfunction of the lungs and immune system. * IUCLID	hay produce on contact skin redness, swelling, the		
CALCIUM CARBONATE	Asthma-like symptoms may continue for months or even years after exposure to allergenic condition known as reactive airways dysfunction syndrome (RADS) whi exposure to high levels of highly irritating compound. Key criteria for the diagnosis respiratory disease, in a non-atopic individual, with abrupt onset of persistent asth minutes to hours of a documented exposure to the irritant. A reversible airflow patr of moderate to severe bronchial hyperreactivity on methacholine challenge testing without eosinophilia, have also been included in the criteria for diagnosis of RADS is an infrequent disorder with rates related to the concentration of and duration of to the irritating substance. No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic	ch can occur following of RADS include the absence of preceding ma-like symptoms within tern, on spirometry, with the presence and the lack of minimal lymphocytic inflammation, . RADS (or asthma) following an irritating inhalation exposure		
Acute Toxicity	Carcinogenic brokenics in the circle of the angle in the degenic of the degenic of the angle in the degenic of the angle in the degenic of the angle in the degenic of the d			
Skin Irritation/Corrosion	Reproductivity	0		
Serious Eye Damage/Irritation	STOT - Single Exposure	0		
Respiratory or Skin sensitisation	STOT - Repeated Exposure	0		
Mutagenicity	Aspiration Hazard	¥		
		uired to make classification available available but does not fill the criteria for classification		

S – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

Toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment. **DO NOT** discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
titanium dioxide	HIGH	HIGH

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
titanium dioxide	LOW (BCF = 10)

12.4. Mobility in soil

Lyreco Solvent Based Correction Fluid Page 10 of 15

Ingredient	Mobility
titanium dioxide	LOW (KOC = 23.74)
12. 5.Results of F	PBT and vPvB assessment

	Ρ	В	т
Relevant available data	Not Available	Not Available	Not Available
PBT Criteria fulfilled?	Not Available	Not Available	Not Available

12.6. Other adverse effects

No data available

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate:
Product / Packaging disposal	▶ Reduction ▶ Reuse ▶ Recycling
	Disposal (if all else fails)
	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 TRANSPORT INFORMATION

Labels Required	
	navyase 3
Marine Pollutant	
HAZCHEM	•3YE
Land transport (ADR)	
14.1. UN number	1263
14.2. Packing group	II Contraction of the second
14.3. UN proper shipping name	PAINT or PAINT RELATED MATERIAL
14.4. Environmental hazard	No relevant data
14.5. Transport hazard class(es)	Class 3 Subrisk Not Applicable
14.6. Special precautions for user	Special provisions 163 640C 640D 650 Limited quantity 5 L

Lyreco Solvent Based Correction Fluid Page 11 of 15

Air transport (ICAO-IATA / DGR)

14.1. UN number	1263				
14.2. Packing group	II				
14.3. UN proper shipping name	Paint (including paint, lac (including paint thinning c	quer, enamel, stain, shellac, varnish, polis or reducing compounds)	sh, liquid filler and liqu	id lacquer base); Paint related material	
14.4. Environmental hazard	No relevant data				
	ICAO/IATA Class	3			
14.5. Transport hazard	ICAO / IATA Subrisk	Not Applicable			
class(es)	ERG Code	ЗL			
	Special provisions A3 A72 A192				
	Cargo Only Packing Ins	structions	364		
	Cargo Only Maximum (Qty / Pack	60 L		
14.6. Special precautions for user	Passenger and Cargo F	Packing Instructions	353		
precautions for user	Passenger and Cargo	Maximum Qty / Pack	5 L		
	Passenger and Carg o	Limited Quantity Packing Instructions	Y341		
	Passenger and Cargo L	.imited Maximum Qty / Pack	1 L		

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1263
14.2. Packing group	Ш
14.3. UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
14.4. Environmental hazard	Not Applicable
14.5. Transport hazard class(es)	IMDG Class 3 IMDG Subrisk Not Applicable
14.6. Special precautions for user	EMS NumberF-E , S-ESpecial provisions163Limited Quantities5 L

Inland waterways transport (ADN)

14.1. UN number	1263
14.2. Packing group	U
14.3. UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)
14.4. Environmental hazard	No relevant data
14.5. Transport hazard class(es)	3 Not Applicable
14.6. Special precautions for user	Classification codeF1Limited quantity5 LEquipment requiredPP, EX, AFire cones number1

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Lyreco Solvent Based Correction Fluid Page 12 of 15

			Print Date: 06/10/2021
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	titanium dioxide	z	

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

NAPHTHA PETROLEUM, LIGHT SOLVENT-REFINED(64741-84-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of Dangerous Substances (updated by ATP: 31) - Carcinogenic Substances
EU REACH Regulation (EC) No 1907/2006 - Annex XVII (Appendix 2) Carcinogens: category 1B (Table 3.1)/category 2 (Table 3.2)	European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of Dangerous Substances (updated by ATP: 31) - Mutagenic
European Customs Inventory of Chemical Substances ECICS (English)	Substances
European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)	European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI
European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of Dangerous Substances - updated by ATP: 31	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
TITANIUM DIOXIDE(13463-67-7) IS FOUND ON THE FOLLOWING REGULATOR	Y LISTS
EU European Chemicals Agency (ECHA) Community Rolling Action Plan (CoRAP) List of Substances	European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)
European Customs Inventory of Chemical Substances ECICS (English) European Trade Union Confederation (ETUC) Priority List for REACH	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
Authorisation	UK Workplace Exposure Limits (WELs)
REGULATORY LISTS	CALCIUM CARBONATE(471-34-1) IS FOUND ON THE FOLLOWING
European Customs Inventory of Chemical Substances ECICS (English)	UK Workplace Exposure Limits (WELs)
European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)	

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : 67/548/EEC, 1999/45/EC, 98/24/EC, 92/85/EC, 94/33/EC, 91/689/EEC, 1999/13/EC, Commission Regulation (EU) 2015/830, Regulation (EC) No 1272/2008 and their amendments as well as the following British legislation: - The Control of Substances Hazardous to Health Regulations (COSHH) 2002 - COSHH Essentials - The Management of Health and Safety at Work Regulations 1999

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (naphtha petroleum, light solvent-refined)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (naphtha petroleum, light solvent-refined)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Lyreco Solvent Based Correction Fluid Page 13 of 15

Full text Risk and Hazard codes

H115Causes skin irritationH116Causes serious eye damageH117May cause respiratory irritationH110May cause genetic defectsH116May cause cancerH117May cause cancer by inhalation.H117Irritating to respiratory system and skin.H117Risk of serious damage to eyes.H116May cause CANCER.H117May cause CANCER.H117May cause CANCER by inhalation.		
H335 May cause respiratory irritation H340 May cause genetic defects H350 May cause cancer H350i May cause cancer by inhalation. R37/38 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. R45 May cause CANCER. R46 May cause heritable genetic damage.	H315	Causes skin irritation
H340 May cause genetic defects H350 May cause cancer H350i May cause cancer by inhalation. Irritating to respiratory system and skin. Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. May cause cANCER. May cause heritable genetic damage.	H318	Causes serious eye damage
H350 May cause cancer H350i May cause cancer by inhalation. R87738 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. R45 May cause CANCER. R46 May cause heritable genetic damage.	H335	May cause respiratory irritation
H350i May cause cancer by inhalation. R37738 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. R45 May cause CANCER. R46 May cause heritable genetic damage.	H340	May cause genetic defects
R37/38 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. R45 May cause CANCER. R46 May cause heritable genetic damage.	H350	May cause cancer
R41 Risk of serious damage to eyes. R45 May cause CANCER. R46 May cause heritable genetic damage.	H350i	May cause cancer by inhalation.
R45 May cause CANCER. R46 May cause heritable genetic damage.	R37/38	Irritating to respiratory system and skin.
R46 May cause heritable genetic damage.	R41	Risk of serious damage to eyes.
	R45	May cause CANCER.
R49 May cause CANCER by inhalation.	R46	May cause heritable genetic damage.
	R49	May cause CANCER by inhalation.

Other information

DSD / DPD label elements



Relevant risk statements are found in section 2.1

Relevant hak statements are	
Indication(s) of danger	F, N, Xn
SAFETY ADVICE	•
S02	Keep out of reach of children.
S09	Keep container in a well ventilated place.
S13	Keep away from food, drink and animal feeding stuffs.
S16	Keep away from sources of ignition. No smoking.
S23	Do not breathe gas/fumes/vapour/spray.
S29	Do not empty into drains.
S33	Take precautionary measures against static discharges.
S35	This material and its container must be disposed of in a safe way.
S40	To clean the floor and all objects contaminated by this material, use water and detergent.
S41	In case of fire and/or explosion, DO NOT BREATHE FUMES.
S43	In case of fire use the extinguishing media detailed in section 5 of this SDS.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well ventilated areas.
S56	Dispose of this material and its container at hazardous or special waste collection point.
S57	Use appropriate container to avoid environmental contamination.
S61	Avoid release to the environment.
Ingredients with multip	ole cas numbers
Name	CAS No

Lyreco Solvent Based Correction Fluid Page 14 of 15

	Thin Date. VUTUE
titanium dioxide	100292-32-8, 101239-53-6, 116788-85-3, 12000-59-8, 12188-41-9, 12701-76-7, 12767-65-6, 12789-63-8, 1309-63-3, 1317-70-0, 1317-80-2, 1344-29-2, 13463-67-7, 185323-71-1, 185828-91-5, 188357-76-8, 188357-79-1, 195740-11-5, 221548-98-7, 224963-00-2, 246178-32-5, 252962-41-7, 37230-92-5, 37230-94-7, 37230-95-8, 37230-96-9, 39320-58-6, 39360-64-0, 39379-02-7, 416845-43-7, 494848-07-6, 494848-23-6, 494851-77-3, 494851-98-8, 55068-84-3, 55068-85-4, 552316-51-5, 62338-64-1, 767341-00-4, 97929-50-5, 98084-96-9
calcium carbonate	1317-65-3, 13397-26-7, 146358-95-4, 15634-14-7, 198352-33-9, 459411-10-0, 471-34-1, 63660-97-9, 72608-12-9, 878759-26-3

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review using available literature references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Print Date: 06/10/2015

end of SDS

Lyreco Solvent Based Correction Fluid