



TASKI® Jontec Linosafe

Linoleum-safe stripper

Description

Linoleum safe stripper for removing emulsions and maintenance films from linoleum and other water-resistant hard floors. Prevents discolouring and damage to your Linoleum floor.

Key properties

- Highly effective, slightly alkaline stripper
- Formulated for the safe removal of emulsions from linoleum floors
- Fast acting, low foaming
- Low odour

Benefits

- Quick and thorough removal of emulsion layers
- Safe for use on all types of water-resistant hard floors, specially on Linoleum and calcium containing stones (example marble floors)
- Easy and safe to use
- Slightly perfumed for a pleasant use

Use instructions

1. Dose the product into full water tank of the machine.
2. Apply the solution.
3. Allow the product to act for 5-10 minutes.
4. Do not allow the floor to dry.
5. Scrub the floor with a single disc machine and an appropriate pad, wet vacuum the soiled solution and rinse thoroughly with clean water.
6. Allow to dry completely before applying additional coats.

Dosage:

TASKI Jontec Linosafe needs to be diluted.

Dosage bucket: 20% (1 L for 5 L bucket) max 50%.

Proper dosage and temperature save costs and minimize environmental impacts.



© A.I.S.E.

**This dosage is according to optimal conditions, recommendations may vary, please consult with your Diversey representative for directions.*



TASKI® Jontec Linosafe

Technical data

Appearance: Clear, pale yellow liquid

pH value (neat): ≈ 9.95

pH value (in use): ≈ 9.8

Relative density (20°C): 1.03 g/cm^3

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet; sds.diversey.com. Store in original closed containers away from extremes of temperature.

Only for professional users / specialists.

Product compatibility

Do not use on solvent-sensitive floorings e.g. asphalt. Do not use on water sensitive floors, e.g. unsealed wood and cork. Immediately remove any solution splashes from wooden/painted surfaces with a wet cloth. Keep from freezing. Test material compatibility on a small, inconspicuous place before use.

Environmental information

The surfactants used in this product are biodegradable in compliance with the requirements of EC Directives 73/404/EEC and 73/405/EEC and their subsequent amendments.

Available pack sizes

TASKI Jontec Linosafe is available in 2x5L.