

## Sprayglue non-permanent

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 - Product identifier

Trade name/designation: Sprayglue non-permanent  
Chemical name:  
Product-type: Mixture  
Product code: 764.400  
UFI: G110-8023-800C-SF80

#### 1.2 - Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: - Adhesives, sealants

#### 1.3 - Details of the supplier of the safety data sheet

Lyreco Switzerland AG  
Riedstrasse 4  
CH-8953 Dietikon  
Tel.:0800484484  
<http://www.lyreco.com>

#### 1.4 - Emergency telephone number

Germany: Intoxications Information Center; +49 761 19240  
Switzerland: Swiss Toxicological Information Centre; +41 44 251 51 51  
Austria: Intoxication information center; +43 1 406 43 43

### SECTION 2: Hazards identification

#### 2.1 - Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Irrit. 2	Eye irritation - Category 2
Aerosol 1	Aerosol - Category 1
STOT SE 3 (H336)	STOT-single exposure - Category 3 (H336)

#### 2.2 - Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word: Danger

Hazard pictograms



Hazard statements

H222	Extremely flammable aerosol
H229	Pressurised container: May burst if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Precautionary statements

## Sprayglue non-permanent

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
EUH-phrases	: None

### 2.3 - Other hazards

## SECTION 3: Composition / information on ingredients

### 3.1 - Substances

Not applicable

### 3.2 - Mixtures

Chemical name	No	%	Class(es)	Specific concentration limit
butane	CAS No. : 106-97-8 Index No. : 601-004-00-0 EC No. : 203-448-7	>= 40 - <= 45	Flam. Gas 1 - H220 Press. Gas	Not applicable
propane	CAS No. : 74-98-6 Index No. : 601-003-00-5 EC No. : 200-827-9	>= 20 - <= 25	Flam. Gas 1 - H220 Press. Gas	Not applicable
propan-2-ol, isopropyl alcohol, isopropanol	CAS No. : 67-63-0 Index No. : 603-117-00-0 EC No. : 200-661-7	>= 10 - <= 12.5	Eye Irrit. 2 - H319 Flam. Liq. 2 - H225 STOT SE 3 (H336) - H336	Not applicable
ethanol, ethyl alcohol	CAS No. : 64-17-5 Index No. : 603-002-00-5 EC No. : 200-578-6	>= 10 - <= 12.5	Flam. Liq. 2 - H225	Not applicable

## SECTION 4: First aid measures

### 4.1 - Description of first aid measures

<u>Following inhalation</u>	- No special measures are necessary. - Provide fresh air.
<u>Following skin contact</u>	- Wash immediately with: Water - When in doubt or if symptoms are observed, get medical advice.
<u>After eye contact</u>	- Rinse immediately carefully and thoroughly with eye-bath or water. - In case of eye irritation consult an ophthalmologist.
<u>After ingestion</u>	- Rinse mouth thoroughly with water. - Do NOT induce vomiting.

### 4.2 - Most important symptoms and effects, both acute and delayed

<u>Symptoms and effects - Following inhalation</u>	- No information available.
<u>Symptoms and effects - Following skin contact</u>	- No information available.

---

## Sprayglue non-permanent

---

Symptoms and effects - After eye contact - Causes eye irritation.

Symptoms and effects - After ingestion - No information available.

4.3 - Indication of any immediate medical attention and special treatment needed

---

### SECTION 5: Firefighting measures

---

#### 5.1 - Extinguishing media

Suitable extinguishing media

- ABC-powder
- Carbon dioxide (CO<sub>2</sub>)
- Foam
- Extinguishing powder

Unsuitable extinguishing media - Full water jet

#### 5.2 - Special hazards arising from the substance or mixture

Special hazards arising from the substance or mixture - No information available.

#### 5.3 - Advice for firefighters

- Co-ordinate fire-fighting measures to the fire surroundings.

---

### SECTION 6: Accidental release measures

---

#### 6.1 - Personal precautions, protective equipment and emergency procedures

For non-emergency personnel - Use personal protection equipment.

For emergency responders - No information available.

#### 6.2 - Environmental precautions

- No information available.

#### 6.3 - Methods and material for containment and cleaning up

Methods and material for containment - No information available.

Methods and material for cleaning up

- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
- Wash with plenty of water.

Inappropriate techniques - No information available.

#### 6.4 - Reference to other sections

- Disposal: see section 13  
- Personal protection equipment: see section 8

---

### SECTION 7: Handling and storage

---

#### 7.1 - Precautions for safe handling

Recommendation - Avoid: Eye contact

## Sprayglue non-permanent

- It is recommended to design all work processes always so that the following is excluded: Eye contact

### Advices on general occupational hygiene

- No information available.

### 7.2 - Conditions for safe storage, including any incompatibilities

- No information available.

### 7.3 - Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 - Control parameters

butane (106-97-8)	
IOELV TWA mg/m3 (UE)	1450 mg/m3
IOELV TWA ppm (UE)	600 ppm
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
IOELV TWA mg/m3 (UE)	1250 mg/m3
IOELV TWA ppm (UE)	400 ppm
IOELV STEL mg/m3 (UE)	999 mg/m3
IOELV STEL ppm (UE)	400 ppm

### DNEL / PNEC

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)			
Type	Value	User	Effect
DNEL long-term oral (repeated)	26 mg/kg bw/day	Consumers	Systemic
DNEL long-term inhalative	500 mg/m3	Workers	Systemic
DNEL long-term inhalative	89 mg/m3	Consumers	Systemic
DNEL long-term dermal	888 mg/kg bw/day	Workers	Systemic
DNEL long-term dermal	319 mg/kg bw/day	Consumers	Systemic
PNEC aquatic, freshwater	140.9 mg/l		
PNEC aquatic, marine water	140.9 mg/l		
PNEC aquatic, intermittent release	140.9 mg/l		
PNEC sediment, freshwater	552 mg/kg		
PNEC sediment, marine water	552 mg/kg		
PNEC Secondary Poisoning	160 mg/kg		
PNEC sewage treatment plant (STP)	2251 mg/l		
ethanol, ethyl alcohol (64-17-5)			
Type	Value	User	Effect
DNEL long-term oral (repeated)	87 mg/kg bw/day	Consumers	Systemic
DNEL acute inhalative	1900 mg/m3	Workers	Local
DNEL acute inhalative	950 mg/m3	Consumers	Local
DNEL long-term inhalative	950 mg/m3	Workers	Systemic
DNEL long-term inhalative	114 mg/m3	Consumers	Systemic
DNEL long-term dermal	343 mg/kg bw/day	Workers	Systemic
DNEL long-term dermal	206 mg/kg bw/day	Consumers	Systemic
PNEC aquatic, freshwater	960 mg/l		
PNEC aquatic, marine water	790 mg/l		
PNEC aquatic, intermittent release	2.75 mg/l		
PNEC sediment, freshwater	3.6 mg/kg		
PNEC sediment, marine water	2.9 mg/kg		
PNEC Secondary Poisoning	380 mg/kg		

## Sprayglue non-permanent

PNEC sewage treatment plant (STP)	580 mg/l		
-----------------------------------	----------	--	--

### 8.2 - Exposure controls

Appropriate engineering controls

- No information available.

Individual protection measures, such as personal protective equipment

- Suitable eye protection: Eye glasses with side protection

- Suitable eye protection: Dust protection eye glasses

- Suitable protective clothing: lab coat



## SECTION 9: Physical and chemical properties

### 9.1 - Information on basic physical and chemical properties

<u>Physical state</u>	Liquid	<u>Appearance</u>	Aerosol
<u>Colour</u>	colourless	<u>Odour</u>	characteristic
Odour threshold		No data available	
pH		No data available	
Melting point		No data available	
Freezing point		> -20 °C	
Boiling point		No data available	
Flash point		> -20 °C	
Evaporation rate		No data available	
flammability		No data available	
Lower explosion limit		No data available	
Upper explosion limit		No data available	
Vapour pressure		No data available	
Vapour density		No data available	
Relative density		No data available	
Density		0.617 g/cm <sup>3</sup>	
Solubility (Water)		No data available	
Solubility (Ethanol)		No data available	
Solubility (Acetone)		No data available	
Solubility (Organic solvents)		No data available	
Log KOC		No data available	
Auto-ignition temperature		No data available	
Decomposition temperature		No data available	
Kinematic viscosity		No data available	
Dynamic viscosity		No data available	

## Sprayglue non-permanent

### Particle characteristics

Particle size	No data available
---------------	-------------------

### 9.2 - Other information

VOC content	87.398 %
Minimum ignition energy	No data available
Conductivity	No data available

## SECTION 10: Stability and reactivity

### 10.1 - Reactivity

- This material is considered to be non-reactive under normal use conditions.

### 10.2 - Chemical stability

- The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3 - Possibility of hazardous reactions

- No hazardous reaction when handled and stored according to provisions.

### 10.4 - Conditions to avoid

- No information available.

### 10.5 - Incompatible materials

- No information available.

### 10.6 - Hazardous decomposition products

- Does not decompose when used for intended uses.

## SECTION 11: Toxicological information

### 11.1 - Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Not classified

#### Toxicity : Mixture

LD50 oral (rat)	No data available
LD50 dermal (rat)	No data available
LD50 dermal (rabbit)	No data available
LC50 inhalation (rat)	No data available
LC50 inhalation dusts and mists (rat)	No data available
LC50 inhalation vapours (rat)	No data available

- Based on available data, the classification criteria are not met.

#### Toxicity : Substances

butane (106-97-8)	
LC50 inhalation vapours (rat)	658 mg/l
propane (74-98-6)	

## Sprayglue non-permanent

LC50 inhalation vapours (rat)	20 mg/l
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
LD50 oral (rat)	5840 mg/kg
LD50 dermal (rabbit)	13900 mg/kg
ethanol, ethyl alcohol (64-17-5)	
LD50 oral (rat)	8300 mg/kg
LD50 dermal (rat)	7060 mg/kg

Skin corrosion/irritation - Not classified

Serious eye damage/eye irritation - Eye irritation - Category 2 - Causes serious eye irritation

- Irritating to eyes.

Respiratory or skin sensitisation - Not classified

Germ cell mutagenicity - Not classified

Carcinogenicity - Not classified

Reproductive toxicity - Not classified

STOT-single exposure - STOT-single exposure - Category 3 (H336) - May cause drowsiness or dizziness

STOT-repeated exposure - Not classified

Aspiration hazard - Not classified

### 11.2 - Information on other hazards

## SECTION 12: Ecological information

### 12.1 - Toxicity

#### Toxicity : Mixture

EC50 48 hr crustacea	No data available
LC50 96 hr fish	No data available
ErC50 algae	No data available
ErC50 other aquatic plants	No data available
NOEC chronic fish	No data available
NOEC chronic crustacea	No data available
NOEC chronic algae	No data available
NOEC chronic other aquatic plants	No data available

#### Toxicity : Substances

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)	
EC50 48 hr crustacea	9714 mg/l
LC50 96 hr fish	9640 mg/l
ErC50 algae	> 100 mg/l

- The substance/mixture does not fulfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

---

## Sprayglue non-permanent

---

### 12.2 - Persistence and degradability

Biochemical oxygen demand (BOD)	No data available
Chemical oxygen demand (COD)	No data available
% of biodegradation in 28 days	No data available

- No information available.

### 12.3 - Bioaccumulative potential

Bioconcentration factor (BCF)	No data available
Log KOC	No data available

- No indication of bioaccumulation potential.

### 12.4 - Mobility in soil

- No information available.

### 12.5 - Results of PBT and vPvB assessment

### 12.6 - Endocrine disrupting properties

### 12.7 - Other adverse effects

- No information available.

---

## SECTION 13: Disposal considerations

---

### 13.1 - Waste treatment methods

Waste treatment methods - Dispose of waste according to applicable legislation.

Sewage disposal - No information available.

Special precautions for waste treatment - No information available.

Community or national or regional provisions - No information available.

---

## SECTION 14: Transport information

---

### 14.1 - UN number or ID number

UN number (ADR) : UN1950

UN number (RID) : UN1950

UN number (ADN) : UN1950

UN number (IMDG) : UN1950

UN number (IATA) : UN1950

## Sprayglue non-permanent

### 14.2 - UN proper shipping name

UN proper shipping name (ADR) : AEROSOLS  
UN proper shipping name (RID) : AEROSOLS  
UN proper shipping name (ADN) : AEROSOLS  
UN proper shipping name (IMDG) : AEROSOLS  
UN proper shipping name (IATA) : AEROSOLS, FLAMMABLE

### 14.3 - Transport hazard class(es)

ADR Transport hazard class(es) : 2  
ADR Classification code: : 5F  
Pictograms



Transport hazard class(es) (RID) : 2  
Pictograms



Transport hazard class(es) (ADN) : 2  
Pictograms



Transport hazard class(es) (IMDG) : 2  
Pictograms



Transport hazard class(es) (IATA) : 2  
Pictograms



## Sprayglue non-permanent

### 14.4 - Packing group

Packing group :  
Packing group (RID) :  
Packing group (ADN) :  
Packing group (IMDG) :  
Packing group (IATA) :

### 14.5 - Environmental hazards

Environmental hazards : No  
Marine pollutant : No

### 14.6 - Special precautions for user

#### **ADR**

ADR Classification code : 5F  
ADR Special provisions : 190+327+344+625  
ADR Limited quantity (LQ) : 1L  
ADR Excepted quantities : E0  
ADR Packing instructions : P207 LP200  
ADR Special packing provisions : PP87 RR6 L2  
ADR Mixed packing provisions : MP9  
Instructions for portable tanks and bulk containers :  
Special provisions for portable tanks and bulk containers :  
ADR tank code :  
ADR tanks special provisions :  
Vehicle for tank carriage :  
ADR Transport category : 2  
ADR Tunnel restriction code : D  
ADR Special provisions loading, unloading and handling : CV9 CV12  
Special provisions - Packages : V14  
Special provisions - Bulk :  
Special provisions - Operation : S2  
ADR Hazard identification number (Kemler No.) :

#### **RID**

Special provisions :  
Limited quantity (LQ) :  
Excepted quantities :

#### **ADN**

Special provisions :  
Limited quantity (LQ) :

## Sprayglue non-permanent

<u>Excepted quantities</u>	:	
<b>IMDG</b>		
<u>Special provisions</u>	:	63 190 277 327 344 381 959
<u>Limited quantity (LQ)</u>	:	
<u>Excepted quantities</u>	:	E0
<u>Packing instructions</u>	:	P207 LP200
<u>Special packing provisions</u>	:	PP87 L2
<u>IBC instruction(s)</u>	:	
<u>IBC provisions</u>	:	
<u>Instructions for portable tanks and bulk containers</u>	:	
<u>Special provisions for portable tanks and bulk containers</u>	:	
<u>EmS codes</u>	:	F-D, S-U
<u>Stowage and handling</u>	:	Category None SW1 SW22
<u>Segregation</u>	:	SG69
<u>Properties and observations</u>	:	

<b>IATA</b>		
<u>PCA - Excepted quantities</u>	:	E0
<u>PCA - Limited Quantity - Packing Instructions</u>	:	Y203
<u>PCA - Limited Quantity - Maximum Net Quantity per Package</u>	:	30kg
<u>PCA - Packing Instructions</u>	:	203
<u>PCA - Maximum Net Quantity per Package</u>	:	75kg
<u>CAO - Packing Instructions</u>	:	203
<u>CAO - Maximum Net Quantity per Package</u>	:	150kg
<u>Special Provisions</u>	:	A145 A167 A802
<u>ERG Code</u>	:	10L

14.7 - Maritime transport in bulk according to IMO instruments

### SECTION 15: Regulatory information

15.1 - Safety, health and environmental regulations/legislation specific for the substance or mixture

<u>Substances REACH candidates</u>	None
<u>Substances Annex XIV</u>	None
<u>Substances Annex XVII</u>	None
<u>VOC content</u>	87.398 %

15.2 - Chemical Safety Assessment

Chemical safety assessment carried out for the product - No information available.

### SECTION 16: Other information

SDS versions

Version	Issue date	Author	Description of the amendments
1	11/24/2022		

---

## Sprayglue non-permanent

---

### Texts of the regulatory sentences

Aerosol 1	Aerosol - Category 1
Eye Irrit. 2	Eye irritation - Category 2
Eye Irrit. 2A	Eye irritation - Category 2A
Flam. Gas 1	Flammable gas. - Category 1
Flam. Liq. 2	Flammable liquid and vapour. - Category 2
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
Press. Gas	Gases under pressure
STOT SE 3 (H336)	STOT-single exposure - Category 3 (H336)

\*\*\* \*\*