

Technical Data Sheet

QuickFix (Elastic, Detectable, Water Resistant, Black & XRay)

1. Identification of the product and the company

1.1 Product identifier and intended use

Trade Name:	QuickFix and QuickFix Long
Intended Use:	Plum QuickFix plasters are intended as first aid products. The plasters provide a mechanical barrier and absorb exudate.
Expiry date:	Printed on the back of the plaster.

1.2 Details of the supplier of the data sheet

Manufacturer

Company:	Plum Safety ApS
Address:	Mandelalléen 1
Zip code:	5610
City:	Assens
Country:	DENMARK
E-mail:	info@plum.eu
Phone:	+45 6916 9600
Fax:	+45 6916 9630

1.3 Legislative information

General information:	As the products are class I medical devices according to <i>Regulation (EU) 2017/745 of the European Parliament and of the Council of 5 April 2017 on medical devices</i> concerning medical devices. No notified body is involved. No Safety Data Sheet is required for medical devices.
-----------------------------	---

Plum Safety ApS is certified according to *ISO 13485:2016 Medical devices – Quality management systems – Requirements for regulatory purposes*.

1.4 Symbol explanation

- Paper wrapping contains rubber latex 
- Do not reuse 
- Do not use if package is damaged 

Technical Data Sheet

QuickFix (Elastic, Detectable, Water Resistant, Black & XRay)

2. General information about the product

Material requirements:

The materials in these products have been judged biocompatible according to the requirements of *EN ISO 10993-1:2020 Biological evaluation of medical devices – Part 1: Evaluation and testing within a risk management process.*

Physical properties and composition:

	Elastic	Detectable	Water resistant	Black	XRay
Material	<i>Pink cross direction elastic fabric (Cotton & polyamide)</i>	<i>Blue cross direction elastic fabric (Cotton & polyamide). Detectable aluminium foil facing the backing.</i>	<i>Pink perforated PE (Polyethylene)</i>	<i>Black Polyester fabric</i>	<i>Blue Ethylene Vinyl Acetate and PE (Polyethylene) fabric with an aluminium foil inlay containing barium sulphate</i>
Adhesive pad	<i>Hypoallergenic acrylic polymer</i>	<i>Hypoallergenic acrylic polymer</i>	<i>Hypoallergenic acrylic polymer</i>	<i>Hypoallergenic hot melt polymer</i>	<i>Hypoallergenic acrylic polymer</i>
Absorbing pad	<i>Viscose and non-woven PP</i>	<i>Viscose and PP/PE non-woven</i>	<i>Viscose and non-woven PP</i>	<i>Viscose and polyester</i>	<i>Viscose and polyester</i>
Primary Packing (Pouch)	<i>Cold sealed paper</i>	<i>Cold sealed paper</i>	<i>Cold sealed paper</i>	<i>Cold sealed paper</i>	<i>Cold sealed paper</i>
Dimensions	<i>72 x 25 mm 120 x 20 mm</i>	<i>72 x 25 mm 120 x 20 mm</i>	<i>72 x 25 mm</i>	<i>72 x 25 mm 120 x 20 mm</i>	<i>72 x 25 mm 120 x 20 mm</i>
Special feature	<i>Elastic Breathable</i>	<i>Elastic Metal detectable Breathable</i>	<i>Water resistant Breathable</i>	<i>Breathable</i>	<i>Water resistant X-ray and metal detectable</i>

3. Side effects and malfunction

Side effects and malfunction:

The products are designed for skin contact and first aid use involving minor wounds. If side effects or malfunctions are experienced, please report these to Plum Safety ApS, info@plum.eu or phone +45 6471 2112, so that necessary remedial measures can be initiated.

Serious adverse effects should always be reported to a relevant and competent authority.

4. Storage

Storage:



Keep dry



Keep away from sunlight



Upper temperature limit (only applicable for Black and Xray)

Shelf life:

5 years from production date.

5. Other information

Version history and indication of changes

Version	Revision date (dd-mm-yyyy)	Responsible	Changes
2.0	08-08-2025	MAW	1, 4, 2, 4, 5
1.5	07-02-2025	MAW	2

Information on earlier revisions to be found on document version 1.5 or earlier

Technical Data Sheet

QuickFix (Elastic, Detectable, Water Resistant, Black & XRay)

Other information Additional information can be obtained by contacting info@plum.eu or by telephone +45 6471 2112.

TDS prepared by:

Company: Plum Safety ApS
Address: Mandelalléen 1
Zip code: 5610
City: Assens
Country: DENMARK
E-mail: info@plum.eu
Phone: +45 6916 9600
Fax: +45 6916 9630

Document Language: English