



LED Beryll

- Professional LED floor luminaire in a fine, modern design
- Ideal direct and indirect illumination:
52% direct light / 48% indirect light
- Long lamp head for precise illumination of the work surface
- ON/OFF switch at lamp head
- Microprismatic diffuser avoids disturbing glare
- Easy and fast to assemble



Technical data:

Lighting source:	LED 50W
Weighted energy consumption:	50 kWh/1000 h
Voltage:	200–240 V AC
Luminous flux:	3970 Lumen, 2070 lm direct/1900 lm indirect
Luminous efficacy:	83 Lumen/Watt
Colour temperature:	4200 Kelvin (neutral white), max. 3 Mac-Adam ellipses
Maximum illuminance:	1080 Lux (measuring distance 105 cm)
Colour rendering index (CRI):	> 80
Life time:	50 000 hours
Height:	1800 mm
Base:	450 mm length x 180 mm width
Head of lamp:	984 mm length x 65 mm width x 35 mm height
Length of the cable:	2.0 m
Net weight:	6.95 kg
Material:	aluminium, iron, PS, PC
Packaging:	white packaging with color label 1 parcel: 185 x 23 x 10 cm, 8.5 kg, girth: 251 cm

Item number: **41-5010.705.CH white**
41-5010.706.CH black

