

Technical specs

VECUT32GR - VENICUT32GR

Name:

DELTANOCUT® KNITTED GLOVE - PU-COATING PALM

Size:

06 - 07 - 08 - 09 - 10 - 11

Colour:

Grey

**Description :**

High Performance Polyethylene grey liner (HPPE) with spandex knitted glove / grey polyurethane (PU) coating on palm & fingertips. 8-cm elasticated wrist. Gauge 15.

Materials:

Gloves : High Performance Polyethylene grey liner (HPPE) with spandex

Coating : 100% polyurethane

Strong points:

DELTANOCUT®:

The new fibre is a resistant single fibre polymer, to a lesser thickness compared with conventional fibres (mixture of several fibres) and thereby provides maximum dexterity. The composition provides a cut resistancy of level 3.

The fibres soft touch texture provides comfort and feeling of freshness all day.

DELTAAnocut ® fibre is guaranteed DMF free for a total material safety and therefore a protection of the handled objects.

DELTAAnocut ® fibre is also washable for hygiene purposes and the gloves can be reused.

Instructions for use:

All-purpose protective gloves for mechanical risks, for general use in dry environment, with no chemical, microbiological, electrical or thermal hazards. It has a grip pattern and prevents hand contact and prints. Its anatomical shape is adapted to the hand. Its thinness ensures a perfect dexterity, a very good sensitivity and grip.

Limits to use:

Do not use other than for the purpose defined in the instructions for use below. *Users attention is drawn to the fact that gloves with very high resistance to traction (level 4) must not be used when there is a risk of catching in moving machines. These gloves do not contain any substances known to be carcinogenic or toxic. Contact with the skin may cause allergic reactions in sensitive persons (natural latex, in the cuff wrists of some gloves). In the event of a reaction, cease use and consult a doctor. Ensure your gloves are intact before and during using its and replace if necessary.

Instructions for storage:

Store in a cool, dry place away from frost and light in their original packaging.

Instructions for cleaning / maintenance:

Machine wash at 30°C maximum (numbers maximum washing : 4). Fast cycle. Do not use detergent. Drying in open air or cold.

Performances :

The levels are obtained on the palm of the glove. They are in increasing levels of performance (from 0 to 4 or 5). 0 indicates that the glove has a lower performance level than the minimum for the individual hazard given. X: indicates that the glove has not been subjected to testing or the test method is not suitable due to the design of the gloves or the material.

- Abrasion (from 0 to 4): Ability of the glove to withstand wear



DELTA PLUS GROUP

La Peyrolière - B.P. 140 - 84405 APT Cedex - France
www.deltaplus.fr



UPDATE : 23/08/2012

Technical specs

VECUT32GR - VENICUT32GR

- Cutting (from 0 to 5): Ability of the glove to withstand cutting
- Tearing (from 0 to 4): Ability of the glove to withstand tearing*
- Puncture (from 0 to 4): Ability of the glove to withstand puncture
- Dexterity (from 0 to 5): Manual ability to accomplish a task

The higher the performance, the greater the ability of the glove to withstand the associated risk. Performance levels are based on the results of laboratory tests, which do not necessarily reflect real conditions in the workplace.

This glove complies with the European directive 89/686, notably regarding ergonomics, innocuousness, comfort, ventilation and flexibility, with EN420:2003+A1:2009 (dexterity 5) and EN388:2003 (levels 4,3,4,2) European standards.

- **EN388:2003** Protective gloves against mechanical Risks (Levels obtained on the palm)



- 4 : Resistance to abrasion (from 0 to 4)
- 3 : Resistance to cut (from 0 to 5)
- 4 : Resistance to tear (from 0 to 4)
- 2 : Resistance to perforation (from 0 to 4)

- **EN420:2003+A1:2009** General requirements