

Product Datasheet uvex i-3 add 2.0
Material No. 6108.211**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth**

Productcharacteristic	<ul style="list-style-type: none">• innovative spectacle with invisible integrated dioptrre correction for near vision, +2,0 dpt.• patented lens technology• free-form lens design, manufactured in accordance with standard parameters and designed for a distance of approx. 64 mm between the eyes• extremely good coverage and fit all the way to the side area• individually adjustable side arms with variable inclination• integrated Softflex zone ensures outstanding wearer comfort for all head sizes• Softflex adjustable nose piece ensures comfortable, pressure-free fit and remain firmly in place
Technical details Frame Material Features Colour	 TPU/TPE Variable inclination, individually adjustable anthracite, lime

Manufacturer	Marking W
EN Standard	166
Low-energy impact	F (45 m/sec) EN 166
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
Lens	
Material	PC
Coating	supravision HC-AF
Colour	clear
Feature	integrated dioptrre correction; +2,0 dpt.
Filter	Marking 2C-1,2 (DIN EN 170)
Manufacturer	W
Optical class	1
Low-energy impact	F (45 m/sec)
Resistance to high speed particles at extremes of temperature	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Corr./PD	i-3 add 2.0, PD 64 / Add. 2,0 dpt.
Miscellaneous	
Weight	38g
Packing	1 piece in soft spectacles case with microfiber cloth
Standards	DIN EN 166 + DIN EN 170