

## CLIMBER S3

Product Reference Climber  
ENISO 20345:2011 S3 SRC  
Sizes 38-47  
Weight (s. 41) 625 gr.

**Model description:** Nubuck shoe, water repellent, black, Nylon mesh lining, antistatic, puncture resistant SJ Flex sole, shock proof, antislip, Composite toe cap, S3 PU/PU sole.

**Application areas:** Manufacturing.

**Precaution and maintenance of the shoe:** To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



		Description	Measure Unit	Result	EN345 required
Complete shoe	Protection of toes: composite toe cap resistant to: A shock of 200 J Pressure of 1500 kg Sole: SJ Flex	Impact resistance (Clearance after shock)	Mm	17,5	>14
		Compressive strength (after clearance compression)	Mm	17	14
	Anti-shock system: Low-Density polyurethane and profile of the heel	Shock absorption in heel	J	>34	>20
Upper	Nubuck leather, water repellent, black Thickness 1,6mm	Permeability to water vapor	Mg/m2 hour	>2,7	>0,8
		Permeability coefficient	Mg/cm2	>25	>20
		Water repellent	Minute	>90	<60
Front	Thickness 1,2mm	Permeability coefficient	Mg/cm2	>35	>30
Lining	Nylon mesh black	Permeability to water vapor	Mg/cm2 hour	>5	>2
Back	Thickness 1,0mm	Permeability coefficient	Mg/cm2	>45	>30
Insole	Antistatic, absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	Cycles	>400	>400
Outsole	Antistatic double density polyurethane injected directly onto the upper	Abrasion resistance (volume loss)	Mm3	110	<150
	Shock absorption, anti-slip, abrasion resistant, mineral oils and weak acids	Oil resistance (volume variation AV)	%	+1,0	<+12
		Coefficient of adhesion of the outsole	-	0,18	>0,15

*Our shoes are constantly evolving, the technical data above may change.*

*All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.*