



Type II environmental label:
self-declared environmental claim

23772 DALYX 3-in-1 USB-C Multi-Port Adapter

Issue Date

2024-07-05

Owner of Declaration

Trust

According to

ISO14021:2016 and EN50693

General information

Company

Manufacturer	Trust International B.V.
Production location	Shenzhen, China
Company address	Laan van Barcelona 600, 3317 DD Dordrecht, The Netherlands
Website	https://www.trust.com/

Self-declared environmental claim

This self-declared environmental claim is drawn up to quantify the environmental impact of one unit. The environmental impact is studied by a Life Cycle Assessment (LCA). The LCA and this declaration are not externally verified.

The disclosed environmental information is in the form of a type II environmental label, a self-declared environmental claim in line with ISO 14021 [1] and EN 50693 [2]. The template for this type II environmental label is set up by Hedgehog Company, while the product and environmental information is filled out by Trust.

Environmental label information

Product name	DALYX 3-in-1 USB-C Multi-Port Adapter
Product ID	23772
Related Product ID(s)	-
PCR	EN 50693
Software	Mobius v 1.1.1
Background database	Ecoinvent v3.8
Impact assessment method	EF 3.0 Method (Ecoinvent v3.8 cut-off)

Product description

Stylish aluminium multi-port adapter to add HDMI, USB-C and USB-A ports to your laptop using a single USB-C connection.

Size (height x width x depth)	Total weight	Power source
115x50x18 mm	78 g	USB

The product does not contain material content of substances of very high concern (SVHC).

Functional unit

The function studied in this EPD is that of providing additional input- and output ports to a computer, from a USB port. It is powered via USB.

Scope of declaration

This is a cradle-to-grave type II environmental label for the DALYX 3-in-1 USB-C Multi-Port Adapter. The life cycle stages are shown as below (x = included, ND = non declared).

Manufacturing stage	Distribution stage	Installation stage	Use stage	De-installation stage	End-of-life stage
x	x	ND	x	ND	x

Calculation rules

The method used to quantify the environmental performance of the product in question is the life cycle assessment (LCA) regulated by ISO 14040 and ISO 14044. Process data over the year of 2023 is used to model the product system. Ecoinvent v3.8 is used as a background database.

Manufacturing

The inventoried data used to model the DALYX 3-in-1 USB-C Multi-Port Adapter is collected from Trust International B.V. Transport to the production site is calculated based on collected information from product suppliers. Coverage of the product manufacturing includes the necessary energy inputs for product assembly, and manufacturing waste. Manufacturing waste is assumed to be incinerated completely, without energy recovery. Further energy inputs and data on the generated manufacturing waste are collected from the product manufacturer.

Table 1. Recycled content of the DALYX 3-in-1 USB-C Multi-Port Adapter.

Component	Material	Recycled content %
Housing	Aluminium	-
Plastic parts	ABS	-
PCB	PCB	-
Metal ports	Stainless steel	-
Cable	TPE cable	-
Package	Carton	70%
Package	PET	-
User manual	Paper	-

Distribution

After the production stage, the products are prepared for shipping to the Netherlands. The final products are transported by truck to the Port of Shenzhen. Further transport is by oceanic containers to the Port of Rotterdam. After docking of the ship, the products are further transported to the Trust distribution center in 's-Heerenberg. Approximately 85% of the products are transported by truck, while 15% is transported by barge. Final transport to the end-user of the products is based on default transport values according to EN 50693, which is 1.000 kilometers for local transport.

Final transport to the end-user of the products is based on default transport values according to EN 50693, which is 1.000 kilometres for local transport.

Use stage

The use stage includes the energy consumption and other flows (emissions, water, etc.) of the product during its use over the RSL. The Reference Service Life (RSL) of the product is five years. Total energy use over lifetime: 10 hr/week * 5 years = 3,2 kWh. Production, distribution, installation, end-of-life of materials or energy aimed at extending the product lifetime, like maintenance and repair are included when relevant.

End-of-life

The end-of-life stage starts with waste collection. The transport distance to the waste treatment facilities is assumed to be 1.000 kilometres, in accordance with EN 50693. Moreover, this study uses the default values for end-of-life treatment in accordance with EN 50693. For materials that are not included in this standard, appropriate waste treatment scenarios are selected.

The end-of-life steps start after the de-installation and include:

- Collection, transport and storage
- De-pollution
- Fractions separation and preparation (e.g. dismantling, crushing, sorting processes)
- Material recovery processes (metallurgical, chemical processes)
- Energy recovery processes (incineration with energy recovery, use as solid recovered fuel)
- Disposal (incineration without energy recovery, landfill)

The end-of-life stage ends at the disposal or the point of substitution.

In line with the EN 50693 Annex G formula without benefits, this study excludes system expansion and does not account for benefits beyond the system boundary. Thus, the impacts of the energy and material recovery operations are not included in the end-of-life stage of this product system.

Table 2. Applied values for the end-of-life modelling of the DALYX 3-in-1 USB-C Multi-Port Adapter.

Material	Incineration (g)	Recycling (g)
ABS	0,88	0,22
aluminium	2,76	11,04
Cable	0,00	8,00
Carton	1,92	14,08
Other plastics	9,16	4,84
PCB	8,76	1,55
Steel	0,68	2,72

Environmental impact per declared unit

Table 3. Environmental impact for the DALYX 3-in-1 USB-C Multi-Port Adapter.

Impact category	Unit	Manufacturing	Distribution	Use	End-of-life	Total
AP	mol H+ eq	1,02E-02	5,40E-04	7,92E-03	4,80E-05	1,87E-02
GWP100	kg CO2 eq	9,91E-01	3,37E-02	1,37E00	6,79E-02	2,46E00
GWP-b	kg CO2 eq	5,08E-03	1,11E-05	8,65E-03	5,32E-03	1,91E-02
GWP-f	kg CO2 eq	9,82E-01	3,37E-02	1,36E00	6,25E-02	2,44E00
GWP-luluc	kg CO2 eq	4,28E-03	1,64E-05	3,16E-03	5,90E-06	7,45E-03
ETP-fw	CTUe	8,85E01	3,67E-01	1,92E01	5,44E-01	1,09E02
EP-fw	kg P eq	6,33E-05	2,27E-07	1,45E-04	2,22E-07	2,09E-04
EP-m	kg N eq	1,16E-03	1,46E-04	1,01E-03	1,53E-05	2,33E-03
EP-T	mol N eq	1,32E-02	1,62E-03	1,24E-02	1,53E-04	2,74E-02
HTP-c	CTUh	1,65E-09	1,65E-11	4,96E-10	1,45E-11	2,18E-09
HTP-nc	CTUh	8,17E-08	3,92E-10	1,69E-08	9,13E-10	9,99E-08
IR	kBq U-235 eq	2,82E-02	2,09E-03	2,45E-01	3,17E-04	2,76E-01
SQP	Pt	4,03E00	2,87E-01	6,20E00	5,18E-02	1,06E01
ODP	kg CFC11 eq	5,19E-08	7,36E-09	1,15E-07	8,10E-10	1,75E-07
PM	disease inc.	7,01E-08	2,69E-09	2,17E-08	8,42E-10	9,54E-08
POCP	kg NMVOC eq	3,92E-03	4,32E-04	3,14E-03	4,26E-05	7,54E-03
ADP-f	MJ	1,19E01	4,83E-01	2,81E01	8,45E-02	4,05E01
ADP-mm	kg Sb eq	1,03E-04	6,30E-07	9,95E-06	1,25E-07	1,14E-04
WDP	m3 depriv.	2,94E-01	1,23E-03	3,14E-01	7,68E-03	6,16E-01

GWP100 = Climate change; **GWP-f** = Climate change - fossil; **GWP-b** = Climate change - biogenic; **GWP-luluc** = Climate change - Land use and LU change; **ODP** = Ozone depletion; **HTP-c** = Human toxicity, cancer; **HTP-nc** = Human toxicity, non-cancer; **PM** = Particulate matter; **IR** = Ionising radiation; **POCP** = Photochemical ozone formation; **AP** = Acidification; **EP-T** = Eutrophication, terrestrial; **EP-m** = Eutrophication, marine; **EP-fw** = Eutrophication, freshwater; **ETP-fw** = Ecotoxicity, freshwater; **SQP** = Land use; **WDP** = Water use; **ADP-f** = Resource use, fossils; **ADP-mm** = Resource use, minerals and metals

References

[1] ISO 14021: Environmental labels and declarations – Self-declared environmental claims (Type II environmental labelling)', International Organization for Standardization, ISO14021:2016.

[2] NEN-EN 50693: Product category rules for life cycle assessments of electronic and electrical products and systems, NEN-EN:50693:2019