

Datasheet

Articel No.	4517300XL-RC		
Film Type	PE Stretchfilm, CAST, transparent film. Made from 100% recycled PCR material 200% Pre-Stretch. Manual film Color of the roll: Grey. No gaps and holes. Some unwinding noise due to the tackifier.		
Packaging:	288 rl/pl Pallet Size: 800X1200 mm,		
Dimensions:	Width:	450 mm	+/- 5%
	Thickness:	17 my	+/-1 my
	Length:	300 m	+/- 5%
	Roll weight:	3.2 kg	+/- 5%
	Film weight net:	2.1 kg	+/- 5%
Core:	Inner Diameter:	50 mm	
	Length:	470 mm	
Copolymer:	Post-consumer recycled PE film content; 90% Adhesive additives: (Polyisobutylene and plastomers): 10%		

Typical film properties:

Property	Value	Unit	Test
Yield point	12	N/mm ²	BS-2782/326C
Elongation at yield point	16	%	BS-2782/326C
Tensile strength MD	16.0	N/mm ²	BS-2782/326C
Tensile strength TD	10.0	N/mm ²	BS-2782/326C
Elongation at break	710.0	%	BS-2782/326C
Tear Strength, TD	140.0	kN/m	BS-2782/326C
Min. Prestretch	200	%	BS-2782/360B

Typical Values; not to be construed as specification limits.

Waste handling: The simple structure of polyethylene with its carbon and hydrogen atoms ensures that Carbon dioxide and Water are the sole combustion products.
The film can be recycled to 100 percent.