



Designation	LED desk lamp
Name	Reflect
Product No	CLED-0400
Average RRP	
Target market	Offices

High quality product and effective after-sales service

Product features	Consumer benefits					
Structure &Switch						
<u>Base:</u> round shape; steel ballast; nonslip protection; painted steel; H17 Ø170 mm; 1.9 Kg <u>Arms:</u> double arm; painted steel; L240 / L 320 mm <u>Articulations:</u> 2 articulations for up/down adjustment	 ⇒ Great stability ⇒ Sober yet elegant shape ⇒ Dynamic and colorful ⇒ Great mobility of the light source ⇒ Easy adjustment of the head position 					
1 multi-direction articulation at head level Head: round shape, painted aluminum; H13 Ø 100 mm	 ⇒ Casy adjustment of the flead position ⇒ Orientation of the light beam in all directions ⇒ Thin design ⇒ Easy manipulation 					
Switch: touch switch with dimmer on the base	⇒ Turn the light on / off with a simple touch ⇒ Intuitive adjustment of the light intensity					
Consumption	& Power supply					
Energy class: A+ Power consumption: 7.5 kW / 1000h Luminous efficacy: 51 lm / W	 ⇒ Reduction of energy consumption and cost ⇒ Environmentally friendly 					
Power supply: plug-in transformer with jack connector. Input AC 240-100 V / 50-60 Hz; Output DC 24 V 0.5A; Cable length 2 m	 ⇒ Reduced space occupation ⇒ Simple plug-in operation 					
Luminaire isolation: protection against electric shock class III	⇒ Extremely safe use					
Light source & Illuminance						
<u>Light source:</u> 12 x 0.4W SMD white LED Luminous flux = 380 lm						
CRI > 80 Life time: 50 000 h Standard EN62471 ("exempt" risk level) Colour temperature 2700 K 3000 K 5000 K 6000 K 7000 K Blancfroid Cool white	 ⇒ Latest LED technology providing high quality lighting ⇒ No maintenance ⇒ Photobiological safety ⇒ An ideal light color temperature for the office 					
CRI > 80 Life time: 50 000 h Standard EN62471 ("exempt" risk level) Colour temperature 2700 K 3000 K 5000 K 6000 K 7000 K Blancfroid	lighting ⇒ No maintenance ⇒ Photobiological safety					
CRI > 80 Life time: 50 000 h Standard EN62471 ("exempt" risk level) Colour temperature 2700 K 3000 K Blanc chaud Warm white Illuminance: 850 lux at 40 cm. Regulation	lighting ⇒ No maintenance ⇒ Photobiological safety ⇒ An ideal light color temperature for the office ⇒ A perfect lighting complement for middle-size desks ⇒ Dimming function to adapt lighting according to					
CRI > 80 Life time: 50 000 h Standard EN62471 ("exempt" risk level) Colour temperature 2700 K 3000 K Blanc froid Gool white Illuminance: 850 lux at 40 cm.	lighting ⇒ No maintenance ⇒ Photobiological safety ⇒ An ideal light color temperature for the office ⇒ A perfect lighting complement for middle-size desks ⇒ Dimming function to adapt lighting according to different work needs					



Why list this product in your catalogue?

A traditional and elegant lamp with great mobility and equipped with a touch switch including dimmer. With its very practical mirror, this lamp has no match on the market.

Suggested catalogue text

French design LED lamp providing a great visual comfort thanks to a powerful lighting (380 lumens / or 850 lux at 40 cm) and to a pleasant color temperature (3000° Kelvin). Very low energy usage (7.5 W) and a very long lifetime (50 000 hours). Touch switch with dimmer on the base. Equipped with three metallic articulations ensuring sturdiness and great mobility of the arms and the head. Delivered with a mirror to be fixed to the head of the lamp: discreet and practical! Weighted base for a great stability. Structure: 100% recyclable aluminum and steel. Dimensions: arm length: 24 + 32 cm, Ø base: 17 cm, Ø head: 10 cm

Available Colours	% Sales	Barcode
Metallic grey Metallic grey, pink base Metallic grey, blue base Metallic grey, green base Metallic grey, white base	New	3462154000966 3462154000799 3462154000720 3462159002125 3462159002156

	Γ.	
Unit of Sales	1	
	L arms 240 / 320 x	
Dimensions UoS (mm)	Ø base 170 x Ø head 100	
	Hmax 520	
Weight UoS	2.4 Kg	
Pack Quantity	1	
Pack Dimensions (mm)	455 x 215 x 135	
Pack Weight	3 Kg	
2 nd packing: nb of UoS	3	
Dim 2 nd packing (mm)	655 x 475 x 165	
Weight 2 nd packing	9.8 Kg	
Pallet : number of units	144	
Pallet: W x L x H (mm)	1200 x 1000 x 2200	

