

# PRODUCT NUMBER: 1006186 BILSOM 303L Foamplug Refill

## 200prs

Learn more about our products at howardleight.com

Learn more about hearing conservation at hearforever.org >



#### **Overview**

#### **Reference Number**

1006186

#### **Product Type**

Hearing Protection

#### Range

Earplugs

#### Line

Disposable Earplugs

#### Brand

Howard Leight by Honeywell

## Brand formerly known as

BILSOM

#### Industry

<ul> <li>Industry</li> <li>Administration</li> <li>Agriculture</li> <li>Army - Defence</li> <li>ATEX environment</li> </ul>
Automotive and Part Manufacturer     Aviation     Building and Construction     Catering
• Chemical Industries • Energy or Electricity • Fire Protection brigades • Fishing • Food Industries
Foundry     Glass Industries     Green Spaces     Homeland defense     Industrial Cleaning
• Iron and steel industry • Laboratory • Logistics • Maintenance • Medical and Pharmaceutical
Metal steel     Minning and Quarrying     Offshore     Paper Industries     Petro-chemical
• Printing Industries • Services • Ship Building • Telecoms • Textile Industries • Transportation
Itilities    Water treatment    Welding     Wood Industries

#### **Product Use**

303L Foamplug Dispenser Refill, 200prs

## **Features & Benefits**

#### Feature

POLYURETHANE FOAM Soft foam delivers superior long-wearing comfort and solid performance. SMOOTH, SOIL-RESISTANT SKIN Prevents dirt or other substances from accumulating on skin or entering ear canal.

#### **Benefit**

## BILSOM 303L Foamplug Refill 200prs - 1006186

The Bilsom 300 Series earplugs are ideal for workers who need to block out loud noise demand the best protection and comfort available in an earplug. Europe most-used polyurethane earplug, the 300 series earplug, offers superior noise-blocking performance in a single-use earplug.

## **Technical Description**

SNR (dB)

33

H (dB)

32

M (dB)

29

L (dB)

29

#### **Attenuation Data**

Frequency (Hz) Frequenz (Hz) Fréquence (Hz)	63	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB) Mittlere Dämmung (dB) Atténuation moyenne (dB)	28.4	37.3	37.9	39.1	36.0	34.6	42.5	46.4
Standard Deviation (dB) Standardabweichung (dB) Déviation standard (dB)	6.4	9.0	9.2	9.7	7.9	4.6	4.9	4.7
Assumed Protection (dB) Angenommener (dB) Protection supposée (dB)	22.0	28.3	28.7	29.4	28.1	30.0	37.6	41.8

Size

Fits All

Color

Yellow

Shape

bullet

Corded

No

Weight (grs)

0.48

## **Certifications**

**■** E.C. Declaration of Conformity

**EC Category PPE** 

2

**Quality Assurance** 

ISO 9001 / 2000

**EC Certificate Number** 

941057

**EC Attestation** 

EC Attestation

**EC Attestation Number** 

9404815

#### **Additional Information**

#### **User Manual**

Instruction Manual - Bilsom 303 (global)

#### **Maintenance**

#### **Storage Information**

All earplugs should be stored before and between usages in a way that protects them from dirt, grease, and other contaminants.

#### **Care Instructions**

Disposable earplugs are made of either TPE (Thermoplastic elastomers) or polyurethane foam. Washing and cleaning of disposable earplugs are not recommended. These plugs must be disposed of and replaced after each wearing. Excessive moisture reduces the attenuation and slows down the foam recovery which may lead to improper fit.

## **Packaging**

#### **EAN Code**

7312550061862

© Honeywell International Inc.