

tesa Powerstrips® Poster – 58003, 58213, 58303, 58076, 58126

Double sided adhesives, die-cuts without backing.

Main Application

For the reversible fixation of UV impermeable and sufficiently firm objects with smooth and flat surfaces. Due to the special pointed shape, Powerstrips® Poster are ideal for sensitive surfaces. Application examples: postcards and poster.

- Holds on tiles, glass, wood, most plastics and woodchip wallpaper.
- Holding power: max. 200 g

For optimal results:

- Preparation: Clean the surfaces with rubbing alcohol and work on/ with flat, dry, dust and grease-free materials.
- Application: When affixing the strip on the wall and the object on the strip, press down firmly and evenly (leave no air bubbles) on the entire strip/ object for at least five seconds to secure the bond.
- Removal: Hold the strip by its tab and slowly pull it down parallel to the wall without pressing it against the surface. Objects that are fixed with tesa Powerstrips® Poster can be removed without a trace.

Please note:

- Do not touch the adhesive area of the strip.
- Not suitable for use on vinyl wallpaper and anti-stick surfaces.
- Glass cleaners for preparing the surface could reduce the holding power (contains e.g. silicones: Silicone prevents an adhesive bonding and cannot be removed from surfaces with cleaners).

Technical Data & Properties

Dimensions	1,5 cm x 4,4 cm (die-cuts with tab)	
Product structure	1 layer	
Colour	white	
Adhesive	Synthetic rubber	
Adhesion/ steel	17,0 N / cm	
Backing	-	
Strip covering	One-sided siliconized release liner (top and bottom)	
Thickness	0,40 mm	
Holding Power	200 g (max. thickness of material: 1 mm)	
Temperature for application & removal	min 15 °C	
Temperature resistance	5 – 35 °C	

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Additional Information & Pictures



58003

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.