



# Technical Data Sheet



## Pritt Stick

Solvent-free glue stick

### CHARACTERISTICS

- Water-based glue stick for crafting and hobby
- CE conform according to EN 71 Safety of Toys (Parts 1,3,5)
- Solvent-free
- Acid-free suitable for archiving
- Up to 97% renewable ingredients (including water)
- Washable at 20°C
- Easy application
- High initial tack
- High efficiency
- Suitable for paper, cardboard, felt, cork and lightweight craft materials

### APPLICATION FIELD

Glue stick adhesive for home, school and office. Ideal for crafting and hobby.

### INSTRUCTIONS FOR USE

#### Pretreatment

Not necessary. Apply to surfaces that are clean, dry and free of dust and grease.

Technical Data Sheet

Ref: PR20000

Issued: 17.11.21

Number of pages: 2



**Application**

Apply the adhesive two or three times on the surface and join the parts to be bonded together.  
Close the cap properly after use to avoid drying out of the glue mass.  
Correction of the bonding parts is possible within a short period of time after bonding.  
Replace cap immediately after use!

**TECHNICAL DATA**

Composition	Starch ether, polysaccharides, soap and water
pH	10.0-10.2
Open time*	up to 210 seconds
Setting time*	60 - 90 seconds
Colour	white
Shelf Life	36 months at 20 °C

\* parameter depends on ambient temperature, moisture content and thickness (characteristic) of the materials.

**STORAGE**

Keep tightly closed and store in a dry and cool place. Avoid temperatures below 5°C and over 50°C.

**PACKAGING**

11g, 22g, Recyclable stick (containing 40% recycled material)  
43g, Recyclable stick (containing 65% recycled material)

**HEALTH AND SAFETY**

Before using the product please see related Material Safety Data Sheet that is available is available to download from [mysds.henkel.com](http://mysds.henkel.com).

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**Henkel Limited**

Road 5, Winsford Industrial Estate, Winsford, Cheshire, CW7 3QY  
Phone: +44 (0) 1606 593 933  
Internet: [www.henkel.co.uk](http://www.henkel.co.uk)  
e.mail: [technical.services@henkel.co.uk](mailto:technical.services@henkel.co.uk)