# TECHNICAL SPECIFICATION



## Replacement Jetstream® Dust & Gas Filter TH2A2P R SL

Jetstream® Dust & Gas Filter TH2A2P R SL / CBU620-000-000



#### DESCRIPTION

Replacement TH2A2P R SL filter for Jetstream® GVX Unit .

\*Replacement Jetstream® Dust & Gas Filter TH2A2P R SL meets the requirements of EN 12941 when fitted to Jetstream® respirator.

#### OPTIONS

Jetstream® Dust & Gas Filter TH2A2P R SL (CBU620-000-000)

#### SAFETY STANDARDS

EN 12941















#### **SPECIFICATIONS**

Classification TH2A2P R SL

Usage

R (Reusable)



Activated Carbon Layer

Y es

Maximum Total Inward Leakage (TIL) 2% When Fitted To Jetstream

**UK Assigned Protection Factor** 

20 When Fitted To JetStream GVX Unit

Filter Material

Pleated Media & Ativated Carbon

Filter Shelf Life 3 Years



**Product Weight** 

TH2A2P R SL Filter 592g



Filter Type

Organic Vapours, Nusance Odours and Particulate



(D) Resistance to dust clogging

Yes - Mandatory Test In EN12491

Minimum Filtration Efficiency

98%

Nominal Protection Factor

50 When Fitted To JetStream GVX Unit

Metal Free

No

Filter Casing Material

ABS



**BSI** Kitemark

Yes

#### RANGE

### **Jetstream**

**ACCESSORIES** 

#### DOWNLOADS


Image Pack (ZIP)

doc-jetstream.pdf (PDF)









Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





