WorkGuard™ 43-216

TECHNICAL DATASHEET

Special Purpose

Print date 25-02-2014

Glove material

- Leather (1.2 split cowhide A/B grade) (Liner material)
- Kevlar® seams (Liner material)
- Cotton Jersey (Liner material)

Possible Harmful ingredients

Sensitizers

No sensitizers

Reach Regulation 1907/2006

For more information, please consult the REACH statement on the Ansell website

Properties

Good abrasion and excellent tear resistance

EN Test Data

Abrasion resistance:

Performance level 3

Blade cut resistance:

Performance level 2

Tear resistance:

Performance level 4

Puncture resistance:

Performance level 3

Flammability:

Performance level 4 After flame time <2s, After glow time <5s

Contact heat resistance:

Performance level 1 Contact temperature 100°C >15s

Convective heat resistance:

Performance level 3 Heat Transfer Index >10s

Radiant heat resistance:

Performance level X (test not applicable)

Resistance to small projections of molten metal:

Performance level 4 >35 droplets

Resistance to large quantities of molten metal:

Performance level X (test not applicable)

European conformity

Gloves conform to the requirements of the European Directive 89/686/EEC and to the European standards EN 420:2003 + A1:2009 and EN 388:2003.EN 407:2004

They are categorised in "Complex Design" (= Protection against mortal risks).

EC-Type Examination Certificate and EC-quality control for the final product by

Centexbel

Technologiepark 7 B-9052 Zwijnaarde

Application - Limitations of use

Mechanical & heat protection

Do not use in heavy-duty cut applications

The glove is not liquidproof, hence is not to be used against chemicals

Storage

Keep away from sources of ozone or ignition.

Keep out of direct sunlight; store in a cool and dry place.

Construction	Liner material	Cuff style	Colour	Length mm	Packaging
Cut & sewn	Leather (1.2 split cowhide A/B grade) Kevlar® seams Cotton Jersey	Gauntlet	Yellow	410	6 pairs in a bag; 6 bags in a carton





