

Product data sheet flat fold mask FFP2 NR D, EN 149:2001 - uvex silv-Air 3210



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth, Germany

| | |
|-------------------------|---|
| Product features | <ul style="list-style-type: none">• Optimised shape• Soft material edges for high wearing comfort• The adjustable head band clips offer easy handling and comfortable fit• Exhalation valve for reduced build-up of heat and moisture inside the mask• Flexible and adjustable nose piece• Mask fulfils the requirements of the dolomite dust test (D)• Compatible with uvex safety eyewear |
| Materials | Headband: elastic textile Nose clip: PP Headband clips: PP Filter / mask: Melt Blown PP, Polyester Sealing lip: EVA foam Valve: ABS |

| | |
|---|--|
| Areas of use The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 10 times the respective limit values. | Mining, chemical industry, shipyards, iron and steel industry, woodworking, dust and fumes of substances such as asbestos, quartz, aluminium, copper, barium, titanium, vanadium, chrome, manganese and coal dust with more than 10% free silicon dioxide. |
| Weight | 17 g |
| Standard | EN 149:2001 + A1:2009 |

Versions/Colour:

| Article-No. | Colour/Version | Retail unit |
|-------------|---------------------------------------|------------------------------|
| 8733.210 | Flat fold mask FFP2, white with valve | 15 pieces per box |
| 8753.210 | Flat fold mask FFP2, white with valve | 3 pieces in retail packaging |

TS-AT-8733 Rev. St. 02 16.02.2015