

Technical specs

QUARTZ3 - QUARTZ III

Name:

RATCHET ADJUSTMENT SAFETY HELMET

Size:

Adjustable

Colour:

Blue - Green - Orange - Red - White - Yellow



CE 0082

Description :

UV-resistant high density polypropylene safety helmet. Polyamide lining : 3 textile bands with 8 fixing points. Sweat band. Ratchet adjustment : head measurement 53 to 63 cm. 2 possible positions of the head measurement (top/low) for a better comfort. This helmet may receive the following accessories: JUGALPHA, or DYNAMIC JUGALPHA MENTALPHA

Materials:

Polypropylene (PP)

Weight : 351 g

Instructions for use:

The helmet is made so that the energy released after a shock is absorbed by partial destruction or damage of the cap and harness, even if such damage is not immediately noticed, it is recommended to replace any helmet having being subject to a strong shock.

In order to ensure enough protection, this helmet should be adapted or adjusted to the users head size. We should draw the users attention also on the eventual hazard of modifying or removing one of the original parts of the protective helmet, except for the modification and removal type recommended by the helmet manufacturer. Helmets should not be adapted in any case for setting accessories according to a procedure not recommended by the helmet manufacturer. Do not apply paints, solvents, adhesives or stickers on it, except for those recommended by the instructions of the helmet manufacturer.

The helmet protects the user against a short accidental contact with electric leads under voltage which may reach 440V a.c. For general use in industry and in working seat where there is the electrical risks below 440V a.c.

Limits to use:

In order to ensure effective protection, this helmet should be worn with its peak forward (sit in straight position) and it should be adjusted to the user's head size (not fit to loose or to squeeze) to by its adjustment system serrated roller screwing-unscrewing located at the rear of the helmet (size 53-63 cm).The helmet life is affected by several factors, such as cold, heat, chemical products, sun light or misuse. A daily check should be performed in order to identify any sign of rendering (cracks, flaws) the helmet, its harness and accessories fragile. Any helmet having been subject to a strong shock or having wear signs should be replaced. If it has no defaults, it is therefore proper for the intended use. The manufacturing date is marked inside each helmet. Under normal usage conditions, this protective helmet should provide proper protection for 2 up to 3 years after the first usage, or 5 years according to the manufacturing date.

This helmet does not include any substance known to be susceptible of causing allergies. However if a sensitive person has an allergic reaction, it should therefore leave the hazardous area, remove the helmet and ask for medical advice.

Instructions for storage:

When it is not used anymore or during transportation, the helmet should be stored in a dry cool place away from light, frost and in a location granting that no chemical product or sharp object bends it by falling above.

Instructions for cleaning / maintenance:

This protective helmet may be cleaned and disinfected by means of a cloth impregnated in a low concentration cleaning solution. One shall not use any abrasive or corrosive chemical product. If this helmet cannot be cleaned by using this method, it should be replaced.



DELTA PLUS GROUP

La Peyrolière - B.P. 140 - 84405 APT Cedex - France
www.deltaplus.fr



UPDATE : 10/05/2012

Technical specs

QUARTZ3 - QUARTZ III

Performances :

This helmet complies with the European directive 89/686, notably regarding ergonomics, innocuousness, comfort and ventilation, and with EN397:1995/A1/2000 (-30°C / +50°C) / 440 V AC standard).

-30°C : Very low temperature

The helmet keeps its performance above these temperatures