

1. Product Powder Free Smooth Soft Stretch Vinyl Glove, GS0013*

2. Material Synthetic Vinyl (PVC)

3. Inspection Parameters

| Criteria | Inspection Level | AQL | Standard |
|---------------------------|------------------|-----|----------|
| Dimension | S - 2 | 4.0 | EN455-2 |
| Physical Properties | S - 2 | 4.0 | EN455-2 |
| Water Tight Test 1,000 ml | G - 1 | 4.0 | EN455-1 |
| Visual Defects | G - 1 | 2.5 | In-house |

4. Dimensions

| Dimension | Size (mm) | | | | |
|------------|-----------|---------|---------|----------|-------|
| | XS | S | M | L | XL |
| Palm Width | 75 ± 5 | 85 ± 10 | 95 ± 10 | 105 ± 10 | ≥ 115 |
| Length | ≥ 230 | ≥ 230 | ≥ 230 | ≥ 230 | ≥ 230 |

5. Thickness

| Point of Thickness Measurement | Single Wall (mm) |
|---|------------------|
| Cuff (at 40mm from the beaded end) | 0.05 Min |
| Palm (at centre of palm) | 0.05 Min |
| Fingertip (at 15mm from the tip of centre finger) | 0.05 Min |

6. Physical Properties

| Parameters | Before Aging | After Aging (70 ± 2 °C for 7 days) |
|--------------------------------|--------------|---------------------------------------|
| Median force at break (Newton) | Min N/A | Min N/A |
| Tensile Strength (MPa) | Min 9 | Min 9 |
| Ultimate Elongation | Min N/A | Min N/A |

7. Powder Residue Maximum 2.0 mg / glove

8. Cuff Beaded

9. Design Ambidextrous

10. Surface Smooth

11. Colour Cream

12. Quality Assurance Manufactured under ISO 9001:2008 and ISO 13485:2003

The data above represents the product norm, which may be changed without notice.