Unigloves Product Specification Sheet

Date of issue: 7th February 2010

Doc. No. PVC

Rev. No. 05

~		Powdered, Smooth Soft Blue Vinyl Glove, GS009*					
2.	Material	Synthetic Vinyl (PVC)					
3.	Inspection Parameters	Criteria	Inspection Level		AQL S		tandard
		Dimension	S – 2		4.0 I		N455-2
		Physical Properties	S – 2		4.0	4.0 E	
		Water Tight Test 1,000 ml	G – 1		4.0 E		N455-1
		Visual Defects	G – 1		2.5	2.5 lr	
4.	Dimensions	Dimension	Size (mm)				
			XS	S	М	L	XL
		Palm Width	75 ± 5	85 ± 10	95 ± 10	105 ± 10	≥ 115
		Length	≥ 230	≥ 230	≥ 230	≥ 230	≥ 230
5.	Thickness	Point of Thickness Measurement Single Wall (mm)					
		Cuff (at 40mm from the beaded end) 0.05 Min					
		Palm (at centre of palm)			0.05 Min		
		Fingertip (at 15mm from the tip of centre finger)			0.05 Min		
6.	Physical Properties	Parameters		Before Aging		After Aging	
						(70 ± 2 °C for 7 days)	
		Median force at break (Newton)		Min N/A		Min N/A	
		Tensile Strength (MPa)		Min 9		Min 9	
		Ultimate Elongation	Min N/A			Min N/A	
7.	Powder Residue	Maximum 10.0 mg / glove					
8.	Cuff	Beaded					
Э.	Design	Ambidextrous					
10.	Surface	Smooth					
11.	Colour	Blue					
12.	Quality Assurance	Manufactured under IS	SO 9001:2	008 and IS	0 13485:	2003	

The data above represents the product norm, which may be changed without notice.