



PRODUCT NUMBER: 1032370
Miller kernmantel edge shock absorbing lanyard 1,5 meters with 2 twist karabiners.

Miller kernmantel edge shock absorbing lanyard 1,5 meters with 2 twist steel karabiners.



Overview

Reference Number

1032370

Product Type

Fall Protection

Range

Shock Absorbing Lanyards

Line

Cut resistant

Brand

Miller by Honeywell

Industry

- Building and Construction

Product Use

Fall arrest lanyards will allow the worker to fall but prevents him from hitting the next lower level, such as the ground, (if well attached). It includes a shock absorber that dissipates the forces exerted on the body in the case of a fall to stay below 6 KN.

This single lanyard is edge tested for safe working on edges (r \geq 0,5 mm).

Features & Benefits

Feature

New design : * Lanyard manufactured with a light green rope with black stripes, which are highly visible from a distance increasing safety at work. * The stitches are highly visible which facilitates the safety check before use.

Benefit

* Lanyard edge tested : manufactured with high quality kernmantel rope and have special. * The rope is 2 times more resistant to the abrasion than the other standard ropes.

Technical Description

Length

1,5 M

Weight

0,644 KG

Breaking Strength

> 22 KN

Operating Temperature

-30°C to +50°C

Rope

Rope Raw Material

Kernmantel Ø 11 mm polyester sheath and polyamide core

Connector

Connector Type

Twist lock karabiner

Connector Raw Material

steel

Connector Opening

17 mm

Connector Breaking Strength

> 22 KN

Connector Standard

EN 362 : 2004

Energy Absorber

Energy Absorber Raw Material

Resistant webbing shock absorber with protective cover

Certifications

E.C. Declaration of Conformity

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Attestation

 EC Attestation

EC Attestation Number

0082-490-160-06-13-0169

Certifications

- EN 355 / VG 11 PFE 11.074

REACH

EU Regulation 1907/2006 (REACH) Compliance

The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.

Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

Additional Information

User Manual

NT90004208 IND L

User Information Sheet

User manual

Maintenance

Life Cycle

Life expectancy of our lanyards is 10 years from the date of manufacture.

Care Instructions

Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Please remember that:

- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.