

1125 Classic Safety Helmet

Technical Data Sheet

1125 Classic Safety Helmet Contact

General purpose safety helmet with a 6 point Terylene cradle and Brushed Nylon sweatband.



Specification	Colours:	White (W), Green (G), Blue (B), Orange (O), Yellow (Y), Red (R)
	Peak:	Full (40mm) or Reduced (20mm)
	Size:	51-63cm
	Options:	Corporate badging
	Accessories:	Compatible with Contract range of face and hearing accessories, Chinstrap (S30
		Retractable Eye Shield (S579)
	Weight:	365g Full, 350g Reduced
	Corporate Badging:	Front: 50 x 40mm or 45 x 45mm, Back and Sides: 100 x 30mm
	Helmet Accessories Clip:	Use Contex accessories clips (S570) supplied with Carriers and Ear Defenders
	Packaging:	20 per colour, box size 58.7 x 44.7 x 43.7cm, box weight 8.32kg (S03),
		8.04kg (\$17)
	Code:	S03*A (Full peak), S17*A (Reduced peak)
		*Insert Colour code of helmet (ie. W for White)
Materials	Shell:	HDPE (High Density Polyethylene)
	Cradle:	6 Point Terylene webbing
	Headband:	LDPE (Low Density Polyethylene)
	Sweatband:	Brushed Nylon with 2mm foam
Standard & Options	European standard - EN 397:1995+A1, EN 397:2012+A1:2012	
	American standards - ANSI/ISEA Z89.1-2009 Type 1 Class E (20,000V a.c.)	
	Options within EN 397	440V a.c (Electrical Resistance)
	Ophons willing Er (077	LD (Lateral Deformation)
		MM (Molten Metal)
Š =		-30°C (Low Temperature Performance)
<u>5</u>		
<u>ရ</u>	Storage:	
	 Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C) May be stored in the dark for up to 5 years Do not store in direct/high heat or sunlight as this may distort the shell 	
υ		
D D	Lifetime: - The Centurion helmet has an in-use life of up to 5 years - Excessive wear and tear can considerably reduce the lifespan of the product	
Storage / Litetime		
<u>ე</u> ნ		
_		

- Clean using warm soapy water and soft cloth

- Do not use solvents or abrasives