

**Product Datasheet model pheos s 9192 786****UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth**

<b>Product characteristics</b>	<ul style="list-style-type: none"><li>* Modern fashion-look – fit to narrower faces</li><li>* Duo spherical lens provides excellent all round vision</li><li>* Eye plus-protection protects the eyebrows through an additional chamfer at the upper range</li><li>* A slim temple geometry enables a comfortable wearing of earmuffs, helmets and caps</li><li>* Outstanding ventilation ensures a well eye climate</li><li>* Temple ends with non-slip components</li></ul>
<b>Technical details</b>	
<b>Frame</b>	<b>Front piece/Temple</b>
<b>Material</b>	POM/TPE
<b>Features</b>	excellent ventilation
<b>Colour</b>	black-grey
<b>Manufacturer's ID code</b>	<b>Marking</b> W
<b>Applicable EN norm</b>	166
<b>Low-energy impact</b>	F (45 m/s)
<b>Conformity symbol</b>	CE

<b>Lens</b>	
Material	PC
Thickness	2,1 mm
Coating	supravison HC-AF
Colour	grey
	<b>Marking</b>
Filter	5-2,5 ( DIN EN 172)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
<b>Miscellaneous</b>	
Weight	28 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 172