

# 151125 Lyreco Permanent Marker C/Tip Red

Lyreco

Chemwatch Hazard Alert Code: 3

Chemwatch: 4854-66

Version No: 2.1.1.1

Safety Data Sheet (Conforms to Regulation (EU) No 2015/830)

Issue Date: 06/04/2013

Print Date: 02/14/2017

S.REACH.GBR.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### 1.1. Product Identifier

Product name	151125 Lyreco Permanent Marker C/Tip Red
Synonyms	151147 PK4 Lyreco Perm Marker C/Tip Asstd Col
Proper shipping name	PAINT or PAINT RELATED MATERIAL
Other means of identification	Not Available

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Permanent Marker. NOTE: Information on this SDS refers to ink used in pens and markers, however, it applies to these inks in bulk.
Uses advised against	Not Applicable

### 1.3. Details of the supplier of the safety data sheet

Registered company name	Lyreco
Address	Deer Park Court, Donnington Wood Telford, TF2 7NB United Kingdom
Telephone	01952 286130
Fax	Not Available
Website	www.lyreco.co.uk
Email	steve.weston@lyreco.com

### 1.4. Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	Not Available
Other emergency telephone numbers	Not Available

## SECTION 2 HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

**Considered a hazardous mixture according to Reg. (EC) No 1272/2008 and their amendments. Classified as Dangerous Goods for transport purposes.**




#### CHEMWATCH HAZARD RATINGS

	Min	Max
Flammability	2	2
Toxicity	2	2
Body Contact	3	3
Reactivity	1	1
Chronic	2	2

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

Classification according to regulation (EC) No 1272/2008 [CLP] <sup>[1]</sup>	Flammable Liquid Category 2, Serious Eye Damage Category 1, Specific target organ toxicity - single exposure Category 3 (narcotic effects)
Legend:	1. Classified by Chemwatch; 2. Classification drawn from EC Directive 67/548/EEC - Annex I ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

### 2.2. Label elements

CLP label elements	  
SIGNAL WORD	<b>DANGER</b>

**Hazard statement(s)**

<b>H225</b>	Highly flammable liquid and vapour.
<b>H318</b>	Causes serious eye damage.
<b>H336</b>	May cause drowsiness or dizziness.

**Supplementary statement(s)**

Not Applicable

**Precautionary statement(s) Prevention**

<b>P101</b>	If medical advice is needed, have product container or label at hand.
-------------	---

**Precautionary statement(s) Response**

<b>P305+P351+P338</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
-----------------------	--

**Precautionary statement(s) Storage**

<b>P403+P235</b>	Store in a well-ventilated place. Keep cool.
------------------	--

**Precautionary statement(s) Disposal**

<b>P501</b>	Dispose of contents/container in accordance with local regulations.
-------------	---

**2.3. Other hazards**

Inhalation, skin contact and/or ingestion may produce health damage\*.

Cumulative effects may result following exposure\*.

May produce discomfort of the respiratory system and skin\*.

Limited evidence of a carcinogenic effect\*.

Repeated exposure potentially causes skin dryness and cracking\*.

REACH - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS****3.1. Substances**

See 'Composition on ingredients' in Section 3.2

**3.2. Mixtures**

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to regulation (EC) No 1272/2008 [CLP]
1.107-98-2 2.203-539-1 3.603-064-00-3 4.01-2119457435-35-XXXX	25-50	<u>propylene glycol monomethyl ether</u> <u>- alpha isomer</u>	Flammable Liquid Category 3, Specific target organ toxicity - single exposure Category 3 (narcotic effects); H226, H336 <sup>[3]</sup>
1.71-23-8 2.200-746-9 3.603-003-00-0 4.01-2119486761-29-XXXX	25-50	<u>n-propanol</u>	Flammable Liquid Category 2, Serious Eye Damage Category 1, Specific target organ toxicity - single exposure Category 3 (narcotic effects); H225, H318, H336 <sup>[3]</sup>
	balance	ingredients, non-hazardous	
<b>Legend:</b>	1. Classified by Chemwatch; 2. Classification drawn from EC Directive 67/548/EEC - Annex I; 3. Classification drawn from EC Directive 1272/2008 - Annex VI 4. Classification drawn from C&L		

**SECTION 4 FIRST AID MEASURES****4.1. Description of first aid measures**

<b>General</b>	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul> <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> </ul>
----------------	--

Continued...

	<ul style="list-style-type: none"> <li>▶ Transport to hospital, or doctor.</li> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul>
<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul>

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

To treat poisoning by the higher aliphatic alcohols (up to C7):

- ▶ Gastric lavage with copious amounts of water.
- ▶ It may be beneficial to instill 60 ml of mineral oil into the stomach.
- ▶ Oxygen and artificial respiration as needed.
- ▶ Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- ▶ To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- ▶ Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5]

#### BASIC TREATMENT

- ▶ Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for shock.
- ▶ Monitor and treat, where necessary, for pulmonary oedema.
- ▶ Anticipate and treat, where necessary, for seizures.
- ▶ **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- ▶ Give activated charcoal.

#### ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- ▶ Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- ▶ If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- ▶ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ▶ Drug therapy should be considered for pulmonary oedema.
- ▶ Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

#### EMERGENCY DEPARTMENT

- ▶ Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- ▶ Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- ▶ Acidosis may respond to hyperventilation and bicarbonate therapy.
- ▶ Haemodialysis might be considered in patients with severe intoxication.
- ▶ Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above.

Symptomatic and supportive therapy is advised in managing patients.

## SECTION 5 FIREFIGHTING MEASURES

**5.1. Extinguishing media**

- ▶ Alcohol stable foam.

**5.2. Special hazards arising from the substrate or mixture**

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

**5.3. Advice for firefighters**

<b>Fire Fighting</b>	▶ Alert Fire Brigade and tell them location and nature of hazard.
<b>Fire/Explosion Hazard</b>	▶ Liquid and vapour are flammable. Combustion products include: , carbon monoxide (CO) , carbon dioxide (CO2) , other pyrolysis products typical of burning organic material.

**SECTION 6 ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

See section 8

**6.2. Environmental precautions**

See section 12

**6.3. Methods and material for containment and cleaning up**

<b>Minor Spills</b>	▶ Remove all ignition sources.
<b>Major Spills</b>	▶ Clear area of personnel and move upwind.

**6.4. Reference to other sections**

Personal Protective Equipment advice is contained in Section 8 of the SDS.

**SECTION 7 HANDLING AND STORAGE****7.1. Precautions for safe handling**

<b>Safe handling</b>	▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b> ▶ Avoid all personal contact, including inhalation.
<b>Fire and explosion protection</b>	See section 5
<b>Other information</b>	▶ Store in original containers in approved flammable liquid storage area.

**7.2. Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	▶ Packing as supplied by manufacturer. ▶ For low viscosity materials (l) : Drums and jerry cans must be of the non-removable head type.
<b>Storage incompatibility</b>	Alcohols ▶ are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.

**7.3. Specific end use(s)**

See section 1.2

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION****8.1. Control parameters****DERIVED NO EFFECT LEVEL (DNEL)**

Not Available

**PREDICTED NO EFFECT LEVEL (PNEC)**

Not Available

**OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
UK Workplace Exposure Limits (WELs)	propylene glycol monomethyl ether - alpha isomer	1-Methoxypropan-2-ol	375 mg/m3 / 100 ppm	560 mg/m3 / 150 ppm	Not Available	Sk
European Union (EU) First List of Indicative Occupational Exposure Limit Values (IOELVs) (English)	propylene glycol monomethyl ether - alpha isomer	1-Methoxypropanol-2	375 mg/m3 / 100 ppm	568 mg/m3 / 150 ppm	Not Available	Skin
EU Consolidated List of Indicative Occupational Exposure Limit Values	propylene glycol monomethyl ether - alpha isomer	1-Methoxypropan-2-ol	375 mg/m3 / 100 ppm	568 mg/m3 / 150 ppm	Not Available	Skin

Continued...

(IOELVs)						
UK Workplace Exposure Limits (WELs)	n-propanol	Propan-1-ol	500 mg/m <sup>3</sup> / 200 ppm	625 mg/m <sup>3</sup> / 250 ppm	Not Available	Sk


**EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
propylene glycol monomethyl ether - alpha isomer	Propylene glycol monomethyl ether; (Ucar Triol HG-170)	100 ppm	160 ppm	660 ppm
n-propanol	n-Propanol (Propyl alcohol, n-)	250 ppm	670 ppm	4000 ppm

Ingredient	Original IDLH	Revised IDLH
propylene glycol monomethyl ether - alpha isomer	Not Available	Not Available
n-propanol	4,000 ppm	800 ppm

**8.2. Exposure controls**

<b>8.2.1. Appropriate engineering controls</b>	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
<b>8.2.2. Personal protection</b>	
<b>Eye and face protection</b>	▶ Safety glasses with side shields.
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	▶ Wear chemical protective gloves, e.g. PVC. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. ▶ Neoprene gloves
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	▶ Overalls. - Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
<b>Thermal hazards</b>	Not Available

**Recommended material(s)****GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

151125 Lyreco Permanent Marker C/Tip Red

Material	CPI
NEOPRENE	A
NITRILE	B
PVC	B

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

**Respiratory protection**

Type A Filter of sufficient capacity.

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	A-AUS / Class 1	-	A-PAPR-AUS / Class 1
up to 25 x ES	Air-line*	A-2	A-PAPR-2
up to 50 x ES	-	A-3	-
50+ x ES	-	Air-line**	-

\* - Continuous-flow; \*\* - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

**8.2.3. Environmental exposure controls**

See section 12

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

<b>Appearance</b>	Red flammable liquid with a characteristic odour; does not mix with water.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	0.83

<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	270
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	4
<b>Initial boiling point and boiling range (°C)</b>	96	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	21	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	HIGHLY FLAMMABLE.	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	13.5	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	2.1	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	1.9 @ 20C	<b>Gas group</b>	Not Available
<b>Solubility in water (g/L)</b>	Immiscible	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	860

**9.2. Other information**

Not Available

**SECTION 10 STABILITY AND REACTIVITY**

<b>10.1. Reactivity</b>	See section 7.2
<b>10.2. Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Presence of elevated temperatures.</li> <li>▶ Unstable in the presence of incompatible materials.</li> </ul>
<b>10.3. Possibility of hazardous reactions</b>	See section 7.2
<b>10.4. Conditions to avoid</b>	See section 7.2
<b>10.5. Incompatible materials</b>	See section 7.2
<b>10.6. Hazardous decomposition products</b>	See section 5.3

**SECTION 11 TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

<b>Inhaled</b>	<p>Inhalation of vapours may cause drowsiness and dizziness.</p> <p>There is some evidence to suggest that the material can cause respiratory irritation in some persons.</p> <p>Subjects unacclimatised to n-propanol exposure experienced mild irritation of the eyes, nose and throat at a concentration of 400 parts per million.</p> <p>Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes.</p> <p>Inhalation hazard is increased at higher temperatures.</p> <p>PGME has an offensive odour, and may cause drowsiness and unconsciousness if higher concentrations are inhaled, and severe reactions involving the eyes, nose and throat.</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p>		
<b>Ingestion</b>	<p>Overexposure to non-ring alcohols causes nervous system symptoms.</p> <p>Propylene glycol monomethyl ether has low hazard if taken orally.</p> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p>		
<b>Skin Contact</b>	<p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.</p> <p>There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time.</p> <p>The calculated human skin permeability coefficient for n-propanol by the U.S. Environment Protection Agency is 1.3 x 10<sup>-3</sup> cm/hr.</p> <p>Most liquid alcohols appear to act as primary skin irritants in humans.</p> <p>Harmful amounts of PGME may be absorbed through the skin following extensive prolonged contact; this may result in drowsiness, unconsciousness and depression.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.</p>		
<b>Eye</b>	<p>If applied to the eyes, this material causes severe eye damage.</p> <p>The vapour when concentrated has pronounced eye irritation effects and this gives some warning of high vapour concentrations.</p>		
<b>Chronic</b>	<p>There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>N-propanol is shown to cause dose dependent severe liver injury, malignant tumours (blood and liver cancers) and benign tumours in rats.</p> <p>When taken repeatedly, PGME may cause damage to liver and kidney, drowsiness and even unconsciousness and death.</p> <p>Some glycol esters and their ethers cause wasting of the testicles, reproductive changes, infertility and changes to kidney function.</p> <p>Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes.</p>		
<b>151125 Lyreco Permanent Marker C/Tip Red</b>	<table border="1" style="width: 100%;"> <tr> <td style="text-align: center;"><b>TOXICITY</b></td> <td style="text-align: center;"><b>IRRITATION</b></td> </tr> </table>	<b>TOXICITY</b>	<b>IRRITATION</b>
<b>TOXICITY</b>	<b>IRRITATION</b>		

Continued...

## 151125 Lyreco Permanent Marker C/Tip Red

	Not Available	Not Available
propylene glycol monomethyl ether - alpha isomer	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit) 230 mg mild
	Inhalation (rat) LC50: 10000 ppm/5 hr <sup>[2]</sup>	Eye (rabbit) 500 mg/24 h.
	Oral (rat) LD50: 5207.2 mg/kg <sup>[1]</sup>	Eye (rabbit): 100 mg SEVERE
n-propanol	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 4032 mg/kg <sup>[1]</sup>	Eye (rabbit): 20 mg/24h moderate
	Oral (rat) LD50: 1870 mg/kg <sup>[2]</sup>	Eye (rabbit): 4 mg open SEVERE
		Skin (rabbit): 20 mg/24h moderate
		Skin (rabbit): 500 mg open mild

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

151125 Lyreco Permanent Marker C/Tip Red	No significant acute toxicological data identified in literature search.
PROPYLENE GLYCOL MONOMETHYL ETHER - ALPHA ISOMER	for propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA); tripropylene glycol methyl ether (TPM). NOTE: For PGE - mixed isomers: Exposure of pregnant rats and rabbits to the substance did not give rise to teratogenic effects at concentrations up to 3000 ppm.
N-PROPANOL	The material may produce severe irritation to the eye causing pronounced inflammation. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	☐	Carcinogenicity	☐
Skin Irritation/Corrosion	☐	Reproductivity	☐
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	☐	STOT - Repeated Exposure	☐
Mutagenicity	☐	Aspiration Hazard	☐

**Legend:** ✗ – Data available but does not fill the criteria for classification  
 ✓ – Data available to make classification  
 ☐ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## 12.1. Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
propylene glycol monomethyl ether - alpha isomer	LC50	96	Fish	1005.858mg/L	3
propylene glycol monomethyl ether - alpha isomer	EC50	48	Crustacea	>500mg/L	1
propylene glycol monomethyl ether - alpha isomer	EC50	96	Algae or other aquatic plants	7152.973mg/L	3
propylene glycol monomethyl ether - alpha isomer	EC50	384	Crustacea	227.843mg/L	3
propylene glycol monomethyl ether - alpha isomer	NOEC	96	Fish	=4600mg/L	1
n-propanol	LC50	96	Fish	163.437mg/L	3
n-propanol	EC50	48	Crustacea	=3642mg/L	1
n-propanol	EC50	96	Algae or other aquatic plants	861.193mg/L	3
n-propanol	EC50	384	Crustacea	37.744mg/L	3

**Legend:**

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

Continued...

**12.2. Persistence and degradability**

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol monomethyl ether - alpha isomer	LOW (Half-life = 56 days)	LOW (Half-life = 1.7 days)
n-propanol	LOW	LOW

**12.3. Bioaccumulative potential**

Ingredient	Bioaccumulation
propylene glycol monomethyl ether - alpha isomer	LOW (BCF = 2)
n-propanol	LOW (LogKOW = 0.25)

**12.4. Mobility in soil**

Ingredient	Mobility
propylene glycol monomethyl ether - alpha isomer	HIGH (KOC = 1)
n-propanol	HIGH (KOC = 1.325)

**12.5. Results of PBT and vPvB assessment**

	P	B	T
Relevant available data	Not Available	Not Available	Not Available
PBT Criteria fulfilled?	Not Available	Not Available	Not Available


**12.6. Other adverse effects**

No data available

**SECTION 13 DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods**

Product / Packaging disposal	▶ Recycle wherever possible or consult manufacturer for recycling options.
Waste treatment options	Not Available
Sewage disposal options	Not Available

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

	
Marine Pollutant	NO
HAZCHEM	•3Y

**Land transport (ADR)**

14.1. UN number	1263
14.2. UN proper shipping name	PAINT or PAINT RELATED MATERIAL
14.3. Transport hazard class(es)	Class : 3 Subrisk : Not Applicable
14.4. Packing group	III
14.5. Environmental hazard	Not Applicable
14.6. Special precautions for user	Hazard identification (Kemler) : 30 Classification code : F1 Hazard Label : 3 Special provisions : 163 640E 650 Limited quantity : 5 L

**Air transport (ICAO-IATA / DGR)**

14.1. UN number	1263
-----------------	------

<b>14.2. UN proper shipping name</b>	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds)	
<b>14.3. Transport hazard class(es)</b>	ICAO/IATA Class	3
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	3L
<b>14.4. Packing group</b>	III	
<b>14.5. Environmental hazard</b>	Not Applicable	
<b>14.6. Special precautions for user</b>	Special provisions	A3 A72 A192
	Cargo Only Packing Instructions	366
	Cargo Only Maximum Qty / Pack	220 L
	Passenger and Cargo Packing Instructions	355
	Passenger and Cargo Maximum Qty / Pack	60 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y344
	Passenger and Cargo Limited Maximum Qty / Pack	10 L

**Sea transport (IMDG-Code / GGVSee)**

<b>14.1. UN number</b>	1263	
<b>14.2. UN proper shipping name</b>	PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)	
<b>14.3. Transport hazard class(es)</b>	IMDG Class	3
	IMDG Subrisk	Not Applicable
<b>14.4. Packing group</b>	III	
<b>14.5. Environmental hazard</b>	Not Applicable	
<b>14.6. Special precautions for user</b>	EMS Number	F-E, S-E
	Special provisions	163 223 367 955
	Limited Quantities	5 L

**Inland waterways transport (ADN)**

<b>14.1. UN number</b>	1263	
<b>14.2. UN proper shipping name</b>	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)	
<b>14.3. Transport hazard class(es)</b>	3	Not Applicable
<b>14.4. Packing group</b>	III	
<b>14.5. Environmental hazard</b>	Not Applicable	
<b>14.6. Special precautions for user</b>	Classification code	F1
	Special provisions	163; 367; 640E; 650
	Limited quantity	5 L
	Equipment required	PP, EX, A
	Fire cones number	0

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 REGULATORY INFORMATION****15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture****PROPYLENE GLYCOL MONOMETHYL ETHER - ALPHA ISOMER(107-98-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)	European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)
EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of Dangerous Substances - updated by ATP: 31
European Customs Inventory of Chemical Substances ECICS (English)	European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI
European Trade Union Confederation (ETUC) Priority List for REACH Authorisation	UK Workplace Exposure Limits (WELs)

**N-PROPANOL(71-23-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles  
European Customs Inventory of Chemical Substances ECICS (English)

European Union - European Inventory of Existing Commercial Chemical Substances (EINECS) (English)

European Union (EU) Annex I to Directive 67/548/EEC on Classification and Labelling of Dangerous Substances - updated by ATP: 31

European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

UK Workplace Exposure Limits (WELs)

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : 98/24/EC, 92/85/EC, 94/33/EC, 91/689/EEC, 1999/13/EC, Commission Regulation (EU) 2015/830, Regulation (EC) No 1272/2008 and their amendments

## 15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

### ECHA SUMMARY

Ingredient	CAS number	Index No	ECHA Dossier
propylene glycol monomethyl ether - alpha isomer	107-98-2	603-064-00-3	01-2119457435-35-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Flam. Liq. 3, STOT SE 3	GHS07, GHS02, Wng	H226, H336
2	Flam. Liq. 3, STOT SE 3, Not Classified, Acute Tox. 4, Eye Irrit. 2	GHS02, Wng, GHS08, GHS03	H336, H371, H335, H225

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
n-propanol	71-23-8	603-003-00-0	01-2119486761-29-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Flam. Liq. 2, Eye Dam. 1, STOT SE 3	GHS07, GHS02, GHS05, Dgr	H225, H318, H336
2	Flam. Liq. 2, Eye Dam. 1, STOT SE 3, Acute Tox. 4, Not Classified	GHS02, GHS05, Dgr, GHS08	H225, H318, H336, H302

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (n-propanol; propylene glycol monomethyl ether - alpha isomer)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
<b>Legend:</b>	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets)

## SECTION 16 OTHER INFORMATION

### Full text Risk and Hazard codes

<b>H226</b>	Flammable liquid and vapour.
<b>H302</b>	Harmful if swallowed.
<b>H335</b>	May cause respiratory irritation.
<b>H371</b>	May cause damage to organs.

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

### Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average

PC—STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit,  
IDLH: Immediately Dangerous to Life or Health Concentrations  
OSF: Odour Safety Factor  
NOAEL: No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index

This document is copyright.