## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink 6061

black

**Revision date:** 28.04.2017 **Version (Revision):** 9.0.0 (8.0.0)

**Print date :** 28.04.2017

#### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

Stamping ink 6061 black (15010230001038)

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Industrial marking ink

#### 1.3 Details of the supplier of the safety data sheet

## Supplier (manufacturer/importer/only representative/downstream user/distributor)

Stefan Kupietz GmbH & Co. KG

Chemische Fabrik

Street: August-Wilhelm-Kühnholz-Str. 9
Postal code/city: 26135 Oldenburg
Telephone: +49(0)441/20 69 50
Telefax: +49(0)441 /20 69 520

**Information contact:** E-Mail: info@kupietz.de

## 1.4 Emergency telephone number

Poison emergency centre +49-551-19240

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Dam. 1; H318 - Serious eye damage/eye irritation: Category 1; Causes serious eye damage.

#### 2.2 Label elements

# Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms



Corrosion (GHS05)

#### Signal word

Danger

#### Hazard components for labelling

2-ETHYLHEXANE-1,3-DIOL; CAS No.: 94-96-2

#### **Hazard statements**

H318 Causes serious eye damage.

#### **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P310 Immediately call a POISON CENTER/doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

#### 2.3 Other hazards

Page: 1 / 6

(EN/D)

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 6061

black

**Revision date:** 28.04.2017 **Version (Revision):** 9.0.0 (8.0.0)

**Print date :** 28.04.2017

None

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### **Hazardous ingredients**

2-ETHYLHEXANE-1,3-DIOL; EC No.: 202-377-9; CAS No.: 94-96-2

Weight fraction: < 25 %

Classification 1272/2008 [CLP]: Eye Dam. 1; H318

**Additional information** 

Full text of H- and EUH-phrases: see section 16.

#### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

#### **General information**

Immediately remove all contaminated clothing.

#### **Following inhalation**

Provide fresh air.

#### In case of skin contact

Wash away with soap and water and rinse.

#### After eye contact

Flush with plenty of water (10 - 15 min.). Call a physician.

#### After ingestion

Drink plenty of water.

## 4.2 Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

None

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam , Carbon dioxide (CO2) , Extinguishing powder or Water spray jet .

## 5.2 Special hazards arising from the substance or mixture

None

#### **5.3** Advice for firefighters

None

#### 5.4 Additional information

Cool endangered containers with water in case of fire.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources on account of the organic solvent content and air room well. Do not inhale vapours.

#### 6.2 Environmental precautions

Page: 2 / 6

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink 6061

black

**Revision date:** 28.04.2017 **Version (Revision):** 9.0.0 (8.0.0)

**Print date :** 28.04.2017

Take up with a liquid absorbing material and proceed according to the waste disposal regulations. Do not allow to enter into surface water or drains.

## 6.3 Methods and material for containment and cleaning up

#### For cleaning up

Remove mechanically, take-up residues with absorbing material.

#### 6.4 Reference to other sections

None

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Normal precautions taken when handling chemicals should be observed. Only use in locations with adequate suction ventilation.

#### **Protective measures**

#### Measures to prevent fire

Take precautionary measures against static discharges. Keep away from sources of ignition. - No smoking.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Do not leave vessels open, earth storage containers.

#### Hints on joint storage

Store the foodstuffs separately. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Storage class: 10

Storage class (TRGS 510): 10

#### Further information on storage conditions

Store containers tightly closed in a cool well ventilated place.

## 7.3 Specific end use(s)

None

#### **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

None

#### 8.2 Exposure controls

#### **Personal protection equipment**

## **Eye/face protection**

Use tightly fitting safety glasses.

## Skin protection

#### **Hand protection**

Use protective butyl rubber gloves (0,5 mm). Permeation time of glove material: level >= 240 min (4h) EN374

#### **Respiratory protection**

#### Suitable respiratory protection apparatus

Respiratory protection necessary at: aerosol or mist formation. Half-face mask (DIN EN 140) Filtering device (full mask or mouthpiece) with filter: A

#### **General health and safety measures**

The usual precautionary measures for the handling of chemicals have to be observed.

#### **SECTION 9: Physical and chemical properties**

Page: 3 / 6

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink 6061

black

**Revision date:** 28.04.2017 **Version (Revision):** 9.0.0 (8.0.0)

**Print date :** 28.04.2017

## 9.1 Information on basic physical and chemical properties

**Colour:** black **Odour:** characteristic

#### Safety relevant basis data

Physical state: liquid

Initial boiling point and boiling ( 1013 hPa ) > 140 °C

Flash point: > 61 °C Brookfield

Vapour pressure: (50°C) < 1100 hPa Density: (20°C) 0,955 g/cm<sup>3</sup> approx. Solvent separation test : (20°C) < 3 % pH: 3 approx.

**Flow time :** (20 °C ) approx. 224 s DIN-cup 4 mm

#### 9.2 Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No information available.

#### 10.2 Chemical stability

No information available.

#### 10.3 Possibility of hazardous reactions

No information available.

#### 10.4 Conditions to avoid

None, if handled according to order.

## 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. In connection with inorganic and organic acids, acid chlorides violent reactions can take place and CO2 released. Formation of hydrogen by acids, lyes, moisture possible.

#### 10.6 Hazardous decomposition products

No information available.

#### **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

## **Acute effects**

#### **Acute oral toxicity**

Parameter: LD50 ( 2-ETHYLHEXANE-1,3-DIOL ; CAS No. : 94-96-2 )

Exposure route: Oral
Species: Rat
Effective dose: 1400 mg/kg

Acute dermal toxicity

Parameter: LD50 ( 2-ETHYLHEXANE-1,3-DIOL; CAS No.: 94-96-2 )

Exposure route: Dermal Species: Rabbit Effective dose: 2 g/kg

Acute inhalation toxicity

Page: 4/6

(EN/D)

## according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Stamping ink 6061

black

**Revision date:** 28.04.2017 **Version (Revision):** 9.0.0 (8.0.0)

**Print date :** 28.04.2017

#### Practical experience/human evidence

Slight narcotic effect. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

No information available.

#### 12.2 Persistence and degradability

In case of appropriate conduction into adapted biological purification plants no disturbances have to be expected.

#### 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

No information available.

#### 12.6 Other adverse effects

No information available.

## 12.7 Additional ecotoxicological information

Do not empty into waters or drains.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Dispose according to legislation.

#### **Product/Packaging disposal**

Waste codes/waste designations according to EWC/AVV

- 080111

#### Waste treatment options

#### Appropriate disposal / Package

Contaminated packaging should be residue-free emptying. They can then be recycled after appropriate cleaning (Waste code 080112 contains no organic solvents). Contaminated packaging should be disposed of like the product. (Waste code 150110)

## **SECTION 14: Transport information**

#### 14.1 UN number

No dangerous good in sense of these transport regulations.

## 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

#### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

## 14.4 Packing group

No dangerous good in sense of these transport regulations.

#### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

#### 14.6 Special precautions for user

None

Page: 5 / 6

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Stamping ink 6061

black

**Revision date :** 28.04.2017 **Version (Revision) :** 9.0.0 (8.0.0)

**Print date :** 28.04.2017

## **SECTION 15: Regulatory information**

# Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** 

**Technische Anleitung Luft (TA-Luft)** 

Weight fraction (Number 5.2.5. I): < 5 %

Water hazard class (WGK)

Class: 1 (Slightly hazardous to water) Classification according to VwVwS

#### 15.2 Chemical safety assessment

No information available.

#### **SECTION 16: Other information**

## 16.1 Indication of changes

03. Hazardous ingredients

## 16.2 Abbreviations and acronyms

None

## 16.3 Key literature references and sources for data

None

# Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

No information available.

## 16.5 Relevant H- and EUH-phrases (Number and full text)

H318 Causes serious eye damage.

## 16.6 Training advice

None

#### 16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 6 / 6