ChemTek™ 38-514

TECHNICAL DATASHEET

Butyl/VITON Print date 23-08-2017

Glove material

Butyl polymer (Coating material)

Possible Harmful ingredients

Sensitizers

- Tetramethylthiuram disulfide
- 2-Mercaptobenzothiazole disulfide
- Dipentamethylene thriuram disulfide

Only a very small number of users may be sensitised to this ingredient in the glove and hence may develop irritant and/or allergic contact reactions.

Reach Regulation 1907/2006

For more information, please consult the REACH statement on the Ansell website

Properties

- Excellent physical properties
- Good dexterity

EN Test Data

Liquidproofness:

Acceptable Quality Level 1.5 or EN performance level 2

Chemical permeation:

For more information on chemical permeation, please consult

Ansell website

EN388:2003

a b c d e f

European conformity

Gloves conform to the requirements of the European Directive 89/686/EEC and to the European standards EN 420:2003 + A1:2009 and EN 388:2003,EN 374:2003

They are categorised in "Complex Design" (= Protection against mortal risks).

EC-Type Examination Certificate and EC-quality control for the final product by

Centexbel

Technologiepark 7

B-9052 Zwijnaarde

Application - Limitations of use

Hand protection

Do not use against flames or temperatures < - 25°C or > 100°C

Storage

Keep away from sources of ozone or ignition.

Keep out of direct sunlight; store in a cool and dry place.

Coating material	Grip design	Cuff style	Colour	AQL (EN374)	EN Size	Length mm	Thickness mm	Packaging
Butyl polymer	Rough Finish	Rolled beaded	Black	1.5	7, 8, 9, 10, 11	350	0.35	36 pairs in a carton;
								individually wrapped with
								insert

