

JALAS® 3358S EASY GRIP

EN ISO 20345:2011, S3 HRO SRB

PROPERTIES

Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

SPECIFICATION

TYPE OF SHOE Safety footwear, low shoes

NAIL PROTECTION MATERIAL Steel

FITTING Regular

SIZE RANGE (EU) 36-47

COLLECTION Grip

PLATFORM Grip

UPPER MATERIAL PU-coated leather, split leather

PRONOSE MATERIAL PU

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester, polyamide

SOLE MATERIAL PU midsole, rubber outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Velcro®

COLOUR Black, grey, yellow



SIZE	ART. NO.	EAN NO.
36	3358s-36	6408487437830
37	3358s-37	6408487437847
38	3358s-38	6408487437854
39	3358s-39	6408487437861
40	3358s-40	6408487437878
41	3358s-41	6408487437885
42	3358s-42	6408487437892
43	3358s-43	6408487437908
44	3358s-44	6408487437915
45	3358s-45	6408487437922
46	3358s-46	6408487437939
47	3358s-47	6408487437946

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 3358S EASY GRIP

FEATURES

ProNose toe reinforcement, KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit), heat-resistant upper, heat-resistant outsole, oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD), heat-resistant, withstands welding sparks and grinding splash

PRIMARY PROTECTION

Prevents risk of: toe injuries, nail penetration, antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, warm surfaces, environments with risk for outsole penetration, harsh environments

PRIMARY AREAS OF USE

Sheet-metal work, metalwork, welding, hot work

PRIMARY INDUSTRIES OF USE

Metal fabrication



CE



Aluminium toecap



Heat-resistant upper



Nail protection in steel



Anti-static properties



Heat-resistant outsole



ESD



Water repellent



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-12-27

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 3358S EASY GRIP

COMPLIANCE
EN ISO 20345:2011

COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-resistant upper

P: Penetration-resistant outsole

HRO: Heat-resistant outsole compound tested at 300°C

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRB: Slip-resistance on steel floor with glycerol

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Heat-resistant upper



Nail protection in steel



Anti-static properties



Heat-resistant outsole



ESD



Water repellent



Oil-resistant outsole



ProNose toe reinforcement



Ergothon Shock Absorption System

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2016-12-27

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com