







DW OFFICE ML

DW Office ML is a single-sided premium wireless DECT headset for quality-conscious business professionals demanding exceptional performance and supreme comfort. Certified for Skype for Business and designed for all-day use, the DW Office ML connects directly to desk phone and Skype for Business via PC to deliver excellent sound quality around the office. The iconic design of the DW Office ML puts it in a class of its own.

Sound leadership

Featuring Sennheiser Voice Clarity and a noise-cancelling microphone, the DW Office ML gives users a natural listening experience while maximizing speech intelligibility for both speaker and listener. Advanced wideband audio and DSP (Digital Signal Processing) ensure clear, detailed sound for a better conversational experience in noisy working environments.

Quality design

With its award-winning iconic design, the DW Office ML stands out for style and performance. From its distinctive base station, with simple setup and intuitive user interface to its lightweight headset, the DW Office ML is designed to both look good and provide all-day wearing comfort.

User focus

DW Office ML is designed to maximize productivity and flexibility in busy offices

with its long distance wireless range up to 180 m (590 ft) with line of sight and 55 m (180 ft) in a typical office environment. A DECT protected frequency band eliminates interference with WIFI networks and efficient encryption ensures secure conversations. One touch switching between desk phone and Skype for Business, easy call management, convenient phone conferencing and hot desking offer maximum flexibility.

With 8 hours wideband and 12 hours narrowband for a full workday of talk time, the DW Office ML features intelligent fast charging, which delivers 50% in just 20 minutes. ActiveGard® provides protection against acoustic injury and a volume limiter guarantees a safe sound level at all times. The FlexFit™ wearing style system offers the choice between a headband, ear hook or neckband* solution for the perfect customized fit.

Features and Benefits:

- Sennheiser Voice Clarity wideband sound for natural listening experiences
- Dual connectivity one touch on the base station switches between desk phone and Skype for Business via PC
- Certified for Skype for Business for maximum productivity
- Noise-cancelling microphone for speech clarity

- Digital Signal Processing for echo cancelling and audio equalization
- Iconic design form and function combine for premium looks and performance
- Perfect customized fit with the FlexFit[™] system, offering 3 wearing style solutions. Choose between headband, ear hook or neckband*
- Lightweight headset design for all-day comfort
- Simple product setup with DIP Switches
- Intuitive user interface with answer/end**, microphone mute and volume +/-
- Full workday of talk time 8 hours wideband and 12 hours narrowband
- Intelligent fast charging delivers 50% in just 20 minutes
- DECT protected frequency band without interference with WIFI networks
- Efficient encryption for secure conversations
- Long distance wireless range up to 180 m
 (590 ft) with line of sight 55 m (180 ft)
 in typical office environment
- Hot desking with fast, secure pairing– simply dock in the base station
- Phone conferences intuitive & easy setup of up to 4 headsets with same base station
- ActiveGard® technology protects users against acoustic injury caused by sudden sound burst on the line
- Two years warranty for peace of mind
- * Neckband available as accessory
- ** Answer/end call requires EHS cable for desk phone

Product Information

Product aname DW 2 Office ML = EU							
### PATH NO.	Product name	DW Office ML - EU	DW Office ML - UK	DW Office ML - US	DW Office ML - AUS		
Mon. Mol.							
### Art. No.							
Art. No. 504.55 504.55 504.55 504.55 504.57 Protouct description (microstription (microstription) (microstri							
Nechania Data							
Readband or ear hook)							
DECT for US DECT 6.0 (1.920 to 1.930 MHz) Ves (Headdest) Connects to desx phone and Skype for Business Ves, can be activated on the base station Connects to desx phone and Skype for Business Ves, can be activated on the base station Firmware requirement His 1.0 (accessory – order Separately) Ves (accessory – order Separately) Ves (adapter separately) Ves (Microphone Ves Frequency response Wirdeband Mode Frequency	Product description						
DECT for US DECT for (1 1 20 to 1 330 MHz) CAP Compatible Ves (Modeste) Base Station Connects to base station Base Station Connects to base sphone and Skype for Business Headset Aut Unix to Base Yes, can be activated on the base station Firmware requirement For newest version please use the Seantheiser Updater. Please refer to sennheiser.com/cco/software EHS (Electronic Note Switch) Yes (casessay - order separately) Call control Yes. Skype for Business certified Yes Frequency response Wideband Mode 150 Hz - 6.8 KHz Frequency response Wideband Mode 150 Hz - 6.8 KHz Frequency response Wideband Mode Neodymlum Magnet Speaker Frequency response Wideband Mode Neodymlum Magnet Speaker Frequency response Wideband Mode 150 Hz - 6.8 KHz Frequency response Wideband Mode 150 Hz - 6.8 KHz Frequency response Wideband Mode 150 Hz - 6.8 KHz Frequency response Wideband Mode 150 Hz - 6.8 KHz Brade and Lamperature range 45 °C to + 45 °C (+41 °E to +138 °F) Weight, ac hook version 26 y 0 x 0 x 0 x 0 x 0 x 0 x 0 x 0 x 0 x 0	Technical Data	(110000001100110011)					
GAP compatible Yes (thosizen) Headset Connects to base station Base Station Connects to desk phone and Skype for Business Flammare requirement For necessity version place use the Seminheiser Updater. Please refer to sennheiser.com/cco/software ENS (Electronic Hook Switch) Yes (accessory - order EHS adapter separately) Microphone HS. 10 (accessory - order Separately) Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Narrowband Mode Mute Microphone NB 2 - 6.8 KHz Speaker Modymium Magnet Speaker Speaker Modymium Magnet Speaker Frequency response Wideband Mode 15 **C to + 45 **C (+41 **F to + 113 **F) Frequency response Narrowband Mode 15 **C to + 45 **C (+41 **F to + 113 **F) Frequency response Narrowband Mode 15 **C to + 45 **C (+41 **F to + 113 **F) Frequency response Narrowband Mode 15 **C to + 45 **C (+41 **F to + 113 **F) Weight, ear hock version 24 g / 08 60 2 Weight, ear hock version 25 **C to + 45 **C (+41 **F to + 113 **F) Weight, ear hock version 26 g / 08 60 2 Weight, ear hock version 26 g / 08 60 2 Range - in	DECT for EU, UK, AUS	DECT (1.880 to 1.900 MH	z)				
Headset Connects to lass station Connects to disk phone and Skype for Business Headset Auto Link to Base Firmware requirement For newest version please use the Sennheiser Updater. Please refer to sennheiser.com/cco/software Heis (Electronic Hook Switch Ves (accessory – order separately) Mechanical Hook Liffer Mechanic	DECT for US	DECT 6.0 (1.920 to 1.930	MHz)				
Base Station Connects to desk phone and Skype for Business Headaset Auto Link to Base Yes, can be activated on the base station Firmware requirement For newest version please use the Sennheiser Updater, Please refer to sennheiser.com/cco/software File (Sectronic Hook Switch) Yes (accessory – order EHS adapter separately) Yes. Plug and play certified for Skype for Business Skype for Business certified Yes. Plug and play certified for Skype for Business Yes Plug and play certified for Skype for Business Yes Yes Plug and play certified for Skype for Business Yes	GAP compatible	Yes (Headset)					
Feedback Auto Link to Base Yes, can be activated on the base station For newest version please use the Sennheiser Updater, Please refer to sennheiser.com/cco/software Yes (accessory – order EHS adapter separately) HSL 10 (accessory – order EHS adapter separately) HSL 10 (accessory – order Separately) HSL 10 (a	Headset	Connects to base station					
Feedback Auto Link to Base Yes, can be activated on the base station For newest version please use the Sennheiser Updater, Please refer to sennheiser.com/cco/software Yes (accessory – order EHS adapter separately) HSL 10 (accessory – order EHS adapter separately) HSL 10 (accessory – order Separately) HSL 10 (a	Base Station	Connects to desk phone a	and Skype for Business				
Firmware requirement For newest version please use the Sennheiser Updater. Please refer to sennheiser.com/cco/software Pers (Electronic Hook Switch) Yes (accessory – order Els dalpeter separately)	Headset Auto Link to Base						
Ves (accessory – order EH5 adapter separately)				r Please refer to sennheiser c	om/cco/software		
Mechanical Hook Lifter	•			i. i lease rerei to semineiser.e	5111, cc3, 531t. Tare		
Call control Yes. Plug and play certified for Skype for Business Skype for Business certified Yes Microphone 150 Hz − 6.8 KHz Frequency response Narrowband Mode Prequency response Narrowband Mode Prequency response Wildeband Mode Prequency response Wildeband Mode Prequency response Narrowband Mode Preparative range Preparative Preparat							
Microphone							
Microphone 150 Hz − 6.8 KHz Frequency response Narrowband Mode Mute Microphone 760 Hz − 8.8 KHz Speaker type Neodymium Magnet Speaker Frequency response Wideband Mode Frequency response Wideband Mode Frequency response Narrowband Mode 150 Hz − 6.8 KHz General Data 0 berational temperature range 150 Hz − 6.8 KHz Oberational temperature range +5 °C to +45 °C (+41 °F to +113 °F) Storage temperature range +5 °C to +45 °C (+41 °F to +138 °F) Weight, ear hook version 24 g / 0.86 oz Weight, theadband version 50 g / 1.76 oz Ear pad size 0 50 mm / 1.96 in Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – in typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Wideband Mode Up to 12 hours Talk time in Marrowband Mode Up to 12 hours Gharge time 0 – 100% Yes w after 30 minutes Package dimensions (H x W x D) 16.5 cm x 16 cm x 16 cm Package dimensions (H x W x D) 36 x 38 x 38 cm / 14.18 x 14.97 x			ed for skype for business				
Frequency response Wideband Mode Frequency response Narrowband Mode Mute Microphone Yes		_ <u>res</u>					
Frequency response Narrowband Mode Speaker 300 Hz = 3.5 KHz Speaker type Neodymium Magnet Speaker Frequency response Wideband Mode Frequency response Narrowband Mode Operational temperature range 150 Hz = 6.8 KHz Operational temperature range Velight, ear hook version 25 °C to +45 °C (+41 °F to +113 °F) Storage temperature range Welight, ear hook version 24 y 0.86 cz Surgh, ear hook version 90 y 1.76 oz Ear pad size Battery (Lithium Polymer) 25 °C to +45 °C (+45 °C +158 °F) Ves with nameplate on headset Range – line of sight 180 m / 590 ft Range – line of sight 180 m / 590 ft Range – In lypical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Wideband Mode Stand by time Up to 10 Hours Charge time 0 – 50% 100 Hours Charge time 0 – 100% 16.5 cm x 16 cm x 16 cm Package dimensions (H x W x D) 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in Master carton weight 36 x 38 x 38 cm / 14.18 x 14.97 x 14		 150 Hz = 6.8 KHz					
Mute Microphone Yes Speaker Neodymium Magnet Speaker Frequency response Wideband Mode Frequency response Narrowband Mode Frequency response Narrowband Mode Frequency response Narrowband Mode General Data 150 Hz − 6.8 KHz Operational temperature range Storage temperature range Weight, ear hook version 24 g / 0.86 oz 24 ° (1.4 ° F to +113 ° F) Weight, headband version Ear pad size Personalization Personalization Yes with nameplate on headset Name Frequency Personalization Yes with nameplate on headset Name Frequency Personalization Yes (sitsance between headset and base) 18 0m / 590 ft. Range – In typical office building Automatic power adjustment Pyto 18 hours Package wing time 0 – 50%. 18 0m / 590 ft. 18 0m / 590 ft. Talk time in Narrowband Mode Up to 12 hours Package time 0 – 50%. 10 to 12 hours Package time 0 – 50%. 20 minutes Charge time 0 – 50%. 20 minutes 20 minutes Charge time 0 – 50%. 36 × 38 × 38 cm / 14.18 × 14.97 × 14.97 in Master carton dimensions (H x W x D) Assate carton weight Assate carton dimensions (H x W x D) Assate carton weight Assate carton weight Assa							
Speaker Neodymium Magnet Speaker Speaker type Neodymium Magnet Speaker Frequency response Wideband Mode Frequency response Narrowband Mode Operational temperature range 150 Hz − 6.8 KHz Operational temperature range +5 °C to + 45 °C (+41 °F to +113 °F) Storage temperature range +5 °C to + 45 °C (+41 °F to +158 °F) Weight, hear hook version 24 g / 0.86 oz Weight, hearband version 50 g / 1.76 oz Ear pad size 0.50 mm / 1.96 in Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – in typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Narrowband Mode Up to 120 Hours Stand by time Up to 120 Hours Auto – headset OFF when out of range Yes * after 30 minutes Charge time 0 – 50% 20 minutes Charge time 0 – 100% 1 hour Package dimensions (H x W x D) 45.5 cm x 16 cm x 16 cm Package dimensions (H x W x D) 36 x 38 x 38 cm / 14.1							
Speaker type							
Frequency response Wideband Mode Frequency response Narrowband Mode General Data Operational temperature range Operational temperature range Storage temperature range Velight, ear hook version Weight, charbook version Ear pad size Storage		Neodymium Magnet Spea	aker				
Frequency response Narrowband Mode 300 Hz − 3.5 KHz General Data F° Cto + 45° C (+41° F to +113° F) Operational temperature range +5° Cto + 45° C (+41° F to +158° F) Storage temperature range +20° Cto + 70° C (-4° F to +158° F) Weight, ear hook version 24 g / 0.86 oz Weight, headband version 50 g / 1.76 oz Ear pad size 65 mm / 1.96 in Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – In typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Wideband Mode Up to 8 hours Talk time in Narrowband Mode Up to 100 Hours Stand by time Up to 100 Hours Charge time 0 – 50% 20 minutes Charge time 0 – 100% 1 hour Package dimensions (H x W x D) 16.5 cm x 16 cm x 16 cm Package weight 940 g / 32.9 oz Units in distributor master carton 8 Master carton weight 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in Safety			anci				
Operational temperature range Operational temperature range Very Storage temperature range Velight, ear hook version Velight, headband version So g / 1.76 oz Velight, headband version So g / 1.76 oz Velight, headband version So g / 1.76 oz Velight, headband version Velight, headband version So g / 1.76 oz Velight, headband version Velight velight Nelight Velight veli							
Storage temperature range Storage temperature range Weight, ear hook version Weight, headband version Storage temperature ange Weight, headband version Storage temperature ange Storage temperature range Weight, headband version Storage temperature ange Storage temperature range Weight, headband version Storage temperature ange Storage temperature range Storage time of sioht Storage line of sight Storage line of							
Weight, ear hook version Weight, headband version So g / 1.76 oz Ear pad size Battery (Lithium Polymer) Personalization Range - line of sight Range - line of sight Range - line of sight Automatic power adjustment Talk time in Narrowband Mode Stand by time Auto - headset OFF when out of range Charge time 0 - 50% Charge time 0 - 50% Charge time 0 - 50% Charge time 0 - 100% Package dimensions (H x W x D) Package weight Master carton dimensions (H x W x D) Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content - 20 °C to + 70 °C (-4 °F to + 158 °F) 24 g / 0.86 oz 24 g / 0.86 oz 24 g / 0.86 oz 35 (4 g / 0.86 oz 35 (3 g / 1.76 oz 35 (3 g / 1.76 oz 36 (3 eu les user manual) 26 (see User manual) 27 ex with nameplate on headset 38 manual) 28 ves with nameplate on headset 38 manual) 48 ves (distance between headset and base) 39 to 18 to 19 t		+5 °C to + 15 °C (+11 °E	to +113 °F)				
Weight, ear hook version 24 g / 0.86 oz Weight, headband version 50 g / 1.76 oz Ear pad size 950 mm / 1.96 in Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – in typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Nirarowand Mode Up to 8 hours Talk time in Nirarowand Mode Up to 12 hours Stand by time Up to 100 Hours Auto – headset OFF when out of range Charge time 0 – 50% 20 minutes Charge time 0 – 50% 20 minutes Charge time 0 – 100% 1 hour Package dimensions (H x W x D) Askage weight 940 g / 32.9 oz Master carton dimensions (H x W x D) Asker carton weight 8.85 kg / 19.51 lb Safety Delivery content YES → ActiveGard® Pelivery content 24 g / 0.86 oz 95 m / 1.76 oz Expandus (See User manual) Expandus							
Weight, headband version 50 g / 1.76 oz Ear pad size ø 50 mm / 1.96 in Battery (Lithium Polymer) Exchangeable for service (see User manual) Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – in typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Wideband Mode Up to 8 hours Talk time in Narrowband Mode Up to 12 hours Stand by time Up to 100 Hours Auto – headset OFF when out of range charge time 0 – 50% 20 minutes Charge time 0 – 100% 1 hour Package ing 1 hour Package weight 940 g / 32.9 oz Units in distributor master carton 8 Master carton dimensions (H x W x D) 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in Master carton weight 8.85 kg / 19.51 lb Safety YES → ActiveGard® Protection YES → Activation by dip switch EU/AUS Limiter depending on regional variant YES → Activation by dip switch Delivery content YES → Activation by dip switch			0 1130 1)				
Ear pad size		3 ·					
Battery (Lithium Polymer) Personalization Range – line of sight Range – line of sight Automatic power adjustment Talk time in Wideband Mode Talk time in Narrowband Mode Talk time in Narrowband Mode Auto – headset OFF when out of range Charge time 0 – 50% Charge time 0 – 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton wiight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content Personalization 180 m / 590 ft 180							
Personalization Yes with nameplate on headset Range – line of sight 180 m / 590 ft Range – in typical office building 55 m / 180 ft Automatic power adjustment Yes (distance between headset and base) Talk time in Wideband Mode Up to 8 hours Talk time in Narrowband Mode Up to 12 hours Stand by time Up to 100 Hours Auto – headset OFF when out of range Charge time 0 – 50% 20 minutes Charge time 0 – 100% 100 Hour Package dimensions (H x W x D) 16.5 cm x 16 cm x 16 cm Package weight 940 g / 32.9 oz Units in distributor master carton 8 8 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in Master carton weight 8.85 kg / 19.51 lb Safety Automatic Acoustic Shock Protection Full Acoustic Shock Protection Fegional variant Delivery content Yes with nameplate on headset 180 m / 590 ft 180 m /							
Range – line of sight Range – in typical office building Automatic power adjustment Talk time in Wideband Mode Talk time in Narrowband Mode Up to 12 hours Stand by time Auto – headset OFF when out of range Charge time 0 – 50% Charge time 0 – 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content 180 m / 590 ft 180 m / 190 ft 190 m / 190 ft 190 m / 1	• • • • • • • • • • • • • • • • • • • •						
Range – in typical office building Automatic power adjustment Talk time in Wideband Mode Talk time in Narrowband Mode Stand by time Auto – headset OFF when out of range Charge time 0 – 50% Charge time 0 – 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content Yes w after 30 minutes Up to 100 Hours Ves w after 30 minutes 20 minutes 21 hour 24 hour 25 minutes 26 minutes 27 minutes 28 minutes 29 minutes 29 minutes 20 minutes 20 minutes 20 minutes 20 minutes 20 minutes 21 hour 21 hour 22 minutes 23 minutes 24 minutes 25 minutes 26 minutes 27 minutes 28 minutes 29 minutes 20 minutes 20 minutes 20 minutes 20 minutes 20 minutes 21 hour 21 hour 22 minutes 23 minutes 24 minutes 25 minutes 26 minutes 27 minutes 28 minutes 29 minutes 20 minutes 21 hour 21 hour 22 minutes 21 hour 22 minutes 23 minutes 24 minutes 24 minutes 25 minutes 26 minutes 27 minutes 28 minutes 28 minutes 28 minutes 29 minutes 20 minutes 21 hour 21 hour 22 minutes 22 minutes 23 minutes 24 minutes 24 minutes 24 minutes 25 minutes 26 minutes 26 minutes 27 minutes 28 minutes 28 minutes 29 minutes 20 minut			eadset				
Automatic power adjustment Talk time in Wideband Mode Talk time in Narrowband Mode Up to 12 hours Stand by time Up to 100 Hours Auto - headset OFF when out of range Charge time 0 - 50% Charge time 0 - 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Ves (distance between headset and base) Up to 10 hours Up to 10 Hours Ves ■ after 30 minutes 20 minutes 1 hour 16.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 940 g / 32.9 oz 940 g / 32.9 oz 956 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 8.85 kg / 19.51 lb 8.85 kg / 19.51 lb 8.85 kg / 19.51 lb 8.85 x ActiveGard® YES ■ ActiveGard® YES ■ Activation by dip switch regional variant Delivery content			180 m / 590 ft				
Talk time in Wideband Mode Talk time in Narrowband Mode Stand by time Auto - headset OFF when out of range Charge time 0 - 50% Charge time 0 - 100% Tackaging Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content Up to 12 hours Up to 100 Hours Ves → after 30 minutes 20 minutes 20 minutes 10 hour 16.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 940 g / 32.9 oz 940 g / 32.9 oz 950 y 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 885 kg / 19.51 lb 950 y 450							
Talk time in Narrowband Mode Stand by time Auto – headset OFF when out of range Charge time 0 – 50% Charge time 0 – 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content Ves → after 30 minutes 20 minutes 21 hour 21 hour 22 minutes 23 minutes 24 minutes 25 minutes 26 minutes 26 minutes 26 minutes 27 minutes 28 minutes 29 minutes 20 minutes 20 minutes 20 minutes 21 hour 20 minutes 21 hour 21 hour 22 minutes 22 minutes 23 minutes 24 minutes 24 minutes 25 minutes 26 minutes 26 minutes 27 minutes 28 minutes 29 minutes 20 minutes 20 minutes 20 minutes 20 minutes 20 minutes 21 hour 20 minutes 21 hour 21 hour 22 minutes 22 minutes 23 minutes 24 minutes 24 minutes 25 minutes 26 minutes 27 minutes 28 minutes 29 minutes 20 minutes 21 hour 21 minutes 22 minutes 22 minutes 22 minutes 23 minutes 24 minutes 24 minutes 24 minutes 25 minutes 26 minutes 27 minutes 28 minutes 28 minutes 29 minutes 20 minutes 20 minutes 20 minutes 21 hour 21 minutes 21 minutes 22 minutes 22 minutes 23 minutes 24 minutes 24 minutes 24 minutes 25 minutes 26 minutes 26 minutes 27 minutes 28 minutes 20 minutes 21 hour 21 minutes 22 minutes 21 minutes 22 minutes 22 minutes 22 minutes 23 minutes 24 minutes 24 minutes 24 minutes 24 minutes 24 minutes 25 minutes 26 minutes 26 minutes 26 minutes 27 minutes 28 minutes 28 minutes 20 minutes 20 minutes 20 minutes 21 minutes 21 minutes 21 minutes 22 minutes 21 minutes 22 minutes 23 minutes 24			eadset and base)				
Stand by time Auto – headset OFF when out of range Charge time 0 – 50% Charge time 0 – 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content Up to 100 Hours Yes → after 30 minutes 20 minutes 20 minutes 21 hour 16.5 cm x 16 cm x 16 cm 24 cm x 16 cm 25 cm x 16 cm x 16 cm 26 cm x 16 cm 27 cm x 16 cm 27 cm x 16 cm 28 cm x 14.18 x 14.97 x 14.97 in 88.85 kg / 19.51 lb 96 cm x 14.18 x 14.97 x 14.97 in 97 cm x 14.18 x 14.97 x 14.97 in 98 cm x 14.18 x 14.97 x 14.97 in 98 cm x 14.18 x 14.97 x 14.97 in 98 cm x 14.18 x 14.97 x 14.97 in 98 cm x 14.18 x 14.97 x 14.97 in 98 cm x 14.18 x 14.97 x 14.97 in 98 cm x 14.18 x 14.97 x 14.97 in 98 cm x 14.18 x 14.97 x 14.97 in 98 cm x 14.18 x 14.97 x 14.97 in 99 cm x 14.18 x 14.97 x 14.97 in 99 cm x 14.18 x 14.97 x 14.97 in 99 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14.97 x 14.97 in 90 cm x 14.18 x 14							
Auto – headset OFF when out of range Charge time 0 – 50% Charge time 0 – 100% Packaging Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content Yes → after 30 minutes 20 minutes 1 hour 16.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 4 hour 16.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 1 hour 16.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 18.85 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 18.85 kg / 19.51 lb Safety YES → ActiveGard® YES → ActiveGard® YES → Activation by dip switch							
Charge time 0 - 50% Charge time 0 - 100% Packaging Package dimensions (H x W x D) Package weight Package weight Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content 20 minutes 1 hour 16.5 cm x 16 cm							
Charge time 0 – 100%1 hourPackaging16.5 cm x 16 cm x 16 cmPackage weight940 g / 32.9 ozUnits in distributor master carton8Master carton dimensions (H x W x D)36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 inMaster carton weight8.85 kg / 19.51 lbSafetyYES → ActiveGard®Automatic Acoustic Shock ProtectionYES → Activation by dip switchEU/AUS Limiter depending on regional variantYES → Activation by dip switchDelivery contentYES → Activation by dip switch		Yes ➡ after 30 minutes					
Package dimensions (H x W x D) Package weight Units in distributor master carton Master carton dimensions (H x W x D) Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content 16.5 cm x 16 cm 940 g / 32.9 oz 940 g / 32							
Package dimensions (H x W x D) Package weight 940 g / 32.9 oz Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content 16.5 cm x 16 cm x 16 cm 940 g / 32.9 oz 8 40 g / 32.9 oz 8 56 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 8.85 kg / 19.51 lb 8.85 kg / 19.51 lb YES → ActiveGard® YES → ActiveGard® YES → Activation by dip switch		1 hour					
Package weight 940 g / 32.9 oz Units in distributor master carton 8 Master carton dimensions (H x W x D) 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in Master carton weight 8.85 kg / 19.51 lb Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content 940 g / 32.9 oz 8 YES ⇒ Active Gard on the switch of the switc		16.5 16					
Units in distributor master carton Master carton dimensions (H x W x D) Master carton weight Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content 8 36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 in 8.85 kg / 19.51 lb 8 YES → ActiveGard® YES → ActiveGard® YES → Activation by dip switch							
Master carton dimensions (H x W x D)36 x 38 x 38 cm / 14.18 x 14.97 x 14.97 inMaster carton weight8.85 kg / 19.51 lbSafetyYES → ActiveGard®ProtectionYES → Activation by dip switchEU/AUS Limiter depending on regional variantYES → Activation by dip switchDelivery contentYES → Activation by dip switch							
Master carton weight 8.85 kg / 19.51 lb Safety Automatic Acoustic Shock Protection YES → ActiveGard® EU/AUS Limiter depending on regional variant YES → Activation by dip switch Delivery content YES → Activation by dip switch			.1407 v 140 7 i				
Safety Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content PYES → ActiveGard® YES → Activation by dip switch							
Automatic Acoustic Shock Protection EU/AUS Limiter depending on regional variant Delivery content YES → ActiveGard® YES → Activation by dip switch		8.85 Kg / 19.51 lb					
Protection EU/AUS Limiter depending on regional variant Delivery content Protection YES → Activation by dip switch		V/56 . A !! - 6 . !®					
EU/AUS Limiter depending on regional variant Delivery content YES → Activation by dip switch		YES ActiveGard ActiveGard ActiveGard					
regional variant Delivery content		VES *** Activation by din c	witch				
Delivery content		Activation by dip s	WIECH				
·							
		nd distance h <u>older)</u>					

- Base Station
- USB cable


- Power supply
 Audio phone cable
 Headband (detachable)
- 1 ear hook adapter with pre-mounted ear hook with leatherette sleeve and earbud size S
 Name plate holder for headband and name plate instruction
- Extra earbuds size M and L
- Printed Quick Guide
- Printed Safety Guide

Product Information

Accessories						
	Order name	Art. No	EAN No.	UPC No.		
EHS Alcatel-Lucent adapter	CEHS-AL 01	504102	40 44155 047400	6 15104 17422 1		
EHS Avaya adapter	CEHS-AV 03	504536	40 44155 081671	6 15104 23371 3		
EHS Avaya adapter	CEHS-AV 04	504589	40 44155 087987	6 15104 24686 7		
EHS Avaya adapter	CEHS-AV 05	506037	40 44155 090291	6 15104 25053 6		
EHS Cisco adapter	CEHS-CI 01	504103	40 44155 047417	6 15104 17423 8		
EHS Cisco adapter	CEHS-CI 02	504533	40 44155 080230	6 15104 23183 2		
EHS Cisco adapter	CEHS-CI 03	506038	40 44155 090307	6 15104 25054 3		
EHS DHSG adapter	CEHS-DHSG	504105	40 44155 047431	6 15104 17425 2		
EHS Polycom adapter	CEHS-PO 01	504104	40 44155 047424	6 15104 17424 5		
EHS Shore Tel adapter	CEHS-SH 01	504590	40 44155 088038	6 15104 24692 8		
EHS Snom adapter	CEHS-SN 01	504101	40 44155 047394	6 15104 17408 5		
EHS Snom adapter	CEHS-SN 02	504188	40 44155 074574	6 15104 22297 7		
Headset Charger	CH 10	504366	40 44155 050998	6 15104 18053 6		
landset Lifter	HSL 10	500712	40 44156 012384	6 15104 11795 2		
Fixation kit for Handset Lifter	Fixation kit - HSL10	504032	40 44155 046984	6 15104 17342 2		
Neckband*	NB 20	506525	40 44155 209044	6 15104 27272 9		
nterface box for AEI EHS	TCI 01	500275	40 44156 001913	6 15104 10232 3		
Mobile phone adaptor	CEHS-MB 01	506033	40 44155 089165	61 5104 24889 2		
Multi USB Power Source	MCH 7	504348	40 44155 050820	6 15104 18030 7		
Spare Headset Charger - USB	CH 10 USB	504365	40 44155 051001	6 15104 18055 0		
Audio cable - RJ45-RJ11	RJ45-RJ11-audio cable	506094	40 44155 096187	61 5104 26002 3		
Audio cable - RJ45-2.5mm	RJ45-2.5mm-audio cable	506467	40 44155 098839	61 5104 26371 0		
Single components						
	Order name	Art. No	EAN No.	UPC No.		
Single headset of DW 10	DW 10 HS	504324	40 44155 050585	6 15104 17992 9		
DW Base set for DW ML series (EU)	DW BS ML - EU	504478	40 44155 052121	6 15104 18217 2		
DW Base set for DW ML series (UK)	DW BS ML - UK	504480	40 44155 052145	6 15104 18219 6		
DW Base set for DW ML series (US)	DW BS ML - US	504479	40 44155 052138	6 15104 18218 9		
DW Base set for DW ML series (AUS)	DW BS ML - AUS	504481	40 44155 052152	6 15104 18220 2		
NOTE: Headset and base station can be purchased separately. This allows a 2nd headset to be added to any DW Series base station or used as a spare. Base including power supply, audio cable and USB cable.						
Enaro narte						

Spare parts				
	Order name	Art. No	EAN No.	UPC No.
Audio cable RJ45 – RJ9	RJ45 - RJ9 - DW	504364	40 44155 050981	6 15104 18052 9
Ear hook with leatherette sleeve and earbuds (size S, M, L)	EH 20	506523	40 44155 209020	6 15104 27270 5
Ear hook with leatherette sleeve, click-on adapter and earbuds (size S, M, L)	HSA 20	506524	40 44155 209037	6 15104 27271 2
Ear pad	HZP 25 DW 10	504349	40 44155 050837	6 15104 18031 4
Headband	SHS 02 DW 10 spare	504344	40 44155 050783	6 15104 18024 6
Name plate set	Name plate set, DW 10	504353	40 44155 050875	6 15104 18036 9
Power supply US	UNI PS US 01	92893	40 12418 928933	6 15104 92893 0
Power supply AUS	UNI PS AUS 01	520334	40 44156 023083	6 15104 13459 1
Power supply UK	UNI PS UK 01	92892	40 12418 928926	6 15104 92892 3
Power supply EU	UNI PS EU 01	94707	40 12418 947071	6 15104 94707 8
Spare battery	DW BATT 03	504374	40 44155 051087	6 15104 18067 3
USB cable	USB cable - DW	504363	40 44155 050974	6 15104 18051 2

 $^{{}^{\}star} \text{ Requires the click-on adapter provided with DW Office products with FlexFit}{}^{\text{\tiny{TM}}} \text{ system or the HSA 20 accessory set}$



Experience Sennheiser

Perfection is always relative: Users have different expectations from their headsets and speakerphones depending on their needs. For professional users, that need is to communicate as effectively as possible.

With Sennheiser's range of headsets and speakerphones, the combination of exceptional HD sound, quality design and build – and a focus on real life usability – give the best performance possible in busy offices, call centers and Unified Communications environments.

Please visit us at: www.sennheiser.com/cco



Sennheiser is one of the world's leading manufacturers of headphones, microphones, wireless transmission systems and high-quality headsets for both business and entertainment.

Drawing on the electro acoustics expertise of Sennheiser and the leading hearing healthcare specialist William Demant, Sennheiser Communications' wireless and wired headsets and speakerphones for contact centers, offices and Unified Communications professionals are the result of Sennheiser's and William Demant's joint leadership in sound quality, design, wearing comfort and hearing protection.

For further information, please visit: www.sennheiser.com/cco

Sennheiser Communications A/S

Industriparken 27 · DK-2750 Ballerup · Denmark