



TEGERA® 335

Leather glove, winter-lined, 0,6-0,7 mm full grain goatskin, nylon, fleece, Cat. II, black, white, green, reinforced index finger, reinforced fingers and thumb, Velcro®, for precision work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good grip, good fit, comfortable, warm

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,6-0,7 mm

BACK MATERIAL Nylon

LINING Winter-lined

LINING MATERIAL Fleece

DEXTERITY 2

FASTENING Velcro®

LENGTH RANGE 220-270 mm

COLOUR Black, white, green

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag

OUTER MATERIAL SPECIFICATION Leather 50%, nylon 49%, natural latex 1%

INNER MATERIAL SPECIFICATION Polyester 100%

1(3)



TEGERA® 335

FEATURES

Reinforced index finger, reinforced fingers and thumb, specially designed details

PRIMARY PROTECTION

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cold environments

PRIMARY AREAS OF USE

Machine operating, building and construction, carpentry, installation work, construction, soil preparation, transport work, machine driving, airport work, wood industry work, repair work, sanitation, cleaning, service work



PRIMARY INDUSTRIES OF USE

Automotive, transportation, building and construction, service, retail

TYPE OF WORK

Light weight

CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-11-16

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 335

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	1	(4)
D) Puncturing resistance (Newton)	1	(4)



EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

EN 511:2006 Protective gloves against cold



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-11-16

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com