



1(3)

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 884

FEATURES

Water and oil repellent palm

PRIMARY PROTECTION

Prevents risk of, abrasion injuries, grazes, scratches, lacerations, contact with dirt, contact with damp, contact with oil, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Slippery environments, wet environments, moist environments, oil and greasy environments, dirty environments

PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, machine operating, building and construction, carpentry, painting, installation work, electrical installation, HVAC installation, sheet-metal work, tiling, construction, soil preparation, concrete work, engineering, transport work, machine driving, warehouse work, airport work, mining, wood industry work, forest work, agricultural work, gardening, repair work

PRIMARY INDUSTRIES OF USE


Agriculture, mining, oil, gas, petrochemical, automotive, transportation, utilities, building and construction

TYPE OF WORK

Light weight



 Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-11-17

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 884

EC TYPE EXAMINATION

Notified Body: 0321 SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom

COMPLIANCE DESCRIPTION

EN 420:2003 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	4	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	4	(4)
D) Puncturing resistance (Newton)	1	(4)


EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

CONFIDENCE IN TEXTILES Tested for harmful substances according to Oeko-Tex® Standard 100



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.