



CRF[®]

TEGERA[®] 910

Cut resistant glove, CRF[®] Technology, glass fibre thread, polyester, 13 gg, cut resistance level 5, cut resistance level C, Cat. II, orange high-viz, high-viz colour, for allround work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good fit, comfortable, light

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (COUP) Cut resistance level 5

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 12,9

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

LINER MATERIAL CRF[®] Technology, glass fibre thread, polyester, 13 gg

DEXTERITY 5

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

LENGTH RANGE 220-270 mm

COLOUR Orange high-viz

PAIRS PER PACKAGE/CARTON 12/120


DISPLAY Bag with euro slot

MATERIAL SPECIFICATION HPPE 70%, glass fibre thread 13%, polyester 5%, natural latex 4%

1(3)



CE Cat. II



TEGERA® 910

FEATURES

Cut resistant according to EN 388:2003 level 5, cut resistant according to 388:2016 level C, high-viz colour, soft, thin

PRIMARY PROTECTION

Prevents risk of, cut injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, dry environments, clean environments

PRIMARY AREAS OF USE

Assembly, inspection work, sheet-metal work, engineering, metalwork, glass industry work, repair work

PRIMARY INDUSTRIES OF USE

Glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, service

TYPE OF WORK

Medium weight

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-11-20

TEGERA® 910

EC TYPE EXAMINATION

Notified Body: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07 France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EN 388:2003 Protective gloves against mechanical risks


Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	3	(4)
B) Resistance to cutting (Index)	5	(5)
C) Tear resistance (Newton)	4	(4)
D) Puncturing resistance (Newton)	X	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	



CE Cat. II



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-11-20

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com