

JALAS® 2902 DANIEL

EN ISO 20347:2012, OB A E SRC FO

PROPERTIES

Excellent grip, perfect fit, comfortable, breathable, excellent shock absorption, light

SPECIFICATION

TYPE OF SHOE Occupational footwear, clogs

FITTING Regular 34-47

COLLECTION Gram à la Sara

PLATFORM Gram

UPPER MATERIAL Microfiber

TOECAP MATERIAL Plastic

LINING MATERIAL Polyester, polyamide

SOLE MATERIAL Plastic shank, PU outsole

INSOLE FX2 Pro

INSOLE MATERIAL Textile, soft EVA, double shock absorption zones in Poron® XRD®

FASTENING Velcro®

COLOUR Black, red



The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

JALAS® 2902 DANIEL

FEATURES

Low weight, oil-resistant outsole, anti-static properties, adjustable heel strap, washable in 40° C, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

PRIMARY PROTECTION

Prevents risk of: antistatic

PRIMARY ENVIRONMENTS OF USE

Indoors

PRIMARY AREAS OF USE

Cleaning, kitchen work, hotel- and restaurant work, healthcare, care work, service work, office work, shop work

PRIMARY INDUSTRIES OF USE

HoReCa, service



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD



The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-11-16

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

JALAS® 2902 DANIEL

COMPLIANCE
EN ISO 20347:2012

COMPLIANCE DESCRIPTION

OB: Footwear with no toe protection against mechanical hazards provided but must provide protection to one or more of the categories P, C, A, E, CI, I, AN, WR or HI

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms)

E: Energy absorption in the heel area (tested at 20 Joules)

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm



CE



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD



The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2017-11-16

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com