



Type II environmental label:
self-declared environmental claim

25084 MYDO Silent optical mouse

Issue Date

2024-07-05

Owner of Declaration

Trust

According to

ISO14021:2016 and EN50693

General information

Company

Manufacturer	Trust International B.V.
Production location	Shenzhen, China
Company address	Laan van Barcelona 600, 3317 DD Dordrecht, The Netherlands
Website	https://www.trust.com/

Self-declared environmental claim

This self-declared environmental claim is drawn up to quantify the environmental impact of one unit. The environmental impact is studied by a Life Cycle Assessment (LCA). The LCA and this declaration are not externally verified.

The disclosed environmental information is in the form of a type II environmental label, a self-declared environmental claim in line with ISO 14021 [1] and EN 50693 [2]. The template for this type II environmental label is set up by Hedgehog Company, while the product and environmental information is filled out by Trust.

Environmental label information

Product name	MYDO Silent optical mouse
Product ID	25084
Related Product ID(s)	-
PCR	EN 50693
Software	Mobius v 1.1.1
Background database	Ecoinvent v3.8
Impact assessment method	EF 3.0 Method (Ecoinvent v3.8 cut-off)

Product description

Wireless computer mouse, made of plastic, and using disposable batteries. It is used in private and business settings, and is available in multiple colours.

Size (height x width x depth)	Total weight	Power source
104x70x35 mm	84 g	disposable batteries (AA)

The product does not contain material content of substances of very high concern (SVHC).

Functional unit

The function studied in this EPD is that of transmitting information to a computer by controlling the movement of a computer mouse.

Scope of declaration

This is a cradle-to-grave type II environmental label for the MYDO Silent optical mouse. The life cycle stages are shown as below (x = included, ND = non declared).

Manufacturing stage	Distribution stage	Installation stage	Use stage	De-installation stage	End-of-life stage
x	x	ND	x	ND	x

Calculation rules

The method used to quantify the environmental performance of the product in question is the life cycle assessment (LCA) regulated by ISO 14040 and ISO 14044. Process data over the year of 2023 is used to model the product system. Ecoinvent v3.8 is used as a background database.

Manufacturing

The inventoried data used to model the MYDO Silent optical mouse is collected from Trust International B.V. Transport to the production site is calculated based on collected information from product suppliers. Coverage of the product manufacturing includes the necessary energy inputs for product assembly, and manufacturing waste. Manufacturing waste is assumed to be incinerated completely, without energy recovery. Further energy inputs and data on the generated manufacturing waste are collected from the product manufacturer.

Table 1. Recycled content of the MYDO Silent optical mouse.

Component	Material	Recycled content %
Main housing	ABS plastic	85% PCR
Various small parts	ABS plastic	-
Lens	PC plastic	-
Scrollwheel	PC plastic	-
PCB	PCB	-
Screws	Carbon steel	-
Protective bag	PE	-
Package	Carton	70%
User manual	Paper	-

Distribution

After the production stage, the products are prepared for shipping to the Netherlands. The final products are transported by truck to the Port of Shenzhen. Further transport is by oceanic containers to the Port of Rotterdam. After docking of the ship, the products are further transported to the Trust distribution center in 's-Heerenberg. Approximately 85% of the products are transported by truck, while 15% is transported by barge. Final transport to the end-user of the products is based on default transport values according to EN 50693, which is 1.000 kilometers for local transport.

Final transport to the end-user of the products is based on default transport values according to EN 50693, which is 1.000 kilometres for local transport.

Use stage

The use stage includes the energy consumption and other flows (emissions, water, etc.) of the product during its use over the RSL. The Reference Service Life (RSL) of the product is five years. Total energy use is 5 years x 2,6 batteries/year = 13 batteries + power for USB dongle 0,182 kWh. Production, distribution, installation, end-of-life of materials or energy aimed at extending the product lifetime, like maintenance and repair are included when relevant.

End-of-life

The end-of-life stage starts with waste collection. The transport distance to the waste treatment facilities is assumed to be 1.000 kilometres, in accordance with EN 50693. Moreover, this study uses the default values for end-of-life treatment in accordance with EN 50693. For materials that are not included in this standard, appropriate waste treatment scenarios are selected.

The end-of-life steps start after the de-installation and include:

- Collection, transport and storage
- De-pollution
- Fractions separation and preparation (e.g. dismantling, crushing, sorting processes)
- Material recovery processes (metallurgical, chemical processes)
- Energy recovery processes (incineration with energy recovery, use as solid recovered fuel)
- Disposal (incineration without energy recovery, landfill)

The end-of-life stage ends at the disposal or the point of substitution.

In line with the EN 50693 Annex G formula without benefits, this study excludes system expansion and does not account for benefits beyond the system boundary. Thus, the impacts of the energy and material recovery operations are not included in the end-of-life stage of this product system.

Table 2. Applied values for the end-of-life modelling of the MYDO Silent optical mouse.

Material	Incineration (g)	Recycling (g)
ABS	50,48	12,62
Battery	19,32	57,93
Carton	5,17	37,93
PCB	6,63	1,17
Steel	0,02	0,08

Environmental impact per declared unit

Table 3. Environmental impact for the MYDO Silent optical mouse.

Impact category	Unit	Manufacturing	Distribution	Use	End-of-life	Total
AP	mol H ⁺ eq	1,19E-02	9,71E-04	8,98E-02	5,99E-04	1,03E-01
GWP100	kg CO ₂ eq	8,62E-01	5,95E-02	1,47E00	2,09E-01	2,60E00
GWP-b	kg CO ₂ eq	4,30E-03	1,96E-05	1,52E-02	2,14E-02	4,10E-02
GWP-f	kg CO ₂ eq	8,56E-01	5,94E-02	1,46E00	1,87E-01	2,56E00
GWP-luluc	kg CO ₂ eq	2,06E-03	2,92E-05	2,01E-03	6,55E-05	4,17E-03
ETP-fw	CTUe	7,44E01	6,42E-01	3,14E02	3,23E00	3,92E02
EP-fw	kg P eq	8,87E-05	3,94E-07	1,47E-04	2,30E-06	2,39E-04
EP-m	kg N eq	1,03E-03	2,62E-04	2,48E-03	7,08E-05	3,84E-03
EP-T	mol N eq	1,18E-02	2,90E-03	3,15E-02	7,34E-04	4,69E-02
HTP-c	CTUh	1,42E-09	2,92E-11	8,94E-09	6,93E-11	1,05E-08
HTP-nc	CTUh	4,07E-08	6,86E-10	1,70E-07	1,98E-09	2,13E-07
IR	kBq U-235 eq	3,99E-02	3,69E-03	8,63E-02	2,37E-03	1,32E-01
SQP	Pt	5,22E00	4,99E-01	4,26E00	2,09E-01	1,02E01
ODP	kg CFC11 eq	5,81E-08	1,30E-08	1,01E-07	3,45E-09	1,75E-07
PM	disease inc.	5,37E-08	4,70E-09	1,62E-07	4,77E-09	2,25E-07
POCP	kg NMVOC eq	4,28E-03	7,73E-04	1,23E-02	2,22E-04	1,76E-02
ADP-f	MJ	1,15E01	8,51E-01	1,88E01	5,95E-01	3,17E01
ADP-mm	kg Sb eq	4,66E-04	1,10E-06	4,12E-03	6,45E-06	4,60E-03
WDP	m ³ depriv.	3,08E-01	2,14E-03	7,87E-01	3,56E-02	1,13E00

GWP100 = Climate change; **GWP-f** = Climate change - fossil; **GWP-b** = Climate change - biogenic; **GWP-luluc** = Climate change - Land use and LU change; **ODP** = Ozone depletion; **HTP-c** = Human toxicity, cancer; **HTP-nc** = Human toxicity, non-cancer; **PM** = Particulate matter; **IR** = Ionising radiation; **POCP** = Photochemical ozone formation; **AP** = Acidification; **EP-T** = Eutrophication, terrestrial; **EP-m** = Eutrophication, marine; **EP-fw** = Eutrophication, freshwater; **ETP-fw** = Ecotoxicity, freshwater; **SQP** = Land use; **WDP** = Water use; **ADP-f** = Resource use, fossils; **ADP-mm** = Resource use, minerals and metals

References

[1] ISO 14021: Environmental labels and declarations — Self-declared environmental claims (Type II environmental labelling)', International Organization for Standardization, ISO14021:2016.

[2] NEN-EN 50693: Product category rules for life cycle assessments of electronic and electrical products and systems, NEN-EN:50693:2019