



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

Pattex Repair 100% universal adhesive

SDS No. : 528149
V003.0

Revision: 20.05.2021
printing date: 24.09.2021

Replaces version from: 06.06.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Pattex Repair 100% universal adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Reaction adhesives

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

Fax-no.: +44 (1442) 278071

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information

Contains: N-(3-(Trimethoxysilyl)propyl)ethylenediamine May produce an allergic reaction.

Precautionary statement:

P102 Keep out of reach of children.

2.3. Other hazards

Evolves methanol during cure.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General chemical description:**

Adhesive

Base substances of preparation:

Reaction product of: Silane & Polyole

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Benzene, C10-13-alkyl derivs. 67774-74-7	267-051-0 01-2119489372-31	10- < 20 %	Asp. Tox. 1 H304
Trimethoxyvinylsilane 2768-02-7	220-449-8 01-2119513215-52	1- < 5 %	Flam. Liq. 3 H226 Acute Tox. 4; Inhalation H332 STOT RE 2 H373 Skin Sens. 1B H317
Dioctyltin dilaurate 3648-18-8	222-883-3 01-2119979527-19	0,1- < 0,3 %	Repr. 1B H360D STOT RE 1 H372 ===== EU REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	217-164-6 01-2119970215-39	0,1- < 1 %	Skin Sens. 1 H317 Eye Dam. 1 H318 Acute Tox. 4; Inhalation H332 STOT RE 2; Inhalation H373

For full text of the H - statements and other abbreviations see section 16 "Other information".**Substances without classification may have community workplace exposure limits available.****SECTION 4: First aid measures****4.1. Description of first aid measures****General information:**

In case of adverse health effects seek medical advice.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:
Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Danger of slipping on spilled product.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure that workrooms are adequately ventilated.

Avoid skin and eye contact.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Temperatures between + 5 °C and + 35 °C

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Reaction adhesives

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Diocetyl tin dilaurate 3648-18-8 [TIN COMPOUNDS, ORGANIC, EXCEPT CYHEXATIN (ISO), (ASSN)]		0,1	Time Weighted Average (TWA):		EH40 WEL
Diocetyl tin dilaurate 3648-18-8 [TIN COMPOUNDS, ORGANIC, EXCEPT CYHEXATIN (ISO), (ASSN)]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Diocetyl tin dilaurate 3648-18-8 [TIN COMPOUNDS, ORGANIC, EXCEPT CYHEXATIN (ISO), (ASSN)]		0,2	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS]		2,4	Time Weighted Average (TWA):		IR_OEL
Diocetyl tin dilaurate 3648-18-8 [TIN, ORGANIC COMPOUNDS]		0,2	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
Diocetyl tin dilaurate 3648-18-8 [TIN, ORGANIC COMPOUNDS]		0,1	Time Weighted Average (TWA):	Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Benzene, C10-13-alkyl derivs. 67774-74-7	aqua (freshwater)		0,001 mg/l				
Benzene, C10-13-alkyl derivs. 67774-74-7	aqua (marine water)		0 mg/l				
Benzene, C10-13-alkyl derivs. 67774-74-7	sewage treatment plant (STP)		14,2 mg/l				
Benzene, C10-13-alkyl derivs. 67774-74-7	sediment (freshwater)				1,65 mg/kg		
Benzene, C10-13-alkyl derivs. 67774-74-7	sediment (marine water)				0,165 mg/kg		
Benzene, C10-13-alkyl derivs. 67774-74-7	Soil				0,329 mg/kg		
Benzene, C10-13-alkyl derivs. 67774-74-7	aqua (intermittent releases)		0 mg/l				
Trimethoxyvinylsilane 2768-02-7	aqua (freshwater)		0,4 mg/l				
Trimethoxyvinylsilane 2768-02-7	aqua (marine water)		0,04 mg/l				
Trimethoxyvinylsilane 2768-02-7	freshwater - intermittent		1,21 mg/l				
Trimethoxyvinylsilane 2768-02-7	sediment (freshwater)				1,5 mg/kg		
Trimethoxyvinylsilane 2768-02-7	sediment (marine water)				0,15 mg/kg		
Trimethoxyvinylsilane 2768-02-7	Soil				0,06 mg/kg		
Diocetyl tin dilaurate 3648-18-8	aqua (freshwater)					0,0018 µg/l	
Diocetyl tin dilaurate 3648-18-8	aqua (marine water)					0 µg/l	
Diocetyl tin dilaurate 3648-18-8	sewage treatment plant (STP)		100 mg/l				
Diocetyl tin dilaurate 3648-18-8	sediment (freshwater)				0,02798 mg/kg		
Diocetyl tin dilaurate 3648-18-8	sediment (marine water)				0,002798 mg/kg		
Diocetyl tin dilaurate 3648-18-8	Soil				0,005593 mg/kg		
Diocetyl tin dilaurate 3648-18-8	oral				0,02 mg/kg		
Diocetyl tin dilaurate 3648-18-8	aqua (intermittent releases)		0,000018 mg/l				
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	aqua (freshwater)		0,062 mg/l				
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	aqua (marine water)		0,0062 mg/l				
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	aqua (intermittent releases)		0,62 mg/l				
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	sediment (freshwater)				0,22 mg/kg		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	sediment (marine water)				0,022 mg/kg		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Soil				0,0085 mg/kg		
N-(3- (Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	sewage treatment plant (STP)		25 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Benzene, C10-13-alkyl derivs. 67774-74-7	Workers	dermal	Long term exposure - systemic effects		9,6 mg/kg	
Benzene, C10-13-alkyl derivs. 67774-74-7	Workers	inhalation	Long term exposure - systemic effects		7 mg/m ³	
Benzene, C10-13-alkyl derivs. 67774-74-7	Workers	inhalation	Long term exposure - local effects		7 mg/m ³	
Benzene, C10-13-alkyl derivs. 67774-74-7	General population	dermal	Long term exposure - systemic effects		4,8 mg/kg	
Benzene, C10-13-alkyl derivs. 67774-74-7	General population	inhalation	Long term exposure - systemic effects		1,8 mg/m ³	
Benzene, C10-13-alkyl derivs. 67774-74-7	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	
Benzene, C10-13-alkyl derivs. 67774-74-7	General population	inhalation	Long term exposure - local effects		1,8 mg/m ³	
Trimethoxyvinylsilane 2768-02-7	Workers	dermal	Long term exposure - systemic effects		3,9 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	inhalation	Long term exposure - systemic effects		27,6 mg/m ³	
Trimethoxyvinylsilane 2768-02-7	General population	dermal	Long term exposure - systemic effects		7,8 mg/kg	
Trimethoxyvinylsilane 2768-02-7	General population	inhalation	Long term exposure - systemic effects		6,7 mg/m ³	
Trimethoxyvinylsilane 2768-02-7	General population	oral	Long term exposure - systemic effects		0,3 mg/kg	
Diocetyl tin dilaurate 3648-18-8	Workers	inhalation	Long term exposure - systemic effects		0,0035 mg/m ³	
Diocetyl tin dilaurate 3648-18-8	Workers	dermal	Long term exposure - systemic effects		0,05 mg/kg	
Diocetyl tin dilaurate 3648-18-8	General population	inhalation	Long term exposure - systemic effects		0,0009 mg/m ³	
Diocetyl tin dilaurate 3648-18-8	General population	dermal	Long term exposure - systemic effects		0,025 mg/kg	
Diocetyl tin dilaurate 3648-18-8	General population	oral	Long term exposure - systemic effects		0,0005 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	inhalation	Long term exposure - systemic effects		35,3 mg/m ³	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	dermal	Long term exposure - systemic effects		5 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Workers	dermal	Acute/short term exposure - systemic effects		5 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	inhalation	Long term exposure - systemic effects		8,7 mg/m ³	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	General population	oral	Long term exposure - systemic effects		2,5 mg/kg	
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	General population	dermal	Acute/short term exposure -		17 mg/kg	

1760-24-3

systemic effects

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Filter : AX (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

Eye protection:

Goggles which can be tightly sealed.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid high viscosity transparent
Odor	mild
Odour threshold	No data available / Not applicable
pH	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	20 - 55 °C (68 - 131 °F)
Flash point	66,0 °C (150.8 °F); no method
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	No data available / Not applicable
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,10 - 1,16 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity (Brookfield; 40 °C (104 °F); Conc.: 10 ppm)	5.000 - 15.000 mPa.s
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

Evolves methanol during cure.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1. Information on toxicological effects**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Trimethoxyvinylsilane 2768-02-7	LD50	7.120 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Diocetyl tin dilaurate 3648-18-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
N-(3- (Trimethoxysilyl)propyl)ε thylenediamine 1760-24-3	LD50	2.295 mg/kg	rat	EPA OPPTS 870.1100 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Trimethoxyvinylsilane 2768-02-7	LD50	3.200 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Diocetyl tin dilaurate 3648-18-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
N-(3- (Trimethoxysilyl)propyl)ε thylenediamine 1760-24-3	LD50	> 2.000 mg/kg	rat	EPA OPPTS 870.1200 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	LC50	> 1,82 mg/l	dust/mist		rat	not specified
Trimethoxyvinylsilane 2768-02-7	LC50	16,8 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	LC50	1,49 - 2,44 mg/l	dust/mist	4 h	rat	EPA OPPTS 870.1300 (Acute inhalation toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	slightly irritating	4 h	rabbit	not specified
Trimethoxyvinylsilane 2768-02-7	not irritating		rabbit	other guideline:

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	not irritating		rabbit	not specified
Trimethoxyvinylsilane 2768-02-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Diocetyl tin dilaurate 3648-18-8	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Trimethoxyvinylsilane 2768-02-7	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	sensitising	Mouse local lymphnode assay (LLNA)	guinea pig	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EU Method B.13/14 (Mutagenicity)
Benzene, C10-13-alkyl derivs. 67774-74-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Trimethoxyvinylsilane 2768-02-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Trimethoxyvinylsilane 2768-02-7	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Trimethoxyvinylsilane 2768-02-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	NOAEL P \geq 50 mg/kg NOAEL F1 \geq 50 mg/kg NOAEL F2 \geq 50 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Trimethoxyvinylsilane 2768-02-7	NOAEL P 250 mg/kg	one-generation study	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
Trimethoxyvinylsilane 2768-02-7	NOAEL P 1.000 mg/kg	one-generation study	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
Trimethoxyvinylsilane 2768-02-7	NOAEL F1 1.000 mg/kg	one-generation study	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
Dioctyltin dilaurate 3648-18-8	NOAEL P 0,3 - 0,4 mg/kg	screening	oral: feed	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	NOAEL 50 mg/kg	oral: gavage	127 d daily	rat	other guideline:
Trimethoxyvinylsilane 2768-02-7	NOAEL < 62,5 mg/kg	oral: gavage	42d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Trimethoxyvinylsilane 2768-02-7	NOAEL 0,605 mg/l	inhalation: vapour	5 days/week for 14 weeks 6 hours/day	rat	not specified
Dioctyltin dilaurate 3648-18-8	NOAEL 0,3 - 0,4 mg/kg	oral: feed	28 d 28 d/daily (ad libitum)	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

The mixture is classified based on Viscosity data.

Hazardous substances CAS-No.	Viscosity (kinematic) Value	Temperature	Method	Remarks
Benzene, C10-13-alkyl derivs. 67774-74-7	4,23 mm ² /s	40 °C	not specified	

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	LC50	Toxicity > Water solubility	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Benzene, C10-13-alkyl derivs. 67774-74-7	NOEC	Toxicity > Water solubility	14 d	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
Trimethoxyvinylsilane 2768-02-7	LC50	191 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Diocetyl tin dilaurate 3648-18-8	LC50	Toxicity > Water solubility	96 h		OECD Guideline 203 (Fish, Acute Toxicity Test)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	LC50	168 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
Trimethoxyvinylsilane 2768-02-7	EC50	168,7 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
Diocetyl tin dilaurate 3648-18-8	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	EC50	87,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	NOELR	Toxicity > Water solubility	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Trimethoxyvinylsilane 2768-02-7	NOEC	28,1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	NOEC	> 1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	EC50	Toxicity > Water solubility	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Benzene, C10-13-alkyl derivs. 67774-74-7	NOEC	Toxicity > Water solubility	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Trimethoxyvinylsilane 2768-02-7	EC50	> 957 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
Trimethoxyvinylsilane 2768-02-7	NOEC	957 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
Diocetyl tin dilaurate 3648-18-8	NOEC	Toxicity > Water solubility	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC50	8,8 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	NOEC	3,1 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	EC0	Toxicity > Water solubility	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
Trimethoxyvinylsilane 2768-02-7	EC50	> 100 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	EC 50	435 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	readily biodegradable	aerobic	60 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Trimethoxyvinylsilane 2768-02-7	not readily biodegradable.	aerobic	51 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Diocetyl tin dilaurate 3648-18-8	not readily biodegradable.	aerobic	1,9 %	28 day	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
N-(3- (Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3		aerobic	50 %		OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	35	48 h	22 °C	Lepomis macrochirus	other guideline:
Diocetyl tin dilaurate 3648-18-8	< 100	30 day		Salmo irideus	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Benzene, C10-13-alkyl derivs. 67774-74-7	6,4	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol/ water), HPLC Method)
Diocetyl tin dilaurate 3648-18-8	14,56		not specified
N-(3-(Trimethoxysilyl)propyl)ethyl enediamine 1760-24-3	-1,67		not specified

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT/ vPvB
Benzene, C10-13-alkyl derivs. 67774-74-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Trimethoxyvinylsilane 2768-02-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Diocetyl tin dilaurate 3648-18-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
N-(3-(Trimethoxysilyl)propyl)ethylenediamine 1760-24-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080410

SECTION 14: Transport information**14.1. UN number**

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.2. UN proper shipping name

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.3. Transport hazard class(es)

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.4. Packing group

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Dioctyltin dilaurate CAS 3648-18-8
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

EU. REACH, Annex XVII, Marketing and Use Restrictions (Regulation 1907/2006/EC): Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H226 Flammable liquid and vapor.
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H360D May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.